

Machine Learning from Data

Lecture 10: Spring 2021

Today's Lecture

- Non-Linear Transforms
 - Z-Space
 - Polynomial Transforms

Linear Model (Recap)


linear in \mathbf{x} : gives the line/hyperplane separator




$$s = \mathbf{w}^T \mathbf{x}$$




linear in \mathbf{w} : makes the algorithms work



Limits of the Linear Model




(a) Linear with outliers



(b) Essentially nonlinear

To address (b) we need something more than linear.

Many Non-Linear Transforms May Work




Choose Transform before Looking at the data



After constructing features carefully, **before** seeing the data ...

... if you think linear is not enough, try **the 2nd order polynomial transform**.


$$\begin{bmatrix} 1 \\ x_1 \\ x_2 \end{bmatrix} = \mathbf{x} \longrightarrow \Phi(\mathbf{x}) = \begin{bmatrix} 1 \\ \Phi_1(\mathbf{x}) \\ \Phi_2(\mathbf{x}) \\ \Phi_3(\mathbf{x}) \\ \Phi_4(\mathbf{x}) \\ \Phi_5(\mathbf{x}) \end{bmatrix} = \begin{bmatrix} 1 \\ x_1 \\ x_2 \\ x_1^2 \\ x_1x_2 \\ x_2^2 \end{bmatrix}$$



Be Careful with Feature Transforms



Digits Data Again




Average Intensity

Linear model

$$E_{\text{in}} = 2.13\%$$

$$E_{\text{out}} = 2.38\%$$



Average Intensity

3rd order polynomial model

$$E_{\text{in}} = 1.75\%$$

$$E_{\text{out}} = 1.87\%$$

Use the Linear Model!

- First try a linear model – simple, robust and works.
- Algorithms can tolerate error plus you have nonlinear feature transforms.
- Choose a feature transform *before* seeing the data. Stay simple.
Data snooping is hazardous to your E_{out} .
- Linear models are fundamental in their own right; they are also the building blocks of many more complex models like support vector machines.
- Nonlinear transforms also apply to regression and logistic regression.

Thanks!