Machine Learning from Data

Lecture 14: Spring 2021


Today's Lecture


- Three Learning Principles
 - Occam's Razor
 - Sampling Bias 1
 - Data Snooping

Validation and Cross Validation











 $\begin{array}{c} \mathbf{Model} \\ \mathbf{Selection} \end{array}$













use a 'razor' to 'trim down'

"an explanation of the data to make it as simple as possible but no simpler."

Simpler is Better

Ein(1)=0

The simplest model that fits the data is also the most plausible.

Of What is simply?

Of Man do we dive to fit data wow?

...or, beware of using complex models to fit data

What is Simpler?

simple hypothesis h

 $\Omega(h)$

low order polynomial

hypothesis with small weights

easily described hypothesis

:

simple hypothesis set \mathcal{H}

 $\Omega(\mathcal{H})$

 ${\cal H}$ with small $d_{ ext{VC}}$

small number of hypotheses \checkmark

low entropy set

:


The equivalence:

A hypothesis set with **simple** hypotheses must be **small**

Why is simpler better?

- Because you will be more surprised when you fit the data.
- When something unlikely happens, it is very significant when it happens.

A Scientific Experiment






Who provides most evidence for the hypothesis " ρ is linear in T"?

Axiom of Non-Falsifiability

Axiom. If an experiment has no chance of <u>falsifying a hypothesis</u>, then the result of that experiment provides no evidence one way or the other for the hypothesis.



Falsification and $m_{\mathcal{H}}(N)$

If \mathcal{H} shatters $[\mathbf{x}_1, \cdots, \mathbf{x}_N,]$))))))

- Don't be surprised if you fit the data.
- Can't falsify " \mathcal{H} is a good set of candidate hypotheses for f".

If \mathcal{H} doesn't shatter $\mathbf{x}_1, \dots, \mathbf{x}_N$, and the target values are uniformly distributed,

 $\mathbb{P}[\text{falsification}] \ge 1 - \underbrace{m_{\mathcal{H}}(N)}_{2^N}.$

A good fit is surprising with simple \mathcal{H} , hence significant. You can, but didn't falsify " \mathcal{H} is a good set of candidate hypotheses for f"

Learning From Data in General

Ein mall

- We may opt for a simpler fit than possible.
- Imperfect fit with a simpler mode is better than a perfect fit with a more complex model.

Exercise 5.2

Football Dyrde

•



Saturday, Oct 13, 2012

Home team will win the Monday Night Footbal Game.

Morday 1 Morday 2

Prediction Julione 6.h week > 50!

\$50

What did the Oracle Really Do?


Really Do? $\frac{2^{5}-32}{2^{5}-32}$

Ein Earr

Sampling Bias

 If the data is sampled in a biased way, learning will produce a similarly biased outcome.

Sampling Bias



November 3rd 1948, Dewey Defeats Truman

Tribune wanted to show off its latest technology could go earlier to press.

Telephone poll on how people <u>voted</u> statisticians had done their thing and were confident.



Imagine Their Surprise When ...



Telephone poll 7

1978

Out of sample.

Sampling Bias in Learning

If the data is sampled in a biased way, learning will produce a similarly biased outcome.

...or, make sure the training and test distributions are the same.

You cannot draw a sample from one bin and make claims about another bin

Puzzle - Credit Analysis

Selection bias

pridit-> untron

Applied -> divised -> system


- Determine credit given salary, debt, years in residence,
- Banks have lots of data
 - customer information: salary, debt, etc.
 - whether or not **who?** defaulted on their credit.

age	32 years
gender	male
salary	40,000
debt	26,000
years in job	1 year
years at home	3 years

Approve for credit?

only data on approved customers

Issues with Extrapolation



Vet representative of the data


Data Snooping

If a data set has affected any step in the learning process, it cannot be fully trusted in assessing the outcome.

Not Gustworthy

...or, estimate performance with a *completely* uncontaminated test set

 \dots and, choose \mathcal{H} before looking at the data



Data Snooping is a Subtle Happy Hell

- The data looks linear so I will use a linear model, and it worked.

 If the data were different and didn't look linear, would you do something different?
- Try linear, it fails; try circles it works.

 If you torture the data enough, it will confess.

 $d_{vc} = \infty$

- Try <u>linear</u>, it works; so I don't need to try circles.

 Would you have tried circles if the data were different?
- Read papers, see what others did on the data. Modify and improve on that.

 If the data were different, would that modify what others did and hence what you did?


the data snooping can happen all at once or sequentially by different people

• Input normalization: normalize the data, now set aside the test set.

Since the test set was involved in the normalization, wouldn't your g change if the test set changed?

Account for Data Snooping

Ask yourself: "If the data were different, could/would I have done something different?"
if yes, then there is data snooping.



You must account for every choice influenced by \mathcal{D} .

We know how to account for the choice of g from \mathcal{H} .

Three Learning Principles

 Occam's Razor: pick a model carefully ✓ Simpler H is better.

Sampling Bias: generate the data carefuly ✓
 Make sure you train and test from the same bin.

Data Snooping: handle the data carefully ✓
 Account for all choices the data influenced. Choose H before you see the data.

Thanks!