

Uniwersytet Wrocławski
Wydział Matematyki i Informatyki
Instytut Matematyczny
specjalność: Analiza danych

Bartosz Chmiela

Locally-informed proposals in Metropolis-Hastings
algorithm with applications

Praca magisterska
napisana pod kierunkiem
dr hab. Pawła Lorka

Wrocław 2022

Abstract

The Markov Chain Monte Carlo methods (abbrev. MCMC) are a family of algorithms used for sampling from a given probability distribution. They prove very effective when the state space is large. This fact can be used to solve many hard deterministic problems – one of them being *traveling salesmen problem*. It will be used in this thesis to test a new approach of *locally-informed propolsals* as a modification of well known *Metropolis-Hastings* algorithm. In this thesis we will present the implementation of modified algorithm, experiments based on it, results and a comparison of to previous MCMC methods.

Metody próbkowania Monte Carlo łańcuchami Markowa są rodziną algorytmów używanych do próbkowania z danego rozkładu prawdopodobieństwa. Okazują się efektywne zwłaszcza gdy przestrzeń stanów jest wielka. Ten fakt może być wykorzystany przy rozwiązywaniu wielu deterministycznych problemów – jednym z nich jest *problem komiwojażera*. Zostanie on użyty w tej pracy do przetestowania nowego podejścia *lokalnie poinformowanego*, jako modyfikacji dobrze znanego algorytmu *Metropolis-Hastingsa*. W tej pracy zaprezentujemy implementację zmodyfikowanego algorytmu, eksperymentów bazujących na nim, wyników oraz porównania z poprzednimi metodami próbkowania Monte Carlo.

Contents

1	Introduction	4
2	Markov Chains	4
3	Markov Chain Monte Carlo methods	4
4	Traveling salesman problem	4
5	Decoding encrypted text	4
6	Code description?	4
7	Conclusions	4
	References	5
A	Source code	6

List of Tables

List of Figures

1 Introduction

The Markov Chain Monte Carlo methods (abbrv. MCMC) are a family of algorithms used for sampling from a given probability distribution. At first they do not seem useful for solving practical deterministic problems, but with some tweaks they can become a powerful tool. It happens especially when space of possible solutions is enormous and computing becomes infeasible for machines. These offer a shortcut for obtaining “close enough” answers.

At their core, MCMC methods generate a Markov Chain (abbrv. MC) with a defined distribution and sample using it. The convergence of the chain is assured by ergodic theorems. The most known of them is *Metropolis-Hastings* algorithm, which constructs a MC using another set of distributions, maybe simpler ones.

In this thesis we work on *locally-informed proposals*, which involve determining *local* distribution – which comes down to finding transition probabilities of the state. They are a bit more complex and computationally heavy, but offer better results with less iterations.

To test this method we will need a deterministic problem which quickly becomes infeasible for machines to compute – one of them is a well-known traveling salesman problem. The testing is carried out using its benchmark training set *tsplib95* and implementation is provided in *Python3*.

2 Markov chains

3 Markov chain Monte Carlo methods

4 Traveling salesman problem

5 Decoding encrypted text

6 Code description?

7 Conclusions

References

- [1] O. Häggström et al. *Finite Markov chains and algorithmic applications*, volume 52. Cambridge University Press, 2002.
- [2] C. Karpiński. On use of monte carlo markov chains to decode encrypted text and to solve travelling salesman problem. 2020.
- [3] C. J. Maddison, D. Duvenaud, K. J. Swersky, M. Hashemi, and W. Grathwohl. Oops i took a gradient: Scalable sampling for discrete distributions. 2021.

A Source code