

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

# Locally-informed proposals in Metropolis-Hastings algorithm with applications

Chmiela Bartosz

University of Wrocław

08.07.2022

# Contents

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

- 1 Markov chains
- 2 Markov chain Monte Carlo methods
- 3 Traveling salesman problem
- 4 Approximate solutions
- 5 Results
- 6 Conclusions

# Markov chain

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Definition (State space)

A state space of a Markov chain is a countable set  $S$ .

## Definition (Index set)

An index set of a Markov chain is a countable set  $T$ .

# Markov chain

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Definition

A Markov chain is a sequence of random variables  $\{X_k\}_{k \in T}$  defined on a common probability space  $(\Omega, \mathcal{F}, P)$ , that take values in  $S$ , such that it satisfies Markov property:

$$\begin{aligned} P(X_{k+m} = j | X_k = i, X_{l_{p-1}} = i_{l_{p-1}}, \dots, X_{l_1} = i_1) = \\ = P(X_{k+m} = j | X_k = i), \end{aligned}$$

for all indices  $l_1 < \dots < l_{p-1} < k < k+m$ ,  $1 \leq p \leq k$ , all states  $j, i, i_{p-1}, i_{p-2}, \dots, i_0 \in S$  and  $m \geq 1$ .

# Properties

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Definition (Irreducibility)

A Markov chain with transition matrix  $\mathbf{P}$  is called irreducible if and only if for every pair of states  $i$  and  $j$  there exists a positive probability of transition between them.

## Definition (Periodicity)

Let  $d_i$  be a greatest common divisor of those  $k$  such that  $\mathbf{P}_{i,i}(k) > 0$ . If  $d_i > 1$  then state  $i$  is periodic. If  $d_i = 1$  then state  $i$  is aperiodic.

# Properties

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Definition (Stationarity)

A probability distribution  $\pi = (\pi_1, \dots, \pi_N)$  is called stationary if it satisfies

$$\pi_j = \sum_{i \in S} \pi_i p_{ij},$$

or equivalently in vector form:

$$\pi = \pi \mathbf{P}.$$

This equation is often described as the balance equation.

## Definition (Ergodicity)

A Markov chain is ergodic when it is irreducible and aperiodic.

# Ergodic chains

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Theorem

*Let  $\{X_k\}$  be a ergodic Markov chain, then:*

$$\lim_{k \rightarrow \infty} p_{ij}(k) = \pi_j.$$

# Metropolis-Hastings algorithm

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

Construct a MC, which has a stationary distribution  $\pi$  ( $\pi_i > 0$ ). Assume that  $\mathbf{Q}$  is stochastic matrix which is irreducible, aperiodic and  $\mathbf{Q}_{i,j} > 0 \iff \mathbf{Q}_{j,i} > 0$ . Let us consider a matrix defined as:

$$\mathbf{P}_{i,j} = \begin{cases} \mathbf{Q}_{i,j} \min \left( 1, \frac{\pi_j \mathbf{Q}_{j,i}}{\pi_i \mathbf{Q}_{i,j}} \right) & \text{if } i \neq j, \\ 1 - \sum_{j \in S \setminus \{i\}} \mathbf{P}_{i,j} & \text{if } i = j. \end{cases} \quad (1)$$

## Theorem

*A matrix defined in 1 is stochastic, irreducible, aperiodic and has a stationary distribution  $\pi$ .*



# Metropolis-Hastings algorithm

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

---

## Algorithm Metropolis-Hastings algorithm

---

- 1: Choose a state  $i \in S$ .
  - 2:  $X_0 \leftarrow i$
  - 3: **for**  $k = 0, 1, \dots$  **do**
  - 4:     Sample  $j \sim \mathbf{Q}_i = (\mathbf{Q}_{i,1}, \mathbf{Q}_{i,2}, \dots, \mathbf{Q}_{i,N})$ .
  - 5:     Sample  $U \sim \text{Unif}(0, 1)$ .
  - 6:     **if**  $U \leq \min\left(1, \frac{\pi_j \mathbf{Q}_{j,i}}{\pi_i \mathbf{Q}_{i,j}}\right)$  **then**
  - 7:          $X_{k+1} \leftarrow j$
  - 8:     **else**
  - 9:          $X_{k+1} \leftarrow X_k$
  - 10:    **end if**
  - 11: **end for**
-

# Traveling salesman problem

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions




Figure: Traveling salesman problem, source: wiki.

# Traveling salesman problem

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Definition

A undirected graph  $G$  is a pair  $(V, E)$ , where  $V$  is a set of vertices and  $E$  is a set of edges, which is a subset of all unordered pairs of vertices.

## Definition

A tour is a Hamiltonian cycle and we identify it with a permutation of vertices.

# Traveling salesman problem

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Definition (Traveling salesman problem)

Given an undirected weighted graph  $G = (V, E)$ ,  $|V| = n$  find a permutation  $\sigma_{\min}$  of vertices such that

$$\sigma_{\min} = \arg \min_{\sigma \in S_n} \left( \sum_{i=1}^{n-1} w_{\sigma(i), \sigma(i+1)} + w_{\sigma(n), \sigma(1)} \right),$$

where  $S_n$  is a set of all permutations of vertices and  $w_{i,j}$  is distance (weight) between state  $i$  and  $j$ .

# Softmax

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Definition

For a given vector  $\mathbf{x} = (x_1, x_2, \dots, x_d)^T \in \mathbb{R}^d$  a softmax function  $s : \mathbb{R}^d \rightarrow [0, 1]^d$  is defined as

$$s(\mathbf{x})_i = \frac{e^{x_i}}{\sum_{j=1}^d e^{x_j}},$$

$$s(\mathbf{x}) = (s(\mathbf{x})_1, s(\mathbf{x})_2, \dots, s(\mathbf{x})_d).$$

$$\sigma_{\min} = \arg \min_{\sigma \in S_n} (w_{\sigma}) = \arg \max_{\sigma \in S_n} \frac{e^{-w_{\sigma}}}{\sum_{\sigma' \in S_n} e^{-w_{\sigma'}}},$$

# Metropolis-Hastings algorithm

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

$$\frac{\pi_j \mathbf{Q}_{j,i}}{\pi_i \mathbf{Q}_{i,j}} = e^{-(w_j - w_i)} \cdot \frac{\mathbf{Q}_{j,i}}{\mathbf{Q}_{i,j}}.$$

$$\log \left( \frac{\pi_j \mathbf{Q}_{j,i}}{\pi_i \mathbf{Q}_{i,j}} \right) = -(w_j - w_i) + \log(\mathbf{Q}_{j,i}) - \log(\mathbf{Q}_{i,j}).$$

# Candidates

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

## Definition

A neighbour  $\sigma'$  of a permutation  $\sigma$  is a permutation, that for some  $k, l$  it satisfies  $\sigma'(k) = \sigma(l)$ ,  $\sigma'(l) = \sigma(k)$  and  $\sigma'(i) = \sigma(i)$  for the rest of indices.

These neighbours are the original tour with two swapped indices. This let us consider a smaller space – there are  $\binom{n}{2} = \frac{n(n-1)}{2} \approx n^2$  neighbours if the number of vertices is  $n$ .

# Random candidates (RN)

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

Sample neighbours uniformly. It is equivalent to choosing random indices to swap



# Random candidates (RN)

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

When given a tour  $\sigma$  and its neighbour  $\sigma'$  they differ only on those edges where swap is happening, let us say  $k, l$ . So for this situation we have tours:

$$\begin{aligned}\sigma &= (\dots, \sigma(k-1), \sigma(k), \sigma(k+1), \dots, \\ &\quad \dots, \sigma(l-1), \sigma(l), \sigma(l+1), \dots) \\ \sigma' &= (\dots, \sigma(k-1), \sigma(l), \sigma(k+1), \dots, \\ &\quad \dots, \sigma(l-1), \sigma(k), \sigma(l+1), \dots)\end{aligned}$$

We need to remove weights  $w_{\sigma(k-1), \sigma(k)}$ ,  $w_{\sigma(k), \sigma(k+1)}$ ,  $w_{\sigma(l-1), \sigma(l)}$ ,  $w_{\sigma(l), \sigma(l+1)}$  and add  $w_{\sigma(k-1), \sigma(l)}$ ,  $w_{\sigma(l), \sigma(k+1)}$ ,  $w_{\sigma(l-1), \sigma(k)}$ ,  $w_{\sigma(k), \sigma(l+1)}$ .

# Random candidates (RN)

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

---

## Algorithm Random neighbours algorithm

---

```
1: Choose a tour  $\sigma \in S_n$ .
2:  $X_0 \leftarrow \sigma$ 
3: Compute weight  $w_\sigma$ .
4: for  $i = 0, 1, \dots$  do
5:   Sample  $k, l \sim Unif\{1, 2, \dots, n\}$  without replacement.
6:   Sample  $U \sim Unif(0, 1)$ .
7:    $w_{\sigma'} \leftarrow w_\sigma - (w_{\sigma(k-1)+\sigma(k)} + w_{\sigma(k)+\sigma(k+1)}, w_{\sigma(l-1)+\sigma(l)} + w_{\sigma(l),\sigma(l+1)})$ 
8:    $w_{\sigma'} \leftarrow w'_{\sigma} + (w_{\sigma(k-1)+\sigma(l)} + w_{\sigma(l)+\sigma(k+1)} + w_{\sigma(l-1)+\sigma(k)} + w_{\sigma(k)+\sigma(l+1)})$ 
9:   if  $\log(U) \leq \min(0, -(w_{\sigma'} - w_\sigma))$  then
10:     $X_{i+1} \leftarrow X_i$ 
11:     $X_{i+1}(k), X_{i+1}(l) \leftarrow X_{i+1}(l), X_{i+1}(k)$ 
12:     $w_\sigma \leftarrow w_{\sigma'}$ 
13:   else
14:     $X_{i+1} \leftarrow X_i$ 
15:   end if
16: end for
```

---

# Locally-informed proposals (LIP)

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

The idea is to balance the increase in the probability of neighbour with decrease of reverse probability, such that it will be easy to compute.

$$Q_{i,j} \propto e^{\frac{-(w_j - w_i)}{\tau}}.$$

The distribution is chosen in such a way, so that we can easily group up the terms in acceptance criterion:

$$\frac{\pi_j Q_{j,i}}{\pi_i Q_{i,j}} = e^{-(w_j - w_i)} \cdot \frac{e^{\frac{-(w_i - w_j)}{\tau}}}{e^{\frac{-(w_j - w_i)}{\tau}}} \cdot \frac{C_j}{C_i} = e^{-(w_j - w_i)(1 - \frac{2}{\tau})} \cdot \frac{C_j}{C_i},$$

# Locally-informed proposals (LIP)

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

Choose tour  $\sigma$  and its neighbour  $\sigma'$  that is connected with swapping indices  $k$  and  $l$ .

$$\begin{aligned}\sigma &= (\dots, \sigma(k-1), \sigma(k), \sigma(k+1), \dots, \\ &\quad \dots, \sigma(l-1), \sigma(l), \sigma(l+1), \dots) \\ \sigma' &= (\dots, \sigma(k-1), \sigma(l), \sigma(k+1), \dots, \\ &\quad \dots, \sigma(l-1), \sigma(k), \sigma(l+1), \dots)\end{aligned}$$

# Locally-informed proposals (LIP)

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

The neighbours  $\sigma_{r,s}$ ,  $\sigma'_{r,s}$  of  $\sigma$  and  $\sigma'$  respectively look like:

$$\begin{aligned}\sigma_{r,s} = & (\dots, \sigma(r-1), \sigma(s), \sigma(r+1), \dots, \\ & \dots, \sigma(s-1), \sigma(r), \sigma(s+1), \dots, \\ & \dots, \sigma(k-1), \sigma(k), \sigma(k+1), \dots, \\ & \dots, \sigma(l-1), \sigma(l), \sigma(l+1), \dots)\end{aligned}$$

$$\begin{aligned}\sigma'_{r,s} = & (\dots, \sigma(r-1), \sigma(s), \sigma(r+1), \dots \\ & \dots, \sigma(s-1), \sigma(r), \sigma(s+1), \dots, \\ & \dots, \sigma(k-1), \sigma(l), \sigma(k+1), \dots, \\ & \dots, \sigma(l-1), \sigma(k), \sigma(l+1), \dots)\end{aligned}$$

# Example

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

Let us set  $k = 2$  and  $l = 7$ , then the set of indices to consider is  $\{1, 2, 3, 6, 7, 8\}$  and the permutations:

$$\sigma = (1, 2, 3, 4, 5, 6, 7, 8, 9, \dots)$$

$$\sigma' = (1, 7, 3, 4, 5, 6, 2, 8, 9, \dots).$$

# Example

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

	2	3	4	5	6	7	8	9	10
1	(1,2)	(1,3)	(1,4)	(1,5)	(1,6)	(1,7)	(1,8)	(1,9)	...
2		(2,3)	(2,4)	(2,5)	(2,6)	(2,7)	(2,8)	(2,9)	...
3			(3,4)	(3,5)	(3,6)	(3,7)	(3,8)	(3,9)	...
4				(4,5)	(4,6)	(4,7)	(4,8)	(4,9)	...
5					(5,6)	(5,7)	(5,8)	(5,9)	...
6						(6,7)	(6,8)	(6,9)	...
7							(7,8)	(7,9)	...
8								(8,9)	...
9									...

Table: Neighbour representation.

# Example

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

Let us set  $r = 3$  and  $s = 9$ , which means that we are looking for weight differences of neighbours obtained by swapping 3 and 9. So the neighbours have form:

$$\sigma_{3,9} = (1, 2, 9, 4, 5, 6, 7, 8, 3, \dots)$$

$$\sigma'_{3,9} = (1, 7, 9, 4, 5, 6, 2, 8, 3, \dots).$$

$$w_{\sigma_{3,9}} - w_{\sigma'_{3,9}} = (w_{1,2} + w_{2,9} + w_{6,7} + w_{7,8}) - (w_{1,7} + w_{7,9} + w_{6,2} + w_{2,8}).$$

We can generalize that equation for any  $p \notin \{1, 2, 3, 6, 7, 8\}$ :

$$w_{\sigma_{3,p}} - w_{\sigma'_{3,p}} = f_3(p) = C + w_{2,p} - w_{7,p}.$$



# Locally-informed proposals (LIP)

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

---

## Algorithm Locally-informed proposals algorithm

---

```
1: Choose a tour  $\sigma \in S_n$ .
2:  $X_0 \leftarrow \sigma$ 
3: Compute weight  $w_\sigma$ .
4: Compute all neighbour weight differences  $\mathbf{d}_\sigma$ .
5:  $s(\mathbf{d}_\sigma) = \text{softmax}(\mathbf{d}_\sigma)$ 
6: for  $i = 0, 1, \dots$  do
7:   Sample  $\sigma' \sim s(\mathbf{d}_\sigma)$ .
8:   Find  $k, l$  connected with swapping.
9:    $w_{\sigma'} \leftarrow w_\sigma + \mathbf{d}_\sigma[(k, l)]$ 
10:   $\mathbf{d}_{\sigma'} \leftarrow \mathbf{d}_\sigma$ 
11:   $\mathbf{d}_{\sigma'} \leftarrow \text{update\_differences}(\mathbf{d}_{\sigma'})$ 
12:   $s(\mathbf{d}_{\sigma'}) = \text{softmax}(\mathbf{d}_{\sigma'})$ 
13:  Sample  $U \sim \text{Unif}(0, 1)$ .
14:  if  $\log(U) \leq \min(0, -(w_{\sigma'} - w_\sigma) + \log(s(\mathbf{d}_{\sigma'})[(k, l)]) - \log(s(\mathbf{d}_\sigma)[(k, l)]))$  then
15:     $X_{i+1} \leftarrow X_i$ 
16:     $X_{i+1}(k), X_{i+1}(l) \leftarrow X_{i+1}(l), X_{i+1}(k)$ 
17:     $w_\sigma \leftarrow w_{\sigma'}$ 
18:     $\mathbf{d}_\sigma \leftarrow \mathbf{d}_{\sigma'}$ 
19:  else
20:     $X_{i+1} \leftarrow X_i$ 
21:  end if
22: end for
```

---

# Locally-informed proposals (LIP)

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

---

## Algorithm update\_differences

---

Require:  $d_{\sigma'}$

Ensure:  $d_{\sigma'}$

```
1: for  $r = k - 1, k, k + 1, l - 1, l, l + 1$  do
2:   for  $s = r + 1, \dots, n$  do
3:      $d_{\sigma'}[(r, s)] \leftarrow \text{get\_difference}(d_{\sigma'}[(r, s)])$ 
4:   end for
5: end for
6: for  $s = k - 1, k, k + 1, l - 1, l, l + 1$  do
7:   for  $r = 1, 2, \dots, l$  do
8:      $d_{\sigma'}[(r, s)] \leftarrow \text{get\_difference}(d_{\sigma'}[(r, s)])$ 
9:   end for
10: end for
```

---

# Simulated annealing

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

The idea is to describe a probability of state using a cooling parameter  $t_k$  such that it reminds the cooling of a metal and may change with each step:

$$\pi_i = \frac{e^{\frac{-E_i}{t_k}}}{C},$$

where  $C$  is normalizing constant. The quotient of probabilities then is:

$$\frac{\pi_j}{\pi_i} = e^{\frac{E_i - E_j}{t_k}}$$

# Initial condition

LIP

B.Chmiela

Markov chains


MCMC

TSP


Approximate  
solutions

Results

Conclusions



(a) Random neighbours.



(b) Locally-informed proposals.

Figure: Different initial states for *berlin52*.

# Simulated annealing

LIP

B.Chmiela

Markov chains


MCMC

TSP


Approximate  
solutions

Results

Conclusions



(a) berlin52.



(b) kroA150.

Figure: Different cooling parameters for *berlin52* and *kroA150*.

# Temperature

LIP

B.Chmiela

Markov chains


MCMC

TSP


Approximate  
solutions

Results

Conclusions



(a) berlin52.



(b) kroA150.

Figure: Different temperature parameters for *berlin52* and *kroA150*.

# Algorithms comparison

LIP

B.Chmiela

Markov chains


MCMC

TSP


Approximate  
solutions

Results

Conclusions



(a) berlin52,  $t_k = 1$ .



(b) kroA150,  $t_k = 1$ .

**Figure:** Comparing RN and LIP for *berlin52* and *kroA150* with low number of iterations.

# Algorithms comparison

LIP

B.Chmiela

Markov chains


MCMC

TSP


Approximate  
solutions

Results

Conclusions



(a)  $t_k = 1$ .



(b)  $t_k = \frac{3}{\log(k+2)}$ .

**Figure:** Comparing RN and LIP for *dsj1000* with different cooling parameters.



# Algorithms comparison

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

	RN			LIP		
dataset	dist.	time [s]	ratio	dist.	time [s]	ratio
berlin52	11344	1.32	1.50	9276	116	1.23
kroA150	62467	1.24	2.36	53988	454	2.04
att532	165445	1.38	5.98	78150	2462	2.82
dsj1000	199343433	1.5	10.68	89105687	6439	4.78

Table: Methods comparison,  $t_k = 1$ , 20000-th step.

# Algorithms comparison

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

	RN			LIP		
dataset	step	distance	time [s]	step	distance	time [s]
berlin52	20000	11344	1.32	27	11198	0.22
kroA150	20000	62467	1.24	139	62459	3.64
att532	20000	165445	1.38	199	165247	24.65
dsj1000	20000	199343433	1.5	256	199338468	80.54

**Table:** Amount of time and number of steps required for LIP algorithm to reach the result of RN after 20000 steps,  $t_k = 1$ .

# Conclusions

## LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

- LIP algorithm is decreasing the distance quicker than RN,
- LIP converges to some value, which is always smaller than the RN,
- LIP reaches better results in feasible time,
- Only first hundreds iterations matter,
- LIP algorithm is considerably slower for a longer run,

# Improvements

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

- Use of interning in *Python3*,
- use of concurrency,
- sampling from  $Q_i$  using MCMC methods,
- better tuning of temperature and cooling parameters.

LIP

B.Chmiela

Markov chains

MCMC

TSP

Approximate  
solutions

Results

Conclusions

Thank you for your attention.