PROLANCE
Simplifying Interiors

ORIGIN

API KEY REFERENCE

Author	S. Jaisimha, Prolance Services Pvt Ltd, Bengaluru		
Revision	R0	27th September 2025	Introduced API Keys
	R1	16th January 2026	Updated API responses

PROLANCE
Simplifying Interiors

CONTENTS

POST /TOKEN....3

API KEY REQUIRED....4

POST /PARTNERS/LOGINAPI....5

To start interacting with the API server, you must first generate a token by providing a valid username and password. The generated token is valid for a period of **twenty-four hours** from the time of generation and will need to be refreshed by generating a new token after that.

POST /TOKEN

```
curl -i -X POST \
   -H "Content-Type:application/x-www-form-urlencoded" \
   -d "grant_type=password" \
   -d "username=<user name>" \
   -d "password= <password>” \
 'https://prolance-api.<customer>.com/token'
```

Note that both username and password are case sensitive. If the username and password are valid, the return JSON will be

200 OK

```
{
    "access_token": "A1KaDx51f.....",
    "token_type": "bearer",
    "expires_in": 86399
}
```

If either is invalid, the return JSON will be

400 Bad Request

```
{
    "error": "invalid_access",
    "error_description": "Unknown user '<username>' or invalid password."
}
```

If the user is marked as “Inactive”, the return JSON will be

400 Bad Request

```
{
    "error": "invalid_access",
    "error_description": "User '<username>' is no longer active."
}
```

API KEY REQUIRED

To continue interacting with the API server, you will require an API Key provided by Prolance. You cannot generate an API key for yourself, it must be provided by Prolance only.

All API calls must have the "OriginAPIKey" header and the provided API key as its value. If this header is not present, you will not be able to successfully call any API endpoint.

API keys are also IP constrained, i.e., any given API key can only work from a particular set of IP addresses. API calls originating from any IP address that is not authorized by Prolance will fail with the response as:

401 Unauthorized

```
{
    "message": "Unauthorized access",
    "status": false,
    "totalPages": 0,
    "currentPage": 0,
    "pageRecords": 0,
    "totalRecords": 0,
    "data": null
}
```

There are several possible messages you may get while using API keys. These are listed below.

Message	Meaning
Access denied	You are trying to access an API to which you have no rights. You can only access APIs available to you. Most of these APIs are documented in the following pages.
API key is invalid	Please ensure you use the exact same value given to you by Prolance
API key has expired	Each API key has a set expiry date. Unless extended by Prolance, using an API key beyond the set expiry date will result in this message.
Unauthorized access	Each API key can be used only from specific IP addresses, which you will need to provide to Prolance at the time of requesting the API key. Using your API key from any other IP address will result in this message. This is a security feature to ensure your API key is not misused by someone else.

POST /PARTNERS/LOGINAPI

```
curl -i -X POST \
   -H "Content-Type:application/json" \
   -H "Authorization:Bearer <Token> \
   -H "OriginAPIKey:<Your API Key>" \
   -H "NoEncryption:1" \
   -d \
'{
  "LoginID": "username@company.com",
  "Password": "<Password>",
  "LoginFrom": 1
}' \
'https://prolance-api.<customer>.com/Origin/Partners/Login'
```

Please note the "NoEncryption" header. All API calls must include this header with value as 1. Otherwise, the API call will be rejected.

The payload validating a login is:

```
{
  "LoginID": "username@company.com ",
  "Password": "password"
}
```

Attribute	Type	Description
LoginID	String	Email ID of the partner
Password	String	Password for this account

If the login is successful, the API will return a 200 OK status and return JSON will be:

```
{
  "message": "Success",
  "status": true,
  "totalPages": 1,
  "currentPage": 1,
  "pageRecords": 1,
  "totalRecords": 1,
  "data": [
    {
      "partnerID": 10001,
      "sessionID": "API-10001-37d51560-1f97-4c57-a71c-99ad3c16564e"
    }
  ]
}
```

All API responses follow the same format. The actual data will be in the “data” array

Attribute	Type	Description
`message`	String	Status of the API response, usually “Success”. Otherwise a description of what the error was.
`status`	Bool	True if the call was successful, false if not
`totalPages`	Integer	Total number of pages in the response
`currentPage`	Integer	Will be 1 by default
`pageRecords`	Integer	Number of records in the “data” array
`totalRecords`	Integer	Total number of records
`data`	Array	This will contain the data itself as an array of values.

For the LoginAPI call, the response is

Attribute	Type	Description
`partnerID`	Integer	The partner ID of the user name
`sessionID`	String	Session ID string for this session

Important information

You should save the SessionID in a globally accessible variable, since it needs to be passed with each subsequent API call. The SessionID is valid until the Logout API is called, or 120 minutes of no activity. If there is no subsequent API call within 120 minutes of the SessionID being generated, the server will automatically logout the user and a new SessionID should be generated via the LoginAPI call.