





19"LCD monitor

VGA/AV



Model Name	VS-9W71
LCD Display	
Display Type	19" active matrix TFT LCD panel
Pixel pitch	0.294(H)×0.294(V) mm
Display Area(HxW)	376.32(H)×301.056(W) mm
Contrast Ratio	800:1
Viewing Angle	L/R +80°~−80° U/D +80°~−80°
Interface	LVDS (5V)
Operation Features	
Frequency input Range(H)	30KHZ—80KHZ
Frequency input Range(V)	50HZ---75HZ
Video Frequency	135MHz
Display Colors	16,777M
Resolution	SXGA 1280X1024 @ 75Hz
Brightness	300 cd / m ²
Response Time	5 ms
Operation conditions	
Humidity	20 % ~80 %
Temperature	0℃~45℃
Storage Conditions	
Humidity	20 % ~80 %
Temperature	−20℃~60℃
Input Connector	
PC	Analog: 15-pin-D-SUB Digital: DVI(Optional) Audio Line in - stereo
VIDEO	Option

Users Control	
Front Panel Controls	Auto Adjust, Menu, up, down, Select+, Select-, ESC, Volume
OSD Controls	Brightness, Contrast, Auto adjust, Phase
	Clock, H. Position, V. Position, Sharpness
	Color Temperature, Language,
	OSD H/V Position, Video select, Recall
Physical Specification	
Dimension (HxWxD)	450(H)×450(W)×220(D) Typ. mm
Net Weight	7.2KG
Power	
Power Saving	VESA DPMS Standard
Power Consumption	50W (Typ)
Regulation	
Safety & EMI	UL, CSA, TUV/GS, CE, VCCI, FCC (DOC)
<div>  豪聯 </div> <div> <i>Your Best Display</i> </div> <div>  </div> <div> <i>Solution Supplier</i> </div> <div> <p>Since 1987</p> <p>台北縣汐止市中興路31號2樓</p> <p>2F, No.31, Chung Hsing Rd., His-Chih City, Taipei County 221, Taiwan.</p> <p>Tel: 02-2648-3999 Fax: 02-2648-0007</p> </div>	