



22" Touch (Wide)



Model Name	VS-22NW71T
LCD Display	
Display Type	22" 16:9 active matrix TFT LCD panel
Pixel pitch	0.282(H)x0.282(V) mm
Display Area(HxW)	473.76x296.1 mm
Contrast Ratio	800:1
Viewing Angle	L/R 85/85
	U/ D 80/80
Interface	LVDS
Operation Features	
H Frequency input Range	30KHZ—80KHZ
V Frequency input Range	56HZ---75HZ
Video Frequency	RGB Analog 75 Ohms 0.7Vp-p
Display Colors	16.7M
Resolution	1680x1050
Brightness	300 cd/m2
Response Time	5ms
Operation conditions	
Humidity	20 % ~80 %
Temperature	0℃~45℃
Storage Conditions	
Humidity	20 % ~80 %
Temperature	—20℃~60℃
Features selection	
Input	VGA only
Option	Audio 2x2W
	VGA+DVI+Audio
Color Option	B/B S/B W/W
Touch Screen	Resistiver/Capacitive/Saw
Port	RS232 /USB
Touch wire	4,5,8 WIRE

Users Control	
Front Panel Controls	Power, Auto Adjust, Menu, up, down
OSD Controls	Brightness, Contrast, Display Adjust
	OSD Adjust ,Language, Color Temperature
	Audio Control , Input Select
	Reset , Exit
Power	
Power Saving	VESA DPMS Standard
Power Consumption	50W(MAX)
Regulation	
Safety & EMI	UL, CSA, TUV CE, FCC (DOC)

HOMLAN® 豪聯
Since 1987

*Your Best Display
Solution Supplier*

Viewtec

台北縣汐止市中興路31號2樓
2F, No.31, Chung Hsing Rd., His-Chih City, Taipei County 221, Taiwan.
Tel: 02-2648-3999 Fax: 02-2648-0007