

15 吋(吸頂式)



型號	HL-1530
面板尺寸	15.3"
可視區域	334.08 (W) x 200.448 (H) mm
解析度	1280(H) x 3 (RGB) x 768(V)
色彩	262,144 colors
像素大小(mm)	0.264 (W) x 0.264 (H) mm
對比	300:1
亮度(cd/m2)	300
可視角度	Horizontal: 60° (typ.,left side) , 60° (typ.,right side)
	Vertical: 40° (typ.,up side) , 60° (typ.,down side)
電源供應	DC12V+-10% less than 1.6A
省電功能	20W power consumption (typ.), less than 3W when in
	backlight sleep mode.
機身尺寸(mm)	148mm(W) x 328mm (L) x 38mm (D)
淨重	3.2 kg
安規	UL, FCC, CE, TUV,
Backlight Unit	CCFL.Side-light type (two lamp)
IR Transmitter	Yes
User's Control	Power on/off, OSD control
System	Auto detection between NTSC/PAL
	2. SECAM is available
Environmental Condition:	Operation Temp.: 0~50 degree C
	Storage Temp.: -20~60 degree C
	Humidity: 10~90%

*Specifications are subject to change in different panel used.



Your Best Display Solution Supplier View eC

22161 新北市汐止區中興路 31 號 2 樓

2F, No.31, Zhongxing Rd., Xizhi Dist., New Taipei City 22161, Taiwan(R.O.C)

Tel: 02-2648-3999 Fax: 02-2648-0007