

10.4" BUS LCD monitor (Roof-mount)



Model No	HL-1040
Panel Size	10.4"
Active Area	211.2 (W) x 158.4 (H) mm
Resolution	640(H) x 3 (RGB) x 480(V)
Display Colors	262,144 colors
Pixel Pitch (mm)	0.264 (W) x 0.264 (H) mm
Contrast Ration	300:1
Brightness (cd/m2)	350
Viewing angle	Horizontal: 60° (typ.,left side) , 60° (typ.,right side) Vertical: 40° (typ.,up side) , 60° (typ.,down side)
Power Supply	DC12V+-10% less than 0.8A
Power management	7.4W power consumption (typ.), less than 3W when in backlight sleep mode.
Dimensional outline(mm)	265.0mm(W) x 268mm (L) x 40.8mm (D)
Weight	1.8 kg
Safety certifications	UL, FCC, CE, TUV,
Backlight Unit	CCFL.Side-light type (single lamp)
IR Transmitter	Yes
User's Control	Power on/off, OSD control
System	1. Auto detection between NTSC/PAL 2. Scream is available
Environmental Condition:	Operation Temp.: 0~50 degree C Storage Temp.: -20~60 degree C Humidity: 10~90%

*Specifications are subject to change in different panel used.

HOMLAN® 豪聯
Since 1987

Your Best Display
Solution Supplier

Viewtec

**2F, No.31, Zhongxing Rd., Xizhi Dist., New Taipei City 22161,
Taiwan(R.O.C)**
Tel : 02-2648-3999 Fax : 02-2648-0007