





19" Touch (Wide)



Model Name	VS-19NW71T
LCD Display	
Display Type	19" 16:9 active matrix TFT LCD panel
Pixel pitch	0.285(H)×0.285(V) mm
Display Area(HxW)	410.4(H)×256.5(W) mm
Contrast Ratio	850:1
Viewing Angle	L/R +85°~ -85°
	U/D +80°~ -80°
Interface	LVDS (5V)
Operation Features	
H Frequency input Range	30KHZ—80KHZ
V Frequency input Range	50HZ---75HZ
Video Frequency	135MHz
Display Colors	16,777M
Resolution	WXGA+ 1440X900 @ 75Hz
Brightness	300 cd /m ²
Response Time	5ms
Operation conditions	
Humidity	20 % ~80 %
Temperature	0℃~45℃
Storage Conditions	
Humidity	20 % ~80 %
Temperature	-20℃~60℃
Features selection	
Input	VGA only
Option	Audio 2x2W
	VGA+DVI+Audio
Color Option	B/B S/B W/W
Touch Screen	Resistiver/Capacitive/Saw
Port	RS232 /USB
Touch wire	4,5,8 WIRE

Users Control	
Front Panel Controls	Power, Auto Adjust, Menu, up, down
OSD Controls	Brightness, Contrast, Display Adjust
	OSD Adjust ,Language, Color Temperature
	Audio Control , Input Select
	Reset , Exit
Power	
Power Saving	VESA DPMS Standard
Power Consumption	50W (max)
Regulation	
Safety & EMI	UL, CSA, TUV/GS, CE, VCCI,FCC (DOC),BSMI
<div>  <div> <i>Your Best Display</i> <i>Solution Supplier</i> </div>  </div> <p> 台北縣汐止市中興路31號2樓 2F, No.31, Chung Hsing Rd., His-Chih City, Taipei County 221, Taiwan. Tel: 02-2648-3999 Fax: 02-2648-0007 </p>	