





22" LCD monitor (Wide)



| Model Name | VS-22NW72 |
|-----------------------------|---------------------------------|
| LCD Display | |
| Display Type | 22" active matrix TFT LCD panel |
| Pixel pitch | 0.282(H)x0.282(V) mm |
| Display Area(HxW) | 473x296 mm |
| Contrast Ratio | 800:1 |
| Viewing Angle | 85/85 80/80 |
| Interface | LVDS |
| Operation Features | |
| H Frequency input Range | 30KHZ—80KHZ |
| V Frequency input Range | 56HZ---75HZ |
| Video Signal | RGB Analog 75 Ohms 0.7Vp-p |
| Display Colors | 16.7M |
| Resolution | 1680x1050 |
| Recommand resolution | 1680x1050@ 60Hz |
| Brightness | 300 cd/m2 |
| Response Time | 5ms |
| Operation conditions | |
| Humidity | 20 % ~80 % |
| Temperature | 0℃~45℃ |
| Storage Conditions | |
| Humidity | 20 % ~80 % |
| Temperature | —20℃~60℃ |

| | |
|--|--|
| Input Connector | |
| PC | VGA |
| | DVI (option) |
| Audio | 2 W speaker x2 |
| Touch Screen (Option) | Res,Cap,Saw |
| TV Tunner (Optin) | NTSC,PaL,Secam |
| Users Control | |
| Front Panel Controls | Power, Auto Adjust, Menu, up, down |
| OSD Controls | Brightness, Contrast, Auto adjust, Phase |
| | Clock, H. Position, V. Position, Sharpness |
| | Color Temperature, Language, |
| | OSD H/V Position, Video select, Recall |
| Physical Specification | |
| Dimension (HxWxD) | 440x514x230mm |
| Power | |
| Power Saving | VESA DPMS Standard |
| Power Consumption | 48W |
| Regulation | |
| Safety & EMI | UL, CSA, TUV CE, FCC (DOC) |
| <div>  豪聯 </div> <div> <i>Your Best Display</i> </div> <div>  </div> <div> <i>Since 1987</i> </div> <div> <i>Solution Supplier</i> </div> <p> 台北縣汐止市中興路31號2樓 2F, No.31, Chung Hsing Rd., His-Chih City, Taipei County 221, Taiwan. Tel: 02-2648-3999 Fax: 02-2648-0007 </p> | |