

22 H. three of screen Digital Signal advertising trolley



Model	VSGT-223H
Panel Size	22"
Panel Active Area	477.5(H)×268.6(V) (21.6"diagonal)
Resolution	Full HDTV(1920×1080pixels)
Color	16.7M
Viewing Angle (H /V)	170° / 160°
Contrast	1000 : 1
Brightness	300 cd/m ²
Response Time	5 ms
Pixel Pitch (mm)	0.248(H) x 0.248(V) mm
Audio/video Processor	Form chip microprocessor of the multimedia
Support Video formats	NTSC · PAL System 480i/p · 576i/p · 720p · 1080i/p
	Can set up the picture to export 4:3 or 16:9
Audio/video Input	VGA · S-VIDEO · AV OUT · AV×2 · YPbPr×2
Memory Card Supported	CF · SDHC/SD · SM · MMC · MS · XD Card&USB 2.0 Pord
Support Picture File	JPEG · BMP
Support Music File	MP3、WMA、WAV、Ogg、AAC
Support Video File	RM、RMVB、MPEG1/2、AVI(Divx、Xvid) 、MP4、VOB、
	DAT · M-JPEG
	RM/RMVB formats max Resolution 1024×576
	Other forms max Resolution 720×576
OSD Language	Traditional Chinese / English
Control Method	IR Remote Controller

	Output it according to the original film form.
Movie Player	· ·
	Movie play has no phenomenon of postponing smoothly.
	Can arrange in an order and broadcast all films in a circle
	automatically.
Player Mode	Automatic photo / movie playing on startup Photo slideshow
	with MP3 music
Sub-Title	Support Traditional Chinese / English Sub-Title
Picture Player	Support Picture+MP3 Player
Speaker	20W(10W+10W)
Power Supply	12V 5A x3 less than 165W
Operating Conditions	Operating: Temperature 0~50% Humidity 20-80%
	Storage: Temperature -20~60% Humidity 10-90%
Dimension / Weight	630 x 1700 x 100 x 360 x710mm / 52kg
Accessory	Remote Controller · User-Guide

*Specifications are subject to change in different panel used.



2F, No.31, Zhongxing Rd., Xizhi Dist., New Taipei City 22161, Taiwan(R.O.C)

Tel: 02-2648-3999 Fax: 02-2648-0007