


32" Desk type Digital Signage



Model	VSGT-32D
Panel Size	32"
Panel Active Area	697.7(H)×392.3(V) (31.51"diagonal)
Resolution	1366×768pixels
Color	16.7M
Viewing Angle (H /V)	176° / 176°
Contrast	3000 : 1
Brightness	450 cd/m ²
Response Time	6.5 ms
Pixel Pitch (mm)	0.17025(H) x 0.51075(V) mm
Audio/video Processor	Form chip microprocessor of the multimedia
Support Video formats	NTSC · PAL System 480i/p · 576i/p · 720p · 1080i/p
	Can set up the picture to export 4 : 3 or 16 : 9
Audio/video Input	VGA · S-VIDEO · AV OUT · AV×2 · YPbPr×2
Memory Card Supported	CF · SDHC/SD · SM · MMC · MS · XD Card&USB 2.0 Pord
Support Picture File	JPEG · BMP
Support Music File	MP3、WMA、WAV、Ogg、AAC
Support Video File	RM、RMVB、MPEG1/2、AVI(Divx、Xvid) 、MP4、VOB、
	DAT · M-JPEG
	RM/RMVB formats max Resolution 1024×576
	Other forms max Resolution 720×576
OSD Language	Traditional Chinese / English
Control Method	IR Remote Controller
Movie Player	Output it according to the original film form.
	Movie play has no phenomenon of postponing smoothly.
	Can arrange in an order and broadcast all films in a circle
	automatically.

Player Mode	Automatic photo / movie playing on startup Photo slideshow with MP3 music
Sub-Title	Support Traditional Chinese / English Sub-Title
Picture Player	Support Picture+MP3 Player
Speaker	20W(10W+10W)
Power Supply	100V-240V 50/60Hz less than 162W
Operating Conditions	Operating: Temperature 0~50% Humidity 20-80%
	Storage: Temperature -20~60% Humidity 10-90%
Dimension / Weight	765 x 535 x 90mm / 19kg
Safety	FCC · CE · RoHS
Accessory	Remote Controller · User-Guide

*Specifications are subject to change in different panel used.



2F, No.31, Zhongxing Rd., Xizhi Dist., New Taipei City 22161, Taiwan(R.O.C)

Tel: 02-2648-3999 Fax: 02-2648-0007