

## 15" BUS LCD monitor (Roof-mount)



<b>Model NO</b>	HL-1530
Panel Size	15.3"
Active Area	334.08 (W) x 200.448 (H) mm
Resolution	1280(H) x 3 (RGB) x 768(V)
Display Colors	262,144 colors
Pixel Pitch (mm)	0.264 (W) x 0.264 (H) mm
Contrast Ration	300:1
Brightness (cd/m2)	300
Viewing angle	Horizontal: 60° (typ.,left side) , 60° (typ.,right side) Vertical: 40° (typ.,up side) , 60° (typ.,down side)
Power Supply	DC12V+-10% less than 1.6A
Power management	20W power consumption (typ.), less than 3W when in backlight sleep mode.
Dimensional outline(mm)	148mm(W) x 328mm (L) x 38mm (D)
Weight	3.2 kg
Safety certifications	UL, FCC, CE, TUV,
Backlight Unit	CCFL.Side-light type (two lamp)
IR Transmitter	Yes
User's Control	Power on/off, OSD control
System	1. Auto detection between NTSC/PAL 2. SECAM is available
Environmental Condition:	Operation Temp.: 0~50 degree C Storage Temp.: -20~60 degree C Humidity: 10~90%

\*Specifications are subject to change in different panel used.

**HOMLAN® 豪聯**  
Since 1987

*Your Best Display*  
*Solution Supplier*

**Viewtec**

**2F, No.31, Zhongxing Rd., Xizhi Dist., New Taipei City 22161,  
Taiwan(R.O.C)**  
**Tel : 02-2648-3999      Fax : 02-2648-0007**