

External Touch Module



LCD SIZE	18.5" WSXGA (16:9)	21.5" WSXGA(16:9)
VIEWABLE AREA	416.40 X 237.00 mm	483.50X273.60 mm
ACTIVE AREA	411.00 X 231.60 mm	477.50X268.60 mm
TRANSMITTAL	82% ± 5%	
Surface Hardness	≥3H (JIS K5400)	
TOUCH RESOLUTION	4096 x 4096	
INTERFACE CONTROLLER	External controllers: USB port	
OPERATING SYSTEMS	Windows XP, 2000,VISTA,Windows7	
HID MODE	Digitizer HID-Vista or Windows7 / Mouse HID	
ACTIVATION FORCE	≤50g	
RESPONSE TIME	10 msec maximum.	
POSITION ACCURACY	3 mm maximum error.	
OPERATING TEMPERATURE	-10°C to +60°C	
STORAGE TEMPERATURE	-40°C to +75°C	
HUMIDITY	Pass 40 degrees C, 95% RH for 96 hours.	
DURABILITY	Finger Touch :35M touches / Pen Hitting :10M touches	

*Specifications are subject to change in different panel use

HOMLAN® 豪聯
Since 1987

Your Best Display
Solution Supplier

Viewtec

22161 新北市汐止區中興路 31 號 2 樓

2F, No.31, Zhongxing Rd., Xizhi Dist., New Taipei City 22161, Taiwan(R.O.C)

Tel : 02-2648-3999 Fax : 02-2648-0007