



CLIENT



CONTRACTOR  SK ecoplant

LINE NO. 15A-AIR-DRY-ST1-N-7037

* PIPE : P/P1	* 90° ELBOW : E90	* 45° ELBOW : E45	* TEE :	* RED.TEE : TR	* STUB-IN : STU	* REINFORCING PAD : RP	* CON.RED : RC	* ECC.RED : RE	* CON.SWAGE : RCS/RCS1	* ECC.SWAGE : RES/RES1	* NIPPLE : NP/NP1/NP2	* CAP : CAP/CAP1	* PLUG : PLG	* FULL COUPLING : FC	* HALF COUPLING : HF/HF1
---------------	-------------------	-------------------	---	----------------	-----------------	------------------------	----------------	----------------	------------------------	------------------------	-----------------------	------------------	--------------	----------------------	--------------------------

INSULATION	CODE	N	CONDITION	PRESS. (kg/cm2g)	TEMP. (°C)	AREA	W14						
	THICK.	—	DESIGN	10	60	UNIT	R1FA						
			OPERATING	7.5	AMB	REF. PLAN DWG.							
						CJ-M15W14-PI-A30-010016-A							
						REF. P & ID							

경고 : 본 도면은 SK HYNIX의 기밀비밀 자료로서, 어떠한 경우에도 목적 외 사용, 복제, 제3자에게 공개, 누설 및 유출할 수 없으며, 회사는 유포자의 불법 사용으로 피해가 발생할 경우 유포자에게 민/형사상 책임을 요구할 수 있음.