

POW-576

PROJECT TITLE : M15X Ph2 Project

[illegible]



CLIENT



1

INSULATION	CODE	C	CONDITION	PRESS. (kg/cm2g)	TEMP. (°C)	AREA W14							CONTRACTOR	PROJECT NAME	
	THICK.	25	DESIGN	13	60	UNIT 4FA								M15X Ph4 Project	
			OPERATING	10	AMB	REF. PLAN DWG. CJ-M15W14-PI-A30-040009-B							COMMODITY	JOB NO.	
						REF. P & ID CJ-M15W13-PR-A20-000080		25.01.24	APPROVED FOR CONSTRUCTION	황래중	안남후	박동영	LINE NO.	22330D	
							REV. NO.	DATE	DESCRIPTION	BY	CHK	APP'D	25A-POW-ST1-C-9071	SH'T NO. 01 / 01	REV. 0



ITEM	SIZE	Q'TY	DESCRIPTION
ST1			
P	25A	4.9M	PIPE, STS 304TP, ERW, PE - SCH 10S
E90	25A	3EA	ELBOW 90 DEG, STSF304, SW - SCH 10S
VG	25A	1EA	GATE VALVE, KS 10K, RF FLG'D, BODY-STSF304 /
			TRIM-STS304, BB / OS&Y, HANDWHEEL
F	25A	3EA	FLG SO, KS 10K, RF, STS304
G	25A	3EA	GASKET, KS 10K, RF, PTFE+EPDM, 3.0MM TH'K
B	25A	3SET	MACHINE BOLT & NUTS :STS 304 / W WASHERS
IN	25tx25A	4.9M	관 보온재(고무발포)



* PIPE : P/P1	* 90° ELBOW : E90	* 45° ELBOW : E45	* TEE : T	* RED.TEE : TR	* STUB-IN : STU	* REINFORCING PAD : RP	* CON.RED : RC	* ECC.RED : RE	* CON.SWAGE : RCS/RCS1	* ECC.SWAGE : RES/RES1	* NIPPLE : NP/NP1/NP2	* CAP : CAP/CAP1	* PLUG : PLG	* FULL COUPLING : FC	* HALF COUPLING : HF/HF1
* STUB-IN : STU	* SOCKET(HDPE/PVC) : SC	* SADDLE(HDPE) : SD	* FLANGE : F/F1	* GASKET : G/G1/G2	* BOLT & NUT : B/B1	* BLIND FLANGE : FB/FB1	* GATE VA. : VG/VG1/VG2	* BALL VA. : VB/VBLO/VB1/VB1LO/VB2/VB2LO	* BUTTERFLY VA. : VF/VF4	* CHECK VA. : VC/VC1/VC2/VC3/VC4/VC5/VC6/VC7					
* GLOBE VA. : VL/VL1/VL2	* DIAPHRAGM VA. : VD/VDLO	* DAMPER : VP	* QUICK COUPLING : SQC	* FLEXIBLE JOINT(STEEL) : FLXB	* FLEXIBLE JOINT(RUBBER) : FLXR	* FLEXIBLE JOINT(STEEL PTFE LINED) : FLXL	* FLEXIBLE HOSE : FLXH	* STEAM TRAP : ST	* SPRAY NOZZLE : SPN	* EMERGENCY SHOWER : SSH					
* STRAINER(Y-TYPE) : YSTR	* STRAINER(T-TYPE) : TSTR	* STRAINER(BUCKET-TYPE) : BSTR	* ANCHOR PLATE : STOP	* BIRD SCREEN : BS	* ISOLATION KIT : IK	* UNLOADING BOX : UB	* AIR TRAP : AT	* LOTO : LOTO	* SIGHT GLASS : SG	* PRESSURE GAUGE : PG	* SHILED : SH	* SPECIAL BOLT & NUT : BL/BL1			

INSULATION	CODE	C	CONDITION	PRESS. (kg/cm2g)	TEMP. (°C)	AREA W14								CONTRACTOR	PROJECT NAME	
	THICK.	25	DESIGN	13	60	UNIT 4FA									M15X Ph4 Project	
			OPERATING	10	AMB	REF. PLAN DWG. CJ-M15W14-PI-A30-040009-B		25.01.24	APPROVED FOR CONSTRUCTION	황래중	안남후	박동영	COMMODITY	POW	JOB NO.	
						REF. P & ID CJ-M15W13-PR-A20-000080							REV. NO.	DATE	DESCRIPTION	BY

경고 본 도면은 SK HYNIX의 기밀비밀 자료로서, 어떠한 경우에도 목적 외 사용, 복제, 제3자에게 공개, 누설 및 유출할 수 없으며, 회사는 유포자의 불법 사용으로 피해가 발생할 경우 유포자에게 민/형사상 책임을 요구할 수 있을

