

- Shin's Lab -

# Python for Data Visualization

# Python for Data Visualization

## -Chapter.4 Bar Plot -

4-00. Intro to Bar Plot

4-01. Bar Plot Basics

4-02. Multiple Bar Plots

4-03. Rect Objects

4-04. Horizontal Bar Plots

**4-05. Exercises**

# Python for Data Visualization

## -Chapter.4 Bar Plot -


### 4-05. Exercises

1. Exercise 4-01
2. Exercise 4-02
3. Exercise 4-03
4. Exercise 4-04

1. Exercise 4-01

Vehicle Re-identification in Aerial Imagery: Dataset and Approach\*

Peng Wang, Bingliang Jiao, Lu Yang, Yifei Yang, Shizhou Zhang, Wei Wei, Yanning Zhang  
School of Computer Science and Engineering, Northwestern Polytechnical University, Xi'an, China  
National Engineering Laboratory for Integrated Aero-Space-Ground-Ocean Big Data Application Technology, China  
`{peng.wang, szzhang, weiweinwpu, ynzhang}@nwpu.edu.cn`  
`{bingliang.jiao, lu.yang, yfyang}@mail.nwpu.edu.cn`



## 1. Exercise 4-01

```
import numpy as np
import matplotlib.pyplot as plt

### data setting
xticklabels = np.array(['White', 'Black', 'Gray', 'Red', 'Green',
                        'Blue', 'Yellow', 'Brown', 'Other'])

data = np.array([47.19, 15.82, 14.32, 7.30, 2.64,
                 5.64, 0.84, 5.38, 0.73])

background = 55*np.ones_like(data)
xticks = np.arange(len(data))

fig, ax = plt.subplots(figsize = (20,10))
### background plotting
ax.bar(xticks, background,
      color = 'k',
      alpha = 0.05,
      hatch = '//',
      edgecolor = 'k')
### bar plotting
rects = ax.bar(xticks, data,
               color = 'cornflowerblue')
```



```
### annotation
for rect in rects:
    height = rect.get_height()
    width = rect.get_width()
    x = rect.get_x()

    ax.text(x + width/2, 55,
            str(height) + '%',
            fontsize=40,
            rotation=-55,
            ha='right',
            va='bottom')

### tick & ticklabel customizing
ax.set_xticks(xticks)
ax.set_xticklabels(xticklabels,
                  fontsize=50,
                  rotation=40,
                  ha='right')
ax.tick_params(axis = 'y',
              labelsize = 0,
              size = 0)
ax.tick_params(axis = 'x',
              size = 0)

### spine customizing
for spine_idx, spine_loc in enumerate(ax.spines):
    ax.spines[spine_loc].set_visible(False)
```



**1. Exercise 4-01**


## 2. Exercise 4-02

### SANet: Scene Agnostic Network for Camera Localization

Luwei Yang<sup>1,\*</sup> Ziqian Bai<sup>1,\*</sup> Chengzhou Tang<sup>1</sup> Honghua Li<sup>2</sup> Yasutaka Furukawa<sup>1</sup> Ping Tan<sup>1</sup>

<sup>1</sup> Simon Fraser University <sup>2</sup> Alibaba A.I Labs

{luweiy, ziqianb, cta73, furukawa, pingtan}@sfu.ca, honghua.lhh@alibaba-inc.com



## 2. Exercise 4-02

```
import numpy as np
import matplotlib.pyplot as plt

### matplotlib style customizing
plt.style.use('seaborn')

### data setting
labels = np.array(['Ours', 'Ours(Skip10)', 'InLoc(Skip10)[30]',
                  'Ours(Baseline)', 'DSAC++[5]', 'DSAC[3]',
                  'RF2[18]', 'RF1[4]'])
data = np.array([68.2, 67.9, 66.3, 63.8, 76.1,
                 62.5, 64.5, 55.2])
yticks = np.arange(len(labels))

### fontdict setting
label_fontdict = {'fontfamily': 'sans-serif',
                  'size': 50}
annot_fontdict = {'size': 50,
                  'ha': 'left',
                  'va': 'bottom'}

### barh plotting
fig, ax = plt.subplots(figsize = (20, 16))
rects = ax.barh(yticks, data)
ax.invert_yaxis()
```

```
### tick & ticklabel customizing
ax.set_yticks(yticks)
ax.set_yticklabels(labels,
                  fontdict=label_fontdict)

xticks = np.arange(0, 101, 20)
xticklabels = [str(i) + '%' for i in xticks]
ax.set_xticks(xticks)
ax.set_xticklabels(xticklabels,
                  fontdict=label_fontdict)



ax.grid(linewidth=5)

### annotation
xtick_interval = xticks[1] - xticks[0]
for rect_idx, rect in enumerate(rects):
    y = rect.get_y()
    height = rect.get_height()
    width = rect.get_width()

    ax.text(width + xtick_interval*0.1,
            y + height/2,
            str(width)+'%',
            fontdict=annot_fontdict)
```



## 2. Exercise 4-02




### 3. Exercise 4-03

## DeepVCP: An End-to-End Deep Neural Network for Point Cloud Registration

Weixin Lu   Guowei Wan   Yao Zhou   Xiangyu Fu   Pengfei Yuan   Shiyu Song\*

Baidu Autonomous Driving Technology Department (ADT)

{luweixin, wanguowei, zhouyao, fuxiangyu, yuanpengfei, songshiyu}@baidu.com



### 3. Exercise 4-03

```
import matplotlib.pyplot as plt
import numpy as np

### data setting
ex_name = ['Kitti Dataset', 'Apollo-SouthBay Dataset']
labels = ['ICP-Po2Po', 'ICP-Po2PI', 'G-ICP',
          'AA-ICP', 'NDT-P2d', 'CPD',
          '3DFeat-Net', 'Ours']
xticks = np.arange(len(labels))

kitti_data = [8.17, 2.92, 6.92, 5.24, 8.73,
              3241.29, 15.02, 2.3]
apollo_data = [6.33, 1.69, 3.94, 4.25, 7.44,
               2566.02, 11.92, 2.07]

fig, ax = plt.subplots(figsize = (22,10))
ax.set_yscale('log')

### bar plotting
WIDTH = 0.25
rect1 = ax.bar(xticks - WIDTH/2 - 0.03,
               kitti_data,
               width=WIDTH,
               label=ex_name[0])
rect2 = ax.bar(xticks + WIDTH/2 + 0.03,
               apollo_data,
               width=WIDTH,
               label=ex_name[1])
```

```
### legend customizing
ax.legend(loc = 'upper center',
          bbox_to_anchor = (0.5, -0.3),
          fontsize = 30,
          ncol = len(ex_name))

### tick & ticklabel customizing
yticks = [10**i for i in range(5)]
x_tick_fontdict = {'size':30,
                  'weight':'semibold',
                  'rotation':40}
y_tick_fontdict = x_tick_fontdict.copy()
del y_tick_fontdict['rotation']
ax.set_yticks(yticks)
ax.set_yticklabels(yticks,
                  fontdict=y_tick_fontdict)
ax.set_yticks([], minor = True)
ax.set_xticks(xticks)
ax.set_xticklabels(labels,
                  fontdict=x_tick_fontdict)
ax.tick_params(axis = 'both',
               size = 0)
```

### 3. Exercise 4-03

```
### grid customizing
ax.grid(axis = 'y',
        linewidth = 4,
        alpha = 0.4)
ax.set_axisbelow(True)

### spine customizing
for spine_idx, spine_loc in enumerate(ax.spines):
    ax.spines[spine_loc].set_visible(False)

### annotation
yticks = ax.get_yticks()
ytick_interval = yticks[1] - yticks[0]
annot_fontdict = {'size': 30,
                  'rotation': 90,
                  'va': 'bottom',
                  'ha': 'center'}
```



```
for rect in rect1:
    height = rect.get_height()
    width = rect.get_width()
    x = rect.get_x()

    ax.text(x + width/2,
            height + ytick_interval*0.2,
            str(height),
            fontdict=annot_fontdict)

for rect in rect2:
    height = rect.get_height()
    width = rect.get_width()
    x = rect.get_x()


    ax.text(x + width/2,
            height + ytick_interval*0.2,
            str(height),
            fontdict=annot_fontdict)
```

3. Exercise 4-03





## 4. Exercise 4-04



## 4. Exercise 4-04

```
import matplotlib.pyplot as plt
import matplotlib.cm as cm
import numpy as np

### data setting
category_names = ['Strongly disagree', 'Disagree',
                  'Neither agree nor disagree', 'Agree', 'Strongly agree']

results = {
    'Question 1': [10, 15, 17, 32, 26],
    'Question 2': [26, 22, 29, 10, 13],
    'Question 3': [35, 37, 7, 2, 19],
    'Question 4': [32, 11, 9, 15, 33],
    'Question 5': [21, 29, 5, 5, 40],
    'Question 6': [8, 19, 5, 30, 38]
}

### data preprocessing
labels = list(results.keys())
data = np.array(list(results.values()))
data_idx = np.arange(data.shape[0])
data_cum = data.cumsum(axis=1)
cmap = cm.get_cmap('RdYlGn')
category_colors = cmap(np.linspace(0.15, 0.85, data.shape[1]))
```

```
### ax customizing
fig, ax = plt.subplots(figsize=(9.2, 5))
ax.invert_yaxis()
ax.xaxis.set_visible(False)
ax.set_xlim([0, 100])

for i, (colname, color) in enumerate(zip(category_names, category_colors)):
    ### bar plotting
    widths = data[:, i]
    starts = data_cum[:, i] - widths
    ax.barh(labels, widths, left=starts, height=0.5,
            label=colname, color=color)
    xcenters = starts + widths / 2

    ### annotation
    r, g, b, _ = color
    text_color = 'white' if r * g * b < 0.5 else 'darkgrey'
    for y, (x, c) in enumerate(zip(xcenters, widths)):
        ax.text(x, y, str(int(c)), ha='center', va='center',
                color=text_color)

    ### legend customizing
    ax.legend(loc='lower left',
            bbox_to_anchor=(0, 1),
            fontsize='small',
            ncol=len(category_names))
```

# Python for Data Visualization

## -Chapter.4 Bar Plot -

### 4-05. Exercises

1. Exercise 4-01
2. Exercise 4-02
3. Exercise 4-03
4. Exercise 4-04