# Port Tours Available

#### **UNF:**

PORT(port\_code, port\_name, country\_code, country\_name, (porttemp\_month, porttemp\_avghigh, porttemp\_avglow), (tour\_num, tour\_name, tour\_desc, tour\_hrsreq, tour\_cost, tour\_wheelchair, tour\_availability, tour\_starttime))

#### **1NF**:

PORT(**port code**, port name, country code, country name)

PORT\_TEMPERATURE(port\_code, porttemp\_month, porttemp\_avghigh, porttemp\_avglow)

TOUR(<u>port\_code, tour\_num</u>, tour\_name, tour\_desc, tour\_hrsreq, tour\_cost, tour\_wheelchair, tour\_availability, tour\_starttime)

# **Partial Dependencies:**

No partial dependencies present

#### 2NF:

PORT(**port\_code**, port\_name, country\_code, country\_name)

PORT\_TEMPERATURE(**port\_code, porttemp\_month**, porttemp\_avghigh, porttemp\_avglow)

TOUR(<u>port\_code, tour\_num</u>, tour\_name, tour\_desc, tour\_hrsreq, tour\_cost, tour\_wheelchair, tour\_availability, tour\_starttime)

#### **Transitive Dependencies:**

country\_code -> country\_name

#### 3NF:

PORT(port code, port name, country code)

COUNTRY(**country code**, country name)

PORT\_TEMPERATURE(**port code, porttemp month**, porttemp\_avghigh, porttemp\_avglow)

TOUR(<u>port\_code</u>, <u>tour\_num</u>, tour\_name, tour\_desc, tour\_hrsreq, tour\_cost, tour\_wheelchair, tour\_availability, tour\_starttime)

### **Full Dependencies:**

```
port_code -> port_name, country_code
country_code -> country_name
port_code, porttemp_month -> porttemp_avghigh, porttemp_avglow
port_code, tour_num -> tour_name, tour_desc, tour_hrsreq, tour_cost, tour_wheelchair, tour_availability, tour_starttime
```

# **Tour Participation Report**

#### **UNF:**

TOUR\_INSTANCE(port\_code, tour\_num, tour\_name, tour\_date, tour\_starttime, (pass\_id, pass\_name, pass\_lang, cruise\_id, cruise\_name, payment\_received)

#### **1NF:**

TOUR\_INSTANCE(<u>port\_code, tour\_num, tour\_date</u>, tour\_name, tour\_starttime)

TOUR\_PASSENGER(<u>port\_code, tour\_num, tour\_date, pass\_id</u>, pass\_name, pass\_lang, cruise\_id, cruise\_name, payment\_received)

## **Partial Dependencies:**

```
port_code, tour_num -> tour_name, tour_starttime
pass_id -> pass_name, pass_lang, cruise_id, cruise_name
```

#### 2NF:

TOUR\_INSTANCE(<u>port\_code</u>, <u>tour\_num</u>, tour\_date)

TOUR(<u>port\_code</u>, <u>tour\_num</u>, tour\_name, tour\_starttime)

TOUR\_PASSENGER(<u>port\_code</u>, <u>tour\_num</u>, <u>pass\_id</u>, payment\_received)

PASSENGER(<u>pass\_id</u>, pass\_name, pass\_lang, cruise\_id, cruise\_name)

### **Transitive Dependencies:**

cruise\_id -> cruise\_name

#### 3NF:

TOUR\_INSTANCE(<u>port\_code</u>, <u>tour\_num</u>, tour\_date)

TOUR(<u>port\_code</u>, <u>tour\_num</u>, tour\_name, tour\_starttime)

TOUR\_PASSENGER(<u>port\_code</u>, <u>tour\_num</u>, <u>pass\_id</u>, payment\_received)

PASSENGER(<u>pass\_id</u>, pass\_name, pass\_lang, cruise\_id, cruise\_name)

CRUISE(cruise\_id, cruise\_name)

# **Full Dependencies:**

```
port_code, tour_num -> tour_name, tour_starttime
port_code, tour_num, pass_id -> payment_received
pass_id -> pass_name, pass_lang, cruise_id
cruise_id -> cruise_name
```

# **Collected 3NF Relations**

- 1. PORT(<u>port\_code</u>, port\_name, country\_code)
- 2. COUNTRY(**country code**, country name)
- 3. PORT\_TEMPERATURE(<u>port\_code</u>, <u>porttemp\_month</u>, porttemp\_avghigh, porttemp\_avglow)
- 4. TOUR(<u>port\_code, tour\_num</u>, tour\_name, tour\_desc, tour\_hrsreq, tour\_cost, tour\_wheelchair, tour\_availability, tour\_starttime)
- 5. TOUR\_INSTANCE(<u>port code, tour num, tour date</u>)
- 6. TOUR(port code, tour num, tour name, tour starttime)
- 7. TOUR\_PASSENGER(port\_code, tour\_num, pass\_id, payment\_received)
- 8. PASSENGER(pass id, pass name, pass lang, cruise id)
- 9. CRUISE(cruise id, cruise name)

# **Attribute Synthesis**

- 1. PORT(<u>port\_code</u>, port\_name, country\_code)
- 2. COUNTRY(**country code**, country name)
- 3. PORT\_TEMPERATURE(<u>port\_code</u>, <u>porttemp\_month</u>, porttemp\_avghigh, porttemp\_avglow)
- 4 & 6. TOUR(**port code, tour num**, tour\_name, tour\_desc, tour\_hrsreq, tour\_cost, tour\_wheelchair, tour\_availability, tour\_starttime)
- 5. TOUR\_INSTANCE(<u>port\_code</u>, <u>tour\_num</u>, <u>tour\_date</u>)
- 7. TOUR\_INSTANCE\_PASSENGER(<u>port\_code, tour\_num, tour\_date, pass\_id</u>, payment\_received)
- 8. PASSENGER(**pass\_id**, pass\_name, pass\_lang, cruise\_id)
- 9. CRUISE(<u>cruise id</u>, cruise\_name)