

A large red square with a white border, centered on a white background. Inside the square, the text "Sprint2" and "Hong Xin" are displayed in white.

# Sprint2

Hong Xin

# Starting...

1. What is the goal?
  - a. Build static code analyzers that identifies 7 types of bugs for Android apps

# Starting...

## 1. What is the goal?

- a. Build static code analyzers that identifies 7 types of bugs for Android apps
  - i. Runtime errors.
  - ii. Logic errors.
  - iii. Compilation errors.
  - iv. Syntax errors.
  - v. Interface errors.
  - vi. Resource errors.
  - vii. Arithmetic errors.

# Starting...


## 1. What is the goal?

- a. Build static code analyzers that identifies 7 types of bugs for Android apps
  - i. Runtime errors.
  - ii. Logic errors.
  - iii. Compilation errors.
  - iv. Syntax errors.
  - v. Interface errors.
  - vi. Resource errors.
  - vii. Arithmetic errors.

## 2. Why do we care?

- a. automatically vs manually
- b. Customize analyzer based on different types of Android apps

1. The ToDoList app is done
2. I am in the process of training model



# Definition of Architecture

1. Phase 1: Build an Android App and use ML classifiers to measure the accuracy of Detekt library

# Definition of Architecture

1. Phase 1: Build an Android App and use ML classifiers to measure the accuracy of Detekt library
2. Phase 2: Use feature vectors to train different types of classifiers and benchmarking their performance to Detekt's performance. Then, select the best classifier

# Definition of Architecture

1. Phase 1: Build an Android App and use ML classifiers to measure the accuracy of Detekt library
2. Phase 2: Use feature vectors to train different types of classifiers and benchmarking their performance to Detekt's performance. Then, select the best classifier
3. Phase 3: Find source codes of a complicated app or build a complicated app and further train those classifiers based on 7 types of most common errors



# Definition of Architecture

1. Phase 1: Build an Android App and use ML classifiers to measure the accuracy of Detekt library
2. Phase 2: Use feature vectors to train different types of classifiers and benchmarking their performance to Detekt's performance. Then, select the best classifier
3. Phase 3: Find source codes of a complicated app or build a complicated app and further train those classifiers based on 7 types of most common errors
4. Phase 4: A static code analyzers that identifies 7 types of programming errors for Android apps

# Technology Selection

1. Development Environment: Android Studio
2. Coding Language: Kotlin
3. Library (Benchmark): Detekt

# Technology Selection

Classifiers:

1. Logistic Regression
2. Naïve Bayes
3. K-Nearest Neighbours
4. Random Forest

Questions?