


Using closures in event listeners



View this example [full screen](#).

JavaScript

JavaScript + HTML

```
function initialize() {  
  var mapOptions = {  
    zoom: 4,  
    center: new google.maps.LatLng(-25.363882, 131.044922)  
  };  
  
  var map = new google.maps.Map(document.getElementById('map-canvas'),  
    mapOptions);  
  
  // Add 5 markers to the map at random locations  
  var southWest = new google.maps.LatLng(-31.203405, 125.244141);  
  var northEast = new google.maps.LatLng(-25.363882, 131.044922);  
  
  var bounds = new google.maps.LatLngBounds(southWest, northEast);  
  map.fitBounds(bounds);  
  
  var lngSpan = northEast.lng() - southWest.lng();  
  var latSpan = northEast.lat() - southWest.lat();  
  
  for (var i = 0; i < 5; i++) {
```

```
var position = new google.maps.LatLng(
    southWest.lat() + latSpan * Math.random(),
    southWest.lng() + lngSpan * Math.random());
var marker = new google.maps.Marker({
    position: position,
    map: map
});

marker.setTitle((i + 1).toString());
attachSecretMessage(marker, i);
}
}

// The five markers show a secret message when clicked
// but that message is not within the marker's instance data
function attachSecretMessage(marker, num) {
    var message = ['This', 'is', 'the', 'secret', 'message'];
    var infowindow = new google.maps.InfoWindow({
        content: message[num]
    });

    google.maps.event.addListener(marker, 'click', function() {
        infowindow.open(marker.get('map'), marker);
    });
}

google.maps.event.addDomListener(window, 'load', initialize);
```

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#).

Last updated March 17, 2015.