




Sign in

Products

Google Maps API

Google Maps JavaScript API v3

Remove Markers



View this example full screen.

JavaScript | JavaScript + HTML

```
// In the following example, markers appear when the user clicks on the map.
// The markers are stored in an array.
// The user can then click an option to hide, show or delete the markers.
var map;
var markers = [];
function initialize() {
 var haightAshbury = new google.maps.LatLng(37.7699298, -122.4469157);
 var mapOptions = {
    zoom: 12,
    center: haightAshbury,
    mapTypeId: google.maps.MapTypeId.TERRAIN
 };
 map = new google.maps.Map(document.getElementById('map-canvas'),
      mapOptions);
 // This event listener will call addMarker() when the map is clicked.
 google.maps.event.addListener(map, 'click', function(event) {
    addMarker(event.latLng);
```

```
// Adds a marker at the center of the map.
 addMarker(haightAshbury);
// Add a marker to the map and push to the array.
function addMarker(location) {
 var marker = new google.maps.Marker({
    position: location,
    map: map
 });
 markers.push(marker);
// Sets the map on all markers in the array.
function setAllMap(map) {
 for (var i = 0; i < markers.length; i++) {</pre>
    markers[i].setMap(map);
 }
}
// Removes the markers from the map, but keeps them in the array.
function clearMarkers() {
  setAllMap(null);
// Shows any markers currently in the array.
function showMarkers() {
  setAllMap(map);
// Deletes all markers in the array by removing references to them.
function deleteMarkers() {
 clearMarkers();
 markers = [];
}
google.maps.event.addDomListener(window, 'load', initialize);
```

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies.

Last updated March 17, 2015.