

Marker Animations



View this example [full screen](#).

JavaScript

JavaScript + HTML

```
// The following example creates a marker in Stockholm, Sweden
// using a DROP animation. Clicking on the marker will toggle
// the animation between a BOUNCE animation and no animation.

var stockholm = new google.maps.LatLng(59.32522, 18.07002);
var parliament = new google.maps.LatLng(59.327383, 18.06747);
var marker;
var map;

function initialize() {
  var mapOptions = {
    zoom: 13,
    center: stockholm
  };

  map = new google.maps.Map(document.getElementById('map-canvas'),
    mapOptions);

  marker = new google.maps.Marker({
    map: map,
```

```
draggable:true,  
animation: google.maps.Animation.DROP,  
position: parliament  
});  
google.maps.event.addListener(marker, 'click', toggleBounce);  
}  
  
function toggleBounce() {  
  
  if (marker.getAnimation() != null) {  
    marker.setAnimation(null);  
  } else {  
    marker.setAnimation(google.maps.Animation.BOUNCE);  
  }  
}  
  
google.maps.event.addDomListener(window, 'load', initialize);
```

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#).

Last updated March 17, 2015.