

Googl X Search	•
----------------	---


Sign in

Products

Google Maps API

Google Maps JavaScript API v3

Adding a Custom Overlay



View this example full screen.

JavaScript JavaScript + HTML

```
// This example creates a custom overlay called USGSOverlay, containing
// a U.S. Geological Survey (USGS) image of the relevant area on the map.

// Set the custom overlay object's prototype to a new instance
// of OverlayView. In effect, this will subclass the overlay class.
// Note that we set the prototype to an instance, rather than the
// parent class itself, because we do not wish to modify the parent class.

var overlay;
USGSOverlay.prototype = new google.maps.OverlayView();

// Initialize the map and the custom overlay.

function initialize() {
    var mapOptions = {
        zoom: 11,
        center: new google.maps.LatLng(62.323907, -150.109291),
        mapTypeId: google.maps.MapTypeId.SATELLITE
    };
```

```
var map = new google.maps.Map(document.getElementById('map-canvas'), mapOptions);
 var swBound = new google.maps.LatLng(62.281819, -150.287132);
 var neBound = new google.maps.LatLng(62.400471, -150.005608);
 var bounds = new google.maps.LatLngBounds(swBound, neBound);
 // The photograph is courtesy of the U.S. Geological Survey.
 var srcImage = 'https://developers.google.com/maps/documentation/javascript/';
 srcImage += 'examples/full/images/talkeetna.png';
 // The custom USGSOverlay object contains the USGS image,
 // the bounds of the image, and a reference to the map.
 overlay = new USGSOverlay(bounds, srcImage, map);
/** @constructor */
function USGSOverlay(bounds, image, map) {
 // Initialize all properties.
 this.bounds = bounds;
 this.image_ = image;
 this.map_ = map;
 // Define a property to hold the image's div. We'll
 // actually create this div upon receipt of the onAdd()
 // method so we'll leave it null for now.
 this.div_ = null;
 // Explicitly call setMap on this overlay.
 this.setMap(map);
}
* onAdd is called when the map's panes are ready and the overlay has been
* added to the map.
*/
USGSOverlay.prototype.onAdd = function() {
 var div = document.createElement('div');
 div.style.borderStyle = 'none';
 div.style.borderWidth = '0px';
 div.style.position = 'absolute';
 // Create the img element and attach it to the div.
 var img = document.createElement('img');
 img.src = this.image_;
 img.style.width = '100%';
 img.style.height = '100%';
 img.style.position = 'absolute';
 div.appendChild(img);
 this.div = div;
 // Add the element to the "overlayLayer" pane.
 var panes = this.getPanes();
 panes.overlayLayer.appendChild(div);
};
```

```
USGSOverlay.prototype.draw = function() {
 // We use the south-west and north-east
 // coordinates of the overlay to peg it to the correct position and size.
 // To do this, we need to retrieve the projection from the overlay.
 var overlayProjection = this.getProjection();
 // Retrieve the south-west and north-east coordinates of this overlay
 // in LatLngs and convert them to pixel coordinates.
 // We'll use these coordinates to resize the div.
 var sw = overlayProjection.fromLatLngToDivPixel(this.bounds_.getSouthWest());
 var ne = overlayProjection.fromLatLngToDivPixel(this.bounds_.getNorthEast());
 // Resize the image's div to fit the indicated dimensions.
 var div = this.div_;
 div.style.left = sw.x + 'px';
 div.style.top = ne.y + 'px';
 div.style.width = (ne.x - sw.x) + 'px';
 div.style.height = (sw.y - ne.y) + 'px';
};
// The onRemove() method will be called automatically from the API if
// we ever set the overlay's map property to 'null'.
USGSOverlay.prototype.onRemove = function() {
 this.div_.parentNode.removeChild(this.div_);
 this.div = null;
};
google.maps.event.addDomListener(window, 'load', initialize);
```

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies.

Last updated March 17, 2015.