deeplearning.ai

One hidden layer Neural Network

Derivatives of activation functions

Sigmoid activation function



$$g(z) = \frac{1}{1+e^{-z}}$$

$a = g(z) = \frac{1}{1+e^{-z}}$

$g'(z) = \frac{d}{dz} g(z)$ = slope of $g(x)$ at z

$= \frac{1}{1+e^{-z}} \left(1 - \frac{1}{1+e^{-z}}\right)$

$= g(z)\left(1 - g(z)\right)$ ←

$= a(1-a)$

$g'(z) = a(1-a)$ ↑

$z = 10$. $g(z) \approx 1$

$\frac{d}{dz} g(z) \approx 1\,(1-1) \approx 0$

$z = -10$ $g(z) \approx 0$

$\frac{d}{dz} g(z) \approx 0 \cdot (1-0) \approx 0$

$z = 0$ $g(z) = \frac{1}{2}$

$\frac{d}{dz} g(z) = \frac{1}{2}\left(1 - \frac{1}{2}\right) = \frac{1}{4}$

Andrew Ng

Tanh activation function



$$g(z) = \tanh(z)$$

$$= \frac{e^z - e^{-z}}{e^z + e^{-z}}$$

$$g'(z) = \frac{d}{dz} g(z) = \text{slope of } g(z) \text{ at } z$$

$$= 1 - (\tanh(z))^2$$

$z = 10 \quad \tanh(z) \approx 1$

$g'(z) \approx 0$

$z = -10 \quad \tanh(z) \approx -1$

$g'(z) \approx 0$

$z = 0 \quad \tanh(z) = 0$

$g'(z) = 1$

$a = g(z)$, $\quad g'(z) = 1 - a^2$

ReLU and Leaky ReLU



ReLU

$g(z) = \max(0, z)$

$g'(z) = \begin{cases} 0 & \text{if } z < 0 \\ 1 & \text{if } z \geq 0 \end{cases}$

~~undefined if $z = 0$~~

$z = 0.0000\ldots0$

g prime then becomes what's called s sub gradient of the activation function g(z), which is why gradient descent still works. But you can think of that the chance of z being you know zero point exactly 0 0 0 0 0 is so small that it almost doesn't matter what you set the derivative to be equal to when z equal to zero. So in practice this is what people implement for the derivative of z.



Leaky ReLU

$g(z) = \max(0.01z, z)$

$g'(z) = \begin{cases} 0.01 & \text{if } z < 0 \\ 1 & \text{if } z \geq 0 \end{cases}$

Andrew Ng