

| <b>TEST REPORT</b><br><b>IEC 60068-2-78:2012: Damp heat , steady state</b> |                                                                                                                                                        |
|----------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Date of issue</b> .....:                                                | 2024-07-12                                                                                                                                             |
| <b>Standard</b> ..... :                                                    | IEC 60068-2-78:2012: Damp heat , steady state                                                                                                          |
| <b>Procedure deviation</b> ..... :                                         | N/A                                                                                                                                                    |
| <b>Non-standard test method</b> .....:                                     | N/A                                                                                                                                                    |
| <b>Type of test object</b> .....:                                          | Infrared No-Touch Forehead Thermometer                                                                                                                 |
| <b>Trademark</b> ..... :                                                   | N/A                                                                                                                                                    |
| <b>Model/type reference</b> .....:                                         | PT9L                                                                                                                                                   |
| <b>Report No</b> .....                                                     | ETX202303-07-078-05                                                                                                                                    |
| <b>Testing period</b> .....:                                               | 2024.07.10-2024.07.11                                                                                                                                  |
| <b>Manufacturer</b> ..... :                                                | ANDON HEALTH CO., LTD.                                                                                                                                 |
| <b>Address</b> .....:                                                      | No.3 JinPing Street, YaAn Road, Nankai District, Tianjin, China                                                                                        |
| <b>Test laboratory</b> .....<br><b>Address</b> .....                       | Tianxu(Tianjin)Testing Technology Service Co.,LTD<br>101, First floor, Building L, No.3 JinPing Street, Ya An Road,<br>Nankai District, Tianjin, China |

Complied by: \_\_\_\_\_ (Kang Yanli) Date: \_\_\_\_\_

Reviewed by: \_\_\_\_\_ (Guan Qingxiang) Date: \_\_\_\_\_

| Clause         | Requirement + Test                                                                                                                                                                                                                                                                      | Result - Remark | Verdict |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|
| Damp heat test | The sample is in normal working condition and put into the programmable constant temperature and humidity test chamber. The temperature and humidity of the test box are adjusted to 40 ° C and 95% RH. After the temperature and humidity are stable, it is maintained for 14.8 hours. |                 | /       |

ATTACHMENT FILE 1 photos of the EUT



--- End of Test Report ---