

# Putting it All Together

Templates

Inheritance

Reference Counting

Smart Pointers


Reference: *C++ Strategies and Tactics*, Robert Murray, 1993

# Goals

- Introduce the code for maintaining reference counts
  - A reference count is a count of the number of times an object is shared
  - Pointer manipulations have to maintain the count
- Class UCObject holds the count
  - "Use-counted object"
- UCPointer is a *smart pointer* to a UCObject
  - A smart pointer is an object defined by a class
  - Implemented using a template
  - Overloads operator-> and unary operator\*

# Reference counts in action

```
String abc("abcdef");
```




Shared memory maintains a count of how many times it is shared

# Reference counts in action


```
String abc("abcdef");
```

```
String def = abc; // shallow copy of abc
```



# Reference counts in action

```
String abc("abcdef");  
String def = abc;      // shallow copy of abc  
abc = "Hello world";   // copy on write
```



# Reference counting

- Each sharable object has a counter
- Initial value is 0
- Whenever a pointer is assigned:


```
p = q;
```

- Have to do the following


```
p->decrement(); // p's count will decrease
```

```
p = q;
```

```
q->increment(); // q/p's count will increase
```



# The four classes involved



# Reusing reference counting

```
#include <assert.h>
class UCOBJECT {
public:
    UCOBJECT() : m_refCount(0) { }
    virtual ~UCOBJECT() { assert(m_refCount == 0); };
    UCOBJECT(const UCOBJECT&) : m_refCount(0) { }
    void incr() { m_refCount++; }
    void decr();
    int references() { return m_refCount; }
private:
    int m_refCount;
};
```



# UCObject continued

```
inline void UCObject::decr() {  
    m_refCount -= 1;  
    if (m_refCount == 0) {  
        delete this;  
    }  
}
```

- "Delete this" is legal
  - But don't use *this* afterwards!

# Class UCPointer

```
template <class T>
class UCPointer {
private:
    T* m_pObj;
    void increment() { if (m_pObj) m_pObj->incr(); }
    void decrement() { if (m_pObj) m_pObj->decr(); }
public:
    UCPointer(T* r = 0) : m_pObj(r) { increment(); }
    ~UCPointer() { decrement(); };
    UCPointer(const UCPointer<T> & p);
    UCPointer& operator=(const UCPointer<T> &);
    T* operator->() const;
    T& operator*() const { return *m_pObj; };
};
```

# UCPointer copy constructor

```
template <class T>
UCPointer<T>::UCPointer(const UCPointer<T> & p) {
    m_pObj = p.m_pObj;
    increment();
}
```

# UCPointer assignment

```
template <class T>
UCPointer<T>&
UCPointer<T>::operator=(const UCPointer<T>& p) {
    if (m_pObj != p.m_pObj) {
        decrement();
        m_pObj = p.m_pObj;
        increment();
    }
    return *this;
}
```

# The -> Operator

- `operator->()` is a unary operator
  - Result must support the -> operation
- C++ allows you to overload
  - `[]` -- subscripting
  - `()` -- "function call"
  - `-->()` -- pointer chasing
  - `*()` -- unary pointer dereference

# The UCPointer -> operator


```
template<class T>
T* UCPointer<T>::operator->() const {
    return m_pObj;
}
```

- **Example: Shape inherits from UCObject.**

```
Ellipse elly(200F, 300F);
UCPointer<Shape> p(&elly);
p->render(); // calls Ellipse::render() on
elly!
```

# Envelope and Letter

- Envelope provides protection
- Letter contains the contents



# String Class

```
class String {  
public:  
    String(const char *);  
    ~String();  
    String(const String&);  
    String& operator=(const String&);  
    int operator==(const String&) const;  
    String operator+(const String&) const;  
    int length() const;  
    operator const char*() const;  
private:  
    UCPointer<StringRep> m_rep;  
};
```



# Class StringRep

```
class StringRep : public UObject {
public:
    StringRep(const char *);
    ~StringRep();
    StringRep(const StringRep&);
    int length() const { return strlen(m_pChars); }
    int equal(const StringRep&) const;
private:
    char *m_pChars;
    // reference semantics -- no assignment op!
    void operator=(const StringRep&) { }
};
```

# StringRep implementation

```
StringRep::StringRep(const char *s) {  
    if (s) {  
        int len = strlen(s) + 1;  
        m_pChars = new char[len];  
        strcpy(m_pChars, s);  
    } else {  
        m_pChars = new char[1];  
        *m_pChars = '\\0';  
    }  
}  
  
StringRep::~~StringRep() {  
    delete [] m_pChars;  
}
```

# StringRep implementation

```
StringRep::StringRep(const StringRep& sr) {  
    int len = sr.length();  
    m_pChars = new char[len + 1];  
    strcpy(m_pChars, sr.m_pChars);  
}
```

```
int StringRep::equal(const StringRep& sp)  
const {  
    return (strcmp(m_pChars, sp.m_pChars) ==  
0);  
}
```

# String implementation

```
String::String(const char *s) : m_rep(0) {  
    m_rep = new StringRep(s);  
}
```

```
String::~~String() {}
```

// Again, note constructor for rep in list.

```
String::String(const String& s) : m_rep(s.m_rep) {  
}
```

```
String&
```

```
String::operator=(const String& s) {  
    m_rep = s.m_rep; // let smart pointer do work!  
    return *this;  
}
```

# String implementation

```
int
String::operator==(const String& s) const {
    // overloaded -> forwards to StringRep
    return m_rep->equal(*s.m_rep); // smart
    ptr *
}
```

```
int
String::length() const {
    return m_rep->length();
}
```

# Critique

- UCPointer maintains reference counts
- UCObject hides the details of the count  
String is very clean
- StringRep deals only with string storage and manipulation
- UCObject and UCPointer are reusable
- Objects with cycles of UCPointer will never be deleted

# Other smart pointers

- Standard library holder for raw pointers on stack
- Releases resource when destroyed (latest)

```
template <class X> std::auto_ptr {  
public:  
    explicit auto_ptr(X* = 0) throw();  
    auto_ptr(auto_ptr&) throw();  
    auto_ptr& operator=(auto_ptr&) throw();  
    ~auto_ptr();  
    X& operator*() const throw();  
    X* operator->() const throw();  
    ...  
};
```