

<div>✕ True-or-False 10</div> <div>A. Multiple-Choice - 1 10</div> <div>A Fill-in-Blank 9</div> <div>🔒 Fill-in-Blank - P 3</div>		
1-1	catch (type p) acts very much like a parameter in a function. Once the exception is caught, you can access the thrown value from this parameter in the body of a catch block.。(2分)	Author: 张德慧 Organization: 西安邮电大学
<div><div><input checked="" type="radio"/> T</div><div><input type="radio"/> F</div></div>		
1-1	Accepted (2 point(s))	
1-2	Insertter << can be used to output all kinds of primitive types, including the pointers. (2分)	Author: 翁恺 Organization: 浙江大学
<div><div><input type="radio"/> T</div><div><input type="radio"/> F</div></div>		
1-2	Accepted (2 point(s))	
1-3	The reason inline functions are introduced into the C++ is to reduce the complecity of space, i.e. to shorten the code. (2分)	Author: 翁恺 Organization: 浙江大学
<div><div><input type="radio"/> T</div><div><input checked="" type="radio"/> F</div></div>		
1-3	Accepted (2 point(s))	
1-4	In C++, only existing operators can be overloaded. (2分)	Author: 张德慧 Organization: 西安邮电大学
<div><div><input checked="" type="radio"/> T</div><div><input type="radio"/> F</div></div>		
1-4	Accepted (2 point(s))	
1-5	If you are not interested in the contents of an exception object, the catch block parameter may be omitted.。(2分)	Author: 张德慧 Organization: 西安邮电大学
<div><div><input type="radio"/> T</div><div><input checked="" type="radio"/> F</div></div>		
1-5	Wrong Answer (0 point(s))	
1-6	It is possible to access any item in a vector directly via its index. (2分)	Author: 翁恺 Organization: 浙江大学
<div><div><input checked="" type="radio"/> T</div><div><input type="radio"/> F</div></div>		
1-6	Accepted (2 point(s))	
1-7	Functions with the same name can be identified via namespaces. (2分)	Author: 翁恺 Organization: 浙江大学
<div><div><input checked="" type="radio"/> T</div><div><input type="radio"/> F</div></div>		
1-7	Accepted (2 point(s))	
1-8	To make functions overloaded, the parameter list of the functions have to be different from each other. (2分)	Author: 翁恺 Organization: 浙江大学
<div><div><input type="radio"/> T</div><div><input checked="" type="radio"/> F</div></div>		
1-8	Wrong Answer (0 point(s))	
1-9	Constructors are able to be declared as virtual. (2分)	Author: 翁恺 Organization: 浙江大学
<div><div><input type="radio"/> T</div><div><input checked="" type="radio"/> F</div></div>		
1-9	Accepted (2 point(s))	
1-10	Manipulators are objects to be inserted or extracted into/from streams. (2分)	Author: 翁恺 Organization: 浙江大学
<div><div><input checked="" type="radio"/> T</div><div><input type="radio"/> F</div></div>		
1-10	Accepted (2 point(s))	