

Report Virtual Sound Sources (Lab 2)

Andreas Johann Hörner

14.03.2014

TTT4170 Audio Technology

Lab group:

- Andreas Johann Hörner
- Milan Stojkovic
- Andreas Ulvoen

Report delivered:

Innhold

1	Introduction	1
2	Theory	1
3	Measurements	1
3.1	Equipment	1
3.2	stereo vs. dummyhead recording	1
3.3	sound source deviation SPL	2
3.4	sound source deviation Δt	2
4	Calculations	2
4.1	calculation of ϕ_{SPL}	2
4.2	calculation of $\phi_{timedifference}$	4
5	Conclusion	6
6	Appendix	7
6.1	Example calculations	7

Summary

In this laboratory virtual sound sources are handled. Stereo recordings with a xy-stereo microphone pair as well as a recording with a dummy head were made and compared both at loudspeaker and headphone listening. There it can be obtained, that directional hearing is possible with headphones, where the virtual source location can be done easier with the dummy head recording. When using loudspeakers the virtual sound source always has a position between the two loudspeakers. A directional representation of the real sound source is not possible.

In an other listening test the influence of sound pressure level differences as well as time delays were obtained. There it can be found out, that the virtual sound source moves to the louder or earlier sound source. A special thing occurs when at time difference listening test. When the time difference gets too big, the two sound sources are obtained as independent ones, a position of a single sound source is not available any more.

1 Introduction

Hearing is important for our lives. Sound effects like time differences and sound pressure differences let us know the position of a sound source and so avoid us from potential safety risk, e.g. in the car traffic. These differences in SPL, time and spectral behaviour of the signal in the two ears can help to get the right position of the source.

In this laboratory the reproducibility of sound source positions with different recording techniques was obtained. As recording techniques xy-stereophony as well as binaural recording with using a dummy head were used. The laboratory mainly was done by human perceiving of recorded signals over both loudspeakers and headphones.

2 Theory

For obtaining the position of a sound source three different characteristics of a sound signal are processed:

- time difference
this is defined by the difference in time which sound arrives earlier at one ear. This is mainly the difference of the sound propagation of the head size. It can be calculated using following formula:

$$\Delta t = \frac{a \cdot (\phi + \sin(\phi))}{c} \quad (1)$$

where

- a : head radius
 - ϕ : angle of sound source regarding to the head position
 - c : speed of sound
- level difference
this can be obtained easily, when the diameter is smaller than the wavelength λ .
 - spectral behaviour

3 Measurements

3.1 Equipment

For this laboratory exercise following equipment was used for the measurements:

- 1 Yamaha Mixing Console (Model: 01v)
- 1 HDD-Recorder (Model: SoundDevices 722)
- 2 microphones (Model: Rde NT5)
- 2 loudspeakers (Model: dynaudio acoustics BM6A)
- 1 dummy head (Model: KUBii)

3.2 stereo vs. dummyhead recording

In this task two recordings were made.

1. One recording was made with a stereo microphone pair. As recording technique xy-stereophony was used. A person speaking was walking around the microphone in an equidistant circle.

2. In an other recording the dummyhead was used. A person walked again around the head and speaked.

After this, the two sound recordings were played over headphones and loudspeakers. Following results can be observed:

results

As result it can be obtained that the sound source with dummyhead recording can be located better when it is at the sides and a little bit harder from back and especially when the sound source is in the front. This can be obtained when using headphones. The same is when using the microphone recording, but the ability to locate is more difficult.

When listening to the recordings on loudspeakers, locating of the sound source is not possible. The sound source appears always between the two loudspeakers, using the dummyhead recording as well as the microphone recording.

3.3 sound source deviation SPL

In this task the position of the virtual sound source regarding to a sound pressure difference between two speakers is measured. Therefore a person speaking was placed in front of a mono microphone and recorded. The reorded signal was played equally strong on two speakers placed in an angle of 60° . A listener was placed 2 meters in front of the loudspeakers, so that a calculation of the deviation of the virtual sound source from the center between the loudspeakers can easily be calculated with a tan-function. The listening position can be seen in figure 1. It can be obtained




Figure 1: Listening position

that with no amplitude difference the sound source appears exactly in the center between the two loudspeakers. With increasing difference of SPL the virtual sound source moves to the speaker with higher sound pressure level. When the sound pressure difference is high enough, the sound is heard as coming only from one speaker. The measured sound source deviation can be seen in table 1 as well as in figure 2.

3.4 sound source deviation Δt

The position of the virtual sound source should be measured with increasing time delay of one loudspeaker. The measured results can be seen in table 2 as well as in figure 3. Until a certain point is reached, the virtual sound source moves to the speaker which sends the sound first. When the time difference between the two speakers is too big (50ms, 100ms), the two loudspeakers seem as two independent sound sources. In the table the position of the first sound signal occuring is listed for these time delays.




Figure 2: Sound source deviation for different SPLs in degrees




Figure 3: Sound source deviation for different time differences in ms

SPL difference dB	deviation from center m	ϕ rad	ϕ $^\circ$
0	0	0	0
3	0.08	0.04	2.29
6	0.23	0.116	6.62
9	0.36	0.182	10.43
12	0.57	0.293	16.79
20	0.81	0.429	24.56

Tabell 1: SPL deviation

time difference ms	deviation from center m	ϕ rad	ϕ $^\circ$
0	0	0	0
0.5	0.28	0.245	14.02
1	0.65	0.337	19.31
2	0.71	0.371	21.24
20	0.68	0.354	20.27
50	0.62	0.320	18.35
100	0.85	0.453	25.93

Tabell 2: time deviation

4 Calculations

4.1 calculation of ϕ_{SPL}

$$\phi_{rad_{3dB}} = \tan\left(\frac{0.08m}{2m}\right) = 0.04$$

$$\phi_{deg_{3dB}} = \phi_{rad_{3dB}} \cdot \frac{180^\circ}{\pi} = 2.29^\circ$$

$$\phi_{rad_{6dB}} = \tan\left(\frac{0.23m}{2m}\right) = 0.116$$

$$\phi_{deg_{6dB}} = \phi_{rad_{6dB}} \cdot \frac{180^\circ}{\pi} = 6.62^\circ$$

$$\phi_{rad_{9dB}} = \tan\left(\frac{0.36m}{2m}\right) = 0.182$$

$$\phi_{deg_{9dB}} = \phi_{rad_{9dB}} \cdot \frac{180^\circ}{\pi} = 10.43^\circ$$

$$\phi_{rad_{12dB}} = \tan\left(\frac{0.57m}{2m}\right) = 0.293$$

$$\phi_{deg_{12dB}} = \phi_{rad_{12dB}} \cdot \frac{180^\circ}{\pi} = 16.79^\circ$$

$$\phi_{rad_{20dB}} = \tan\left(\frac{0.81m}{2m}\right) = 0.429$$

$$\phi_{deg_{20dB}} = \phi_{rad_{20dB}} \cdot \frac{180^\circ}{\pi} = 24.56^\circ$$

4.2 calculation of $\phi_{timedifference}$

$$\phi_{rad_{0.5ms}} = \tan\left(\frac{0.28m}{2m}\right) = 0.245$$

$$\phi_{deg_{0.5ms}} = \phi_{rad_{0.5ms}} \cdot \frac{180^\circ}{\pi} = 14.02^\circ$$

$$\phi_{rad_{1ms}} = \tan\left(\frac{0.65m}{2m}\right) = 0.337$$

$$\phi_{deg_{1ms}} = \phi_{rad_{1ms}} \cdot \frac{180^\circ}{\pi} = 19.31^\circ$$

$$\phi_{rad_{2ms}} = \tan\left(\frac{0.71m}{2m}\right) = 0.371$$

$$\phi_{deg_{2ms}} = \phi_{rad_{2ms}} \cdot \frac{180^\circ}{\pi} = 21.24^\circ$$

$$\phi_{rad_{20ms}} = \tan\left(\frac{0.68m}{2m}\right) = 0.354$$

$$\phi_{deg_{20ms}} = \phi_{rad_{20ms}} \cdot \frac{180^\circ}{\pi} = 20.27^\circ$$

$$\phi_{rad_{50ms}} = \tan\left(\frac{0.62m}{2m}\right) = 0.320$$

$$\phi_{deg_{50ms}} = \phi_{rad_{50ms}} \cdot \frac{180^\circ}{\pi} = 18.35^\circ$$

$$\phi_{rad_{100ms}} = \tan\left(\frac{0.85m}{2m}\right) = 0.453$$

$$\phi_{deg_{100ms}} = \phi_{rad_{100ms}} \cdot \frac{180^\circ}{\pi} = 25.93^\circ$$

5 Conclusion

6 Appendix

6.1 Example calculations