Xprinter®

XP-T230L / T300L

Thermal Receipt Printer

- Water proof, oil proof, dust proof design

- Wifi, Bluetooth option

- Led light and sound alarm

- Wall mountable design

APPLICATIONS

Shopping

Mart

Hospital

Coffee Shop

Restaurant

Ticketing

Express

Factory

XP-T230L / T300L
Thermal Receipt Printer

QR CODE	EASY LOAD	COMPACT DESIGN	HIGH SPEED	AUTO CUTTER	VARIOUS INTERFACE	PAPER WIDTH

Model	XP-T230L	XP-T300L
Printing method	Direct thermal	
Paper width	79.5±0.5mm×φ80mm	
Print width	72mm	58mm/80mm
Column capacity	576 dots/line(adjustable by command)	
Printing speed	230 mm/s Max.	300 mm/s Max.
Interface	USB+Lan (Optional WiFi / Bluetooth)	USB+Serial+Lan
Line spacing	3.75mm (Adjustable by commands)	
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)	

Cutter

Auto cutter	Partial

Barcode Character

Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	T230L:void	T300L: QR CODE / PDF417
Input buffer	64 Kbytes	2048 Kbytes
NV Flash	256 Kbytes	

Power

Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics

Weight	1.78 Kg
Dimensions	198×148×138mm (D×W×H)

Environmental Requirements

Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 80%)

Reliability

Cutter life	1.5 million cuts
Printer head life	150 KM

Software

Emulation	ESC/POS
Driver	Windows/JPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows

ANDROID iOS Windows Linux