Xprinter®

XP-A260M / A300M

Thermal Receipt Printer

- Fast and versatile printing

- Drop in paper loading with auto cutter

- Multi-interface design to meet different user requirements

- Support audible alarm

APPLICATIONS

Shopping

Mart

Hospital

Coffee Shop

Restaurant

Ticketing

Express

Factory

XP-A260M/A300M
Thermal Receipt Printer

QR CODE	EASY LOAD	COMPACT DESIGN	HIGH SPEED	AUTO CUTTER	VARIOUS INTERFACE	PAPER WIDTH

MODEL	XP-A260M	XP-A300M
Printing method	Direct thermal	
Printing speed	260mm/s	300mm/s
Paper width	79.5±0.5 mm	
Printable area	72mm(adjustable by commands)	
Maximum paper diameter	Φ80 mm	
Paper thickness	0.06-0.08mm	
Column capacity	576 dots/line 512 dots/line	
Line space	3.75mm(Changeable by commands)	
Commands	Compatible with ESC/POS	
Interface type	USB+Serial+Lan	
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Dimension	195 ×140×137.5 mm (D×W×H)	
Gross weight	1.05 kg	
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2-dimension code	QR CODE / PDF417	
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)	
Cutter	Partial	
Cutter life	1.5 million cuts	
Print head life	100KM	
Input buffer	64 Kbytes	2048 Kbytes
NV Flash	256 Kbytes	
Power adaptor	AC110V/220V, 50~60Hz	
Power source	DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
Work environment	Temperature: 0~45℃, humidity: 10~80RH%	
Storage environment	Temperature: -10~60℃, humidity: 10~90RH%	
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux	

Windows 7 Windows 8 Windows 10