2023

LED Sequence V3.0

HOSSAM ELWAHSH
EMBEDDED SYSTEMS - LEVEL 1

Table of Contents

System Requirements Specifications 2
Brief 2
Hardware Requirements 2
Software Requirements 2
System Design 3
State Machine Diagram 3
Layered Architecture 4
Project Modules APIs 5
DIO Driver 5
EXI (External Interrupt) Driver 7
LED Driver 8
Button Driver 10
Timer Driver 11
Application 13
Project Tree 13
Project Modules APIs Charts 14
EXI Flowcharts 14
Button API Flowcharts 15
LED API Flowcharts 16
DIO API Flowcharts 19
Timer API Flowcharts 22
Application API Flowcharts 24

LED Sequence V3.0

System Requirements Specifications

Brief

Develop a system that controls 4 LEDs lighting sequence according to button pressing.

Hardware Requirements

- Four LEDs (LED0, LED1, LED2, LED3)
- Two buttons (BUTTON0, BUTTON1)

Software Requirements

1. Initially, all LEDs are OFF
2. Once **BUTTON0** is pressed, **LED0** will blink with **BLINK_1** mode
3. Each press further will make another LED blinks **BLINK_1** mode
4. At the **fifth press**, **LED0** will changed to be **OFF**
5. Each **press further** will make only one LED is **OFF**
6. This will be repeated forever
7. The sequence is described below
    1. Initially (OFF, OFF, OFF, OFF)
    2. Press 1 (BLINK_1, OFF, OFF, OFF)
    3. Press 2 (BLINK_1, BLINK_1, OFF, OFF)
    4. Press 3 (BLINK_1, BLINK_1, BLINK_1, OFF)
    5. Press 4 (BLINK_1, BLINK_1, BLINK_1, BLINK_1)
    6. Press 5 (OFF, BLINK_1, BLINK_1, BLINK_1)
    7. Press 6 (OFF, OFF, BLINK_1, BLINK_1)
    8. Press 7 (OFF, OFF, OFF, BLINK_1)
    9. Press 8 (OFF, OFF, OFF, OFF)
    10. Press 9 (BLINK_1, OFF, OFF, OFF)

8. When BUTTON1 has pressed the blinking on and off durations will be changed
    1. No press → **BLINK_1** mode (**ON**: 100ms, **OFF**: 900ms)
    2. First press → **BLINK_2** mode (**ON**: 200ms, **OFF**: 800ms)
    3. Second press → **BLINK_3** mode (**ON**: 300ms, **OFF**: 700ms)
    4. Third press → **BLINK_4** mode (**ON**: 500ms, **OFF**: 500ms)
    5. Fourth press → **BLINK_5** mode (**ON**: 800ms, **OFF**: 200ms)
    6. Fifth press → **BLINK_1** mode

9. **USE EXTERNAL INTERRUPTS**

System Design

State Machine Diagram

Software used: Microsoft Visio



Software used: Microsoft Visio

LED Sequence V3.0
Layered Architecture



Project Modules APIs

DIO Driver

DIO Macros/Enums:

Type	Name	Values	Desc
`#define`	LOW HIGH	LOW = 0 HIGH = 1	**Macro for digital levels**
`typedef enum`	EN_DIO_PORT_T	• A, B, C, D	**Defines available DIO ports**
`typedef enum`	EN_DIO_DIRECTION_T	• In = 0 • Out = 1	**Defines DIO pin direction**
`typedef enum`	EN_DIO_Error_T	• DIO_OK • DIO_Error	**Defines DIO return error**

DIO Functions:

```
/**
 * Configures pin at given portNumber as input/output
 * @param pinNumber [in] pin number
 * @param portNumber [in] Port to configure
 * @param direction [in] direction for pin enum (IN, OUT)
 */
EN_DIO_Error_T DIO_init(uint8_t pinNumber, EN_DIO_PORT_T portNumber, EN_DIO_DIRECTION_T direction);
```

```
/**
 * Writes pin value for the given port/pin
 * @param pinNumber [in] pin number
 * @param portNumber [in] Port to use
 * @param value [in] value to write
 */
EN_DIO_Error_T DIO_write(uint8_t pinNumber, EN_DIO_PORT_T portNumber, uint8_t value);
```

```
/**
 * Toggles pin value for the given port/pin
 * @param pinNumber [in] pin number
 * @param portNumber [in] Port to use
 */
EN_DIO_Error_T DIO_toggle(uint8_t pinNumber, EN_DIO_PORT_T portNumber);
```

```
/**
 * Reads pin value for the given port/pin and stores it in *value
 * @param pinNumber [in] pin number
 * @param portNumber [in] Port to use
 * @param *value [out] pointer to output pin value into
 */
EN_DIO_Error_T DIO_read(uint8_t pinNumber, EN_DIO_PORT_T portNumber, uint8_t *value);
```

```c
/**
 * Writes a byte to a given PORT
 * @param portNumber [in] Port to use
 * @param byte [in] value to write
 */
EN_DIO_Error_T DIO_port_write(EN_DIO_PORT_T portNumber, uint8_t byte, uint8_t mask);
```

```c
/**
 * Toggles a given PORT
 * @param portNumber [in] Port to use
 * @param mask [in] (optional, 0 to disable)
 */
EN_DIO_Error_T DIO_port_toggle(EN_DIO_PORT_T portNumber, uint8_t mask);
```

```c
/**
 * Toggles pin value for the given port/pin
 * @param pinNumber [in] pin number
 * @param portNumber [in] Port to use
 */
EN_DIO_Error_T DIO_toggle(uint8_t pinNumber, EN_DIO_PORT_T portNumber);
```

EXI (External Interrupt) Driver

EXI Macros/Enums:

Type	Name/Value	Desc
#define	EXT_INT_0 __vector_1	Interrupt vector naming
#define	EXT_INT_1 __vector_2	Interrupt vector naming
#define	EXT_INT_2 __vector_3	Interrupt vector naming
#define	sei() __asm__ __volatile__ ("sei" ::: "memory")	Enables global interrupt
#define	cli() __asm__ __volatile__ ("cli" ::: "memory")	Disables global interrupt
#define	ISR(INT_VECT) void INT_VECT(void) __attribute__ ((signal,used));\ void INT_VECT(void)	ISR definition
typedef enum	typedef enum EN_EXI_INT_t { INT0, INT1 } EN_EXI_INT_t;	Defines Interrupt port names

typedef enum	typedef enum EN_EXI_SENSE_t {
	// Interrupts on low level
	LOW_LEVEL = 0xFC,
	// Interrupts on any logical change
	ANY_LEVEL = 0x01,
	// Interrupts on Falling edge
	FALLING_EDGE = 0x02,
	// Interrupts on Rising edge
	RISING_EDGE = 0x03
	} EN_EXI_SENSE_t;
		Enum for ATmega32 interrupt sense modes

typedef enum	typedef enum EN_EXI_ERROR_t { EXI_OK, EXI_ERROR } EN_EXI_ERROR_t;	Error return type for EXI API

EXI Functions:

```
/**
 * Sets and enables an external interrupt pin with given mode
 * @param interrupt [in] Interrupt number (INT0, INT1)
 * @param interruptSenseMode [in] sense mode enum
 */
EN_EXI_ERROR_t EXI_enableInterrupt(EN_EXI_INT_t interrupt, EN_EXI_SENSE_t interruptSenseMode);
```

```
/**
 * Disables a given interrupt pin
 * @param interrupt [in] enum (INT0, INT1)
 */
EN_EXI_ERROR_t EXI_disableInterrupt(EN_EXI_INT_t interrupt);
```

```
/**
* Disables global interrupts
*  sets I-(7th) bit in SREG to 0
*/
void EXI_disableAll(void); // no return needed
```

LED Driver

LED Macros/Enums:

Type	Name/Value	Desc
typedef enum	typedef enum EN_LED_ERROR_t { LED_OK, LED_ERROR }EN_LED_ERROR_t;	Enum for LED error return

LED Functions:

```
/**
 * Initializes LED on given port & pin
 * @param ledPort [in] LED Port
 * @param ledPin [in] LED Pin number in ledPort
 */
EN_LED_ERROR_t LED_init(EN_DIO_PORT_T ledPort, uint8_t ledPin);
```

```
/**
 * Turns on LED at given port/pin
 * @param ledPort [in] LED Port
 * @param ledPin [in] LED Pin number in ledPort
 */
EN_LED_ERROR_t LED_on(EN_DIO_PORT_T ledPort, uint8_t ledPin);
```

```
/**
 * Turns off LED at given port/pin
 * @param ledPort [in] LED Port
 * @param ledPin [in] LED Pin number in ledPort
 */
EN_LED_ERROR_t LED_off(EN_DIO_PORT_T ledPort, uint8_t ledPin);
```

```
/**
 * Toggles LED at given port/pin
 * @param ledPort [in] LED Port
 * @param ledPin [in] LED Pin number in ledPort
 */
EN_LED_ERROR_t LED_toggle(EN_DIO_PORT_T ledPort, uint8_t ledPin);
```

LED ARRAYS Functions

```
/**
 * Turns on a LED Array at given PORT
 * @param ledPort [in] LED Port
 * @param mask [in] (optional, 0 to disable)
 * \n mask to turn on specific LEDs only | e.g. to only turn on the first LED use 0x01 (0b0000 0001)
 */
EN_LED_ERROR_t LED_array_on(EN_DIO_PORT_T ledPort, uint8_t mask);
```

```
/**
 * Turns off a LED Array at given PORT
 * @param ledPort [in] LED Port
 * @param mask [in] (optional, 0 to disable)
 * \n mask to turn off specific LEDs only | e.g. to only turn off the first LED use 0x01 (0b0000 0001)
 */
EN_LED_ERROR_t LED_array_off(EN_DIO_PORT_T ledPort, uint8_t mask);
```

```
/**
 * Toggles a LED Array at given PORT
 * @param ledPort [in] LED Port
 * @param mask [in] (optional, 0 to disable)
 * \n mask to turn off specific LEDs only | e.g. to only turn off the first LED use 0x01 (0b0000 0001)
 */
EN_LED_ERROR_t LED_array_toggle(EN_DIO_PORT_T ledPort, uint8_t mask);
```

```
/**
 * Blinks LED array once at given port
 * @param ledPort [in] LED Port
 * @param ledPin [in] LED Pin number in ledPort
 * @param onTime [in] Time in which LED will be on (milliseconds)
 * @param offTime [in] Time in which LED will be off (milliseconds)
  * @param mask [in] optional, 0 to disable i.e. blinks all LEDs
 * \n mask to blink specific LEDs only | e.g. to only blink the first LED use 0x01 (0b0000 0001)
 */
void LED_array_blink(EN_DIO_PORT_T ledPort, uint16_t onTime, uint16_t offTime, uint8_t mask);
```

Button Driver

Button Macros/Enums:

Type	Name/Value	Desc
typedef enum	typedef enum EN_ButtonError_t { BUTTON_OK, BUTTON_ERROR }EN_ButtonError_t;	**Button Error Types**

Button Functions:

```
/**
 * Initializes port and pin as button
 * @param buttonPort [in] Port to use
 * @param buttonPin [in] Pin number in port
 */
EN_ButtonError_t BUTTON_init(EN_DIO_PORT_T buttonPort, uint8_t buttonPin);
```

```
// Read Button State
/**
 * Reads button state and stores value in buttonState
 * @param buttonPort [in] Port to use
 * @param buttonPin [in] Pin number in port
 * @param buttonState [out] Store Button State (1:High / 0:Low)
 */
EN_ButtonError_t BUTTON_read(EN_DIO_PORT_T buttonPort, uint8_t buttonPin, uint8_t *
buttonState);
```

Timer Driver

Timer Macros/Enums:

Type	Name/Value	Desc

#define(s)	`/* Microcontroller Related Macros */`
	`#define timerNBits 8`
	`#define SystemClockInMhz 1`
	
	`/* Clears mode bits in timer */`
	`#define TimerClearModes() TCCR0 &= 0xB7`
	
	`/* Clears Clock selection bits */`
	`#define TimerClearClockSelection() TCCR0 &= 0xF8`	

typdef enum	`typedef enum EN_TimerMode_t`
	`{`
	`NORMAL = 0xB7,`
	`CTC = 0x08,`
	`FAST_PWM = 0x48,`
	`PWM_PHASE_CORRECT = 0x40`
	`}EN_TimerMode_t;`
		ATmega32 Timer Modes

typedef enum	`typedef enum EN_ClockSelection_t`
	`{`
	`NoClock = 0xF8, // stops clock - no clock is set`
	`NoPrescaling = 0x01, // clock matches internal clock with no prescaling`
	`Prescale8 = 0x02, // prescale clock /8`
	`Prescale64 = 0x03, // prescale clock /64`
	`Prescale256 = 0x04, // prescale clock /256`
	`Prescale1024 = 0x05, // prescale clock /1024`
	
	`/* External Clock on T0 pin with falling edge */`
	`ExternalFallingEdge = 0x06,`
	
	`/* External Clock on T0 pin with rising edge */`
	`ExternalRisingEdge = 0x07,`
	`}EN_ClockSelection_t; // 1 byte`
		ATmega32 Timer/Counter clock selections

typdef enum	`typedef enum EN_timerError_t`
	`{`
	`OK,`
	`Error`
	`}EN_timerError_t;`
		Error return type for timer driver

Timer Functions:

```
/**
 * Initialize timer-0 with given operating mode
 *  and automatically calculates init start value and overflow count to achieve the
 *  desiredDelayMs (ms)
 * @param operatingMode one of (Normal, CTC, FAST_PWM, PWM_PHASE_CORRECT)
 * @param desiredDelayMs desired delay in milliseconds
 */
EN_timerError_t timer_init(EN_TimerMode_t operatingMode);
```

```
/**
 * blocks for a given delay time before returning
 * @param desiredDelay [in] (ms) delay to wait for - Range 2ms upto 60 seconds, sensitivity ~1.2 ms
 * @return Error if any
 */
void timer_delay(uint16_t desiredDelay);
```

```
/**
 * sets given Prescaler for timer0
 * @param enClockPrescaleSelection [in] prescaler enum
 * @return
 */
static EN_timerError_t timer_start(EN_ClockSelection_t enClockPrescaleSelection);
```

```
/*
*//**
 * Manually set initial timer start value
 * @param timerInitValue [in] value (0 -> 255)
 */
static void timer_setTimerValue(uint8_t timerInitValue);
```

```
/**
 * Resets the timer
 */
void timer_reset();
```

Application

Application Includes:

```
#include "../ECUAL/LED Driver/led.h"
#include "../ECUAL/Button Driver/button.h"
#include "../MCAL/EXI Driver/interrupts.h"
```

Application Functions:

```
/// Application initialization
void App_init();
```

```
/// Start Application routine
void App_Start();
```

Project Tree

```
D:.
    .gitignore
    main.c
    main.h
    README.md

---Application
        application.c
        application.h

---Common
        bit_manipulation.h
        types.h

---Docs
    ---Visio Diagrams
                *.visio
    ---LED Sequence V3.0 - Design.pdf

---ECUAL
    ---Button Driver
            button.c
            button.h

    ---LED Driver
            led.c
            led.h

---MCAL
    |   registers.h
    |
    ---DIO Driver
    |       dio.c
    |       dio.h
    |
    ---Timer Driver
    |       timer.c
    |       timer.h
    |
    ---EXI Driver
            interrupts.c
            interrupts.h

---Proteus
        Proteus_LED_Sequence_V3.0.pdsprj
```

EXI Flowcharts







Button API Flowcharts





LED Driver

EN_LED_ERROR_t LED_init(EN_DIO_PORT_T ledPort, uint8_t ledPin);



LED Driver

EN_LED_ERROR_t LED_on(EN_DIO_PORT_T ledPort, uint8_t ledPin);



LED Driver

EN_LED_ERROR_t LED_off(EN_DIO_PORT_T ledPort, uint8_t ledPin);



LED Driver

EN_LED_ERROR_t LED_toggle(EN_DIO_PORT_T ledPort, uint8_t ledPin);



LED Driver

EN_LED_ERROR_t LED_array_on(EN_DIO_PORT_T ledPort, uint8_t mask)

Led Array ON Function



LED Driver

EN_LED_ERROR_t LED_array_off(EN_DIO_PORT_T ledPort, uint8_t mask)

Led Array OFF Function



LED Driver

EN_LED_ERROR_t LED_array_toggle(EN_DIO_PORT_T ledPort, uint8_t mask)

LED Array Toggle Function



LED Driver

void LED_array_blink(EN_DIO_PORT_T ledPort, uint16_t onTime, uint16_t offTime, uint8_t mask)

LED Array Toggle Function



DIO Driver

EN_DIO_Error_T DIO_init(uint8_t pinNumber,
EN_DIO_PORT_T portNumber,
EN_DIO_DIRECTION_T direction);



DIO Driver

EN_DIO_Error_T DIO_write(uint8_t pinNumber,
EN_DIO_PORT_T portNumber, uint8_t value);



DIO Driver

EN_DIO_Error_T DIO_read(uint8_t pinNumber,
EN_DIO_PORT_T portNumber, uint8_t *value);



DIO Driver

EN_DIO_Error_T DIO_toggle(uint8_t pinNumber,
EN_DIO_PORT_T portNumber);




DIO Driver
EN_DIO_Error_T DIO_port_write(EN_DIO_PORT_T portNumber, uint8_t byte, uint8_t mask)
Start
mask == 0
true
mask = 0xFF
False
Switch `portNumber`
Case `A`
PORT_A = ((NOT(mask)) AND PORT_A) OR (mask AND byte)
Case `B`
PORT_B = ((NOT(mask)) AND PORT_B) OR (mask AND byte)
Case `C`
PORT_C = ((NOT(mask)) AND PORT_C) OR (mask AND byte)
Case `D`
PORT_D = ((NOT(mask)) AND PORT_D) OR (mask AND byte)
Else
RETURN DIO_Error
RETURN DIO_OK
DIO Port Write Function


DIO Driver
EN_DIO_Error_T DIO_port_toggle(EN_DIO_PORT_T portNumber, uint8_t mask)
Start
mask == 0
true
mask = 0xFF
False
Switch `portNumber`
Case `A`
PORT_A = PORT_A XOR `mask`
Case `B`
PORT_D = PORT_D XOR `mask`
Case `C`
PORT_C = PORT_C XOR `mask`
Case `D`
PORT_D = PORT_D XOR `mask`
Else
RETURN DIO_Error
RETURN DIO_OK
DIO Port Write Function

Timer Driver

Timer Delay Function

void timer_delay(uint16_t desiredDelay)



Timer Driver

TIMER INIT FUNCTION

EN_DIO_Error_T DIO_init(uint8_t pinNumber,
EN_DIO_PORT_T portNumber,
EN_DIO_DIRECTION_T direction);



Timer Driver

TIMER START FUNCTION

EN_timerError_t timer_start(EN_ClockSelection_t
enClockPrescaleSelection)



Timer Driver

Timer setValue

void timer_setTimerValue(uint8_t timerInitValue)



Timer Driver

Timer Reset

void timer_reset()

Application API Flowcharts

Application

Globals

```
/* LEDs */
#define LED_0_PORT C
#define LED_0_PIN 0
#define LED_1_PORT C
#define LED_1_PIN 1
#define LED_2_PORT C
#define LED_2_PIN 2
#define LED_3_PORT C
#define LED_3_PIN 3

/* Buttons */
#define BUTTON_0_port D
#define BUTTON_0_PIN 3   // INT0
#define BUTTON_1_port D
#define BUTTON_1_PIN 2   // INT1

/* Magic Numbers */
#define NUMBER_OF_LED_STATES 7

/* Global Variables */
uint8_t state_number = 0;
uint8_t current_blink_mode_index = 1;

/* App Blink Modes */
ST_APP_BLINK_MODES_t appBlinkModes;
ST_APP_BLINK_MODE_t
currentBlinkMode;
```

Globals

Application

void App_init();



Application init function

Application

void App_Start();



Application Start Function


Application
ISR(EXT_INT_0)
Start
Switch
`current blink mode index`
BLINK 1
Set current mode -> BLINK_2
index ++
BLINK 2
Set current mode -> BLINK_3
index ++
BLINK 3
Set current mode -> BLINK_4
index ++
BLINK 4
Set current mode -> BLINK_5
index ++
BLINK 5
Set current mode -> BLINK_1
index = 1
ELSE/DEF
END
ISR function for INT0


Application
ISR(EXT_INT_1)
Start
State_number <
NO_OF_LED_STATES
No
Yes
State_number = 0
State_number++
END
ISR function for INT1