

## Displaying 3D fields on raster devices

**P Quarendon**

IBM UK Scientific Centre, St Clement Street, Winchester,  
Hants SO23 9DR, UK

A system is being implemented at the IBM UK Scientific Centre to display 3D fields. The system generates output intended for raster devices, both displays and printers.

**System outline.** At present the system deals only with potential fields, where a single scalar quantity is given at each point in space. The scalar quantities might represent electrostatic potentials, electron densities or even temperatures. The system is not aware of the physical meaning of the data. In the current implementation, the field is given as a set of sample values on a uniform rectangular grid. Fields can be represented using one or more of the methods described below. The system renders the requested images into a pixel array, and this can be displayed on the various raster devices at the Scientific Centre.

**Equipotential surfaces.** The system allows objects to be defined which have a surface corresponding to a given potential level of a given field. Equipotential surfaces are rendered in the same way as are geometrically defined objects, their surface colour and characteristics can be defined and they are lit similarly. The shading gives a strong impression of the 3D shape of the surface.

**Density clouds.** The most direct way to display a quantity such as an electron density is to render it directly as if it were a physical cloud of electrons. When generating a cloud, control can be exercised over its 'optical depth'. This is the distance that a light ray could travel through the densest part and influences the solidity of resulting shape.

**Colour mapped field values.** Field values are represented using colour. The system allows any surface to be coloured from the value of a field. This includes surfaces produced by geometric construction and those from contouring fields. The technique is best suited to cases when the field value is of most interest on a particular geometric surface, for example a van der Waals or solvent-accessible surface.

**Field direction.** Field direction is indicated using solid arrows. When rendered with hidden surfaces removed, the arrows give some indication of the direction of the field not only in the plane of the display, but also into and out of this plane. Arrows can be placed in a regular grid over the surface of any geometric object. As a further feature, each arrow can be considered as the start of a field line and further arrows added along this field line. The field lines are followed until a local maximum or minimum in the field is reached.

24

Graphics computer-generated receptor mapping as a predictive tool for drug design

**M Hibert, M W Gittos, D N Middlemiss and J R Fozard**

Merrell Dow Research Institute, Strasbourg Centre, 16  
rue d'Ankara 67084, Strasbourg Cedex, France

Computer graphics technology has proven particularly useful in the determination of crystallographic structures and for theoretical mechanistic studies of the interaction between a substrate and a receptor of known or partially elucidated structure. On the other hand, when the receptor structure is totally unknown, the graphics computer has generally been used *a posteriori* to account for structure-activity relationships. *De novo* generated receptor maps have not yet been shown to be a *predictive* tool, probably for two reasons: (i) the method relies on the lock-key model for receptor-substrate interaction and generally neglects the receptor flexibility and the induced fit phenomenon; (ii) it is difficult to ensure that the substrates which are to be compared to perform the mapping actually bind at the same site. An example of where graphics computer-aided receptor mapping technology has led to the *a priori* design of highly optimized ligands is presented here. Our target was the putative 5-HT<sub>1A</sub> receptor which has been recently characterized in the CNS using the specific radioligand [<sup>3</sup>H]-8-hydroxy-*N*-di-*n*-propyl amino tetralin ([<sup>3</sup>H]-8-OH-DPAT)<sup>1</sup>. A VAX 750/PS 300/Sybyl system was used. The starting point for the development of potent and selective *antagonist* ligands was the comparison of four structurally diverse antagonists having moderate affinities ( $pIC_{50} < 7$ ) and no selectivity for the 5-HT<sub>1A</sub> recognition site. Using this model, we have designed several original molecules structurally unrelated to the reference compounds; as predicted, all were highly active. For example, 8-[4-(1,4-benzodioxan-2-yl-methyl-amino)butyl]-8-azaspiro[4,5]decane-7,9-dione (MDL 72832) has nanomolar affinity ( $pIC_{50} = 9.14$ ) for the 5-HT<sub>1A</sub> binding site in rat frontal cortex. Moreover, we successfully predicted the stereochemistry of the interaction and optimized the selectivity of substrates. We have also compared several active 5-HT<sub>1A</sub> receptor *agonists* to provide a steric map of the 5-HT<sub>1A</sub> agonist site. The resultant pharmacophore differed significantly from the antagonist site map. It accounted for: (i) the affinity of all the agonists, (ii) the weak differentiation between *R* and *S* enantiomers of 8-OH-DPAT, (iii) the positive contribution of lipophilic substitution on the basic N atom of substrates, (iv) the positive contribution of the electro-negativity or of the H acceptor properties of substituents in a precise region corresponding to the carbon 8 of 8-OH-DPAT, (v) the negative contribution of substitution in positions 5,6 or 7 of 8-OH-DPAT. Our study demonstrates that graphics computer-generated receptor maps can constitute a predictive tool which can help the chemist to design totally original molecules from different chemical classes with optimized affinity and selectivity for the target receptor.

## Reference

1 Gozlan, H et al. *Nature* Vol 305 (1983) p 140

25

Simplified formulae for inter- and intramolecular interactions related with quantum theory

**P Claverie**

Dynamique de Interactions Moléculaire, Université  
Paris VI, Tour 22, 4 place Jussieu, 75230 Paris Cedex  
05, France