Java Messaging Service (JMS) Agreement between P1 Receive Images and P2 Image Recognition

#### Queue Name:

p1ReceiveImages

### JMS Message:

Should contain the below JSON object definition.

## JSON Object Definition

```
{
    "uuid": "123e4567-e89b-12d3-a456-556642440000",
    "cameraId": 1,
    "timestamp": "2020-11-05T17:24:30.000+00:00",
    "numberplate": "",
    "photo": "/9j/4S/WRXhpZgAASUkqAAgAAAAJAA8BAgAQAAAAegAAABABAgAdAAAigAAABIB
AwABAAAAAQAAABoBBQABAAAApwAAABsBBQABAAAArwAAACgBAwABAAAAAgAAADIBAgAVAAAAtwAAAB
MCAwABAAAAAQAAAGm..."
}
```

#### **Definition**

uuid: is the universal unique identifier for the image in the P1 database.

camerald: is the camera ID.

timestamp: is in the ISO-8601 standard.

numberplate: will be the recognised numberplate add by p2.

photo: is the base64 encoded image.

### Object Serialisation and deserialization:

Will be don using Jackson (https://github.com/FasterXML/jackson)

# Image Format:

Should be sent as Base64/JPG image.

#### Base64 Conversion:

The JSON image string should be able to be decoded with the base64 Java utility. (https://docs.oracle.com/javase/8/docs/api/java/util/Base64.html)