

Clock 2 Diagnostics

Read-only engineering status

PPS

Valid / count

true / 15753

Age

461.3 ms

Last interval

1000004 μs

Interval n / mean

15752 / 1000003 μs

Interval min / max

999996 / 1000010 μs

Selected edge

rising

Pulse width

unavailable

NMEA TIMING

GGA

n=15753
mean=162914 μs
min=94096
max=234377

RMC

n=15752
mean=758833 μs
min=447087
max=860171

ZDA

n=15752
mean=841015 μs
min=528175
max=942490

Last valid age

279.8 ms

TIMEBASE

Valid / UTC

true / 2026-08-04T22:35:45Z

Source

ZDA

PPS / label age

461.4 ms / 611.8 ms

Accepted / rejected

31504 / 126

Association window

50000–950000 μs

PPS / GNSS timeout

2500000 / 10000000 μs

NTP / NETWORK

NTP received / sent

245 / 244

Ignored / invalid-timebase

1 / 1

NTP port / precision

123 / -20

Ethernet

link up

IP / MAC

192.168.1.161 / 3C:0F:02:D7:DE:A3

Netmask / gateway

255.255.255.0 / 192.168.1.1

BUILD / SYSTEM

Project / version

clock2_hwtest / v0.3.0-1-g26c3a8c-dirty

Build

Aug 4 2026 13:33:53

ESP-IDF

v6.0.2

Chip

esp32s3 rev 0.2, 2 cores

Reset reason

power-on

Flash

16777216 B

Uptime

15816 s

Heap free / minimum

320276 / 315448 B

NTP path diagnostics

disabled

PPS diagnostics

disabled

HARDWARE CONFIGURATION

GPS UART

1 GPIO45 @ 9600 baud

PPS GPIO

GPIO43

W5500 SPI

MOSI 11 MISO 12 SCLK 13 CS 14

W5500 INT / RESET

10 / 9

W5500 SPI clock

20000000 Hz

Raw NMEA dump

disabled