

# 3007 Final Exam Review

*William Findlay*

*April 22, 2018*

# Contents

<b>1</b>	<b>Definitions</b>	<b>3</b>
1.1	Imperative vs Declarative . . . . .	3
1.1.1	Imperative . . . . .	3
1.1.2	Declarative . . . . .	3
1.2	Scope vs Visibility . . . . .	3
1.2.1	Scope . . . . .	3
1.2.2	Visibility . . . . .	4
1.3	Lexical Scope vs Dynamic Scope . . . . .	4
1.3.1	Lexical . . . . .	4
1.3.2	Dynamic . . . . .	4
1.4	Free Variables . . . . .	4
1.5	Applicative Order Evaluation vs Normal Order Evaluation . . . . .	4
1.5.1	Applicative Order Evaluation . . . . .	4
1.5.2	Normal Order Evaluation . . . . .	5
1.6	Special Forms . . . . .	5
1.7	Tail Recursion . . . . .	5

# 1 Definitions

Define the following terms and provide examples or sample code as appropriate.

## 1.1 Imperative vs Declarative

### 1.1.1 Imperative

- Series of instructions
- Iterative functions
- Command driven, statement oriented
- Procedural
  - C
  - Pascal
  - Assembly
- Object oriented
  - C++
  - Java

### 1.1.2 Declarative

- No side effects
- Focus on relations
- “What to get” instead of “How to get”
- Order of statements *shouldn't* matter
- Examples:
  - SQL
  - Prolog
  - Regex

## 1.2 Scope vs Visibility

### 1.2.1 Scope

- The set of expressions for which the variable *exists*
- In lexical scoping
  - variables in the scope we were *defined* in
  - and local variables
  - who uses this?
    - \* C-family languages
    - \* Scheme
    - \* Algol
- In dynamic scoping
  - variables in the scope we were *called* in
  - and local variables
  - who uses this?
    - \* early LISP
    - \* APL
    - \* BASH

### 1.2.2 Visibility

- The set of expressions for which the variable *can be reached*
- If we **declare a local variable** with the *same name* as a variable in enclosing scope
  - that enclosing scope variable is now hidden
  - all references to *name* are to our locally scoped variable instead

## 1.3 Lexical Scope vs Dynamic Scope

### 1.3.1 Lexical

- Function scope is enclosed in the scope which *defined us*
  - if you can't find a binding, recursively search in the function that defined you

### 1.3.2 Dynamic

- Function scope is enclosed in the scope which *called us*
  - if you can't find a binding, recursively search in the function that called you

## 1.4 Free Variables

- **Used locally but bound in an enclosing scope**
- In the following example:

```
(define (f x y)
  (define z 2)
  (define (g)
    (* x y z)
  )
)
```

- *x, y, z* are free variables in *(g)*

## 1.5 Applicative Order Evaluation vs Normal Order Evaluation

### 1.5.1 Applicative Order Evaluation

- **Strict evaluation**
- Evaluate an expression *before* it is passed in as an argument
  - go as deep as you can until you hit primitives, then evaluate and go back
  - as deep into the nest as possible and work backwards
  - e.g.,

```
(double (* (+ 1 3) 4))
(double (* 4 4))
(double 16)
(* 16 2)
32
```

### 1.5.2 Normal Order Evaluation

- **Lazy evaluation**
- Evaluate an expression *only* when its value is needed
  - first **expand**, then **reduce**
  - e.g.,  
(double (\* (+ 1 3) 4))  
(\* (\* (+ 1 3) 4) 2)  
(\* (\* 4 4) 2)  
(\* 16 2)  
32

## 1.6 Special Forms

- **Exceptions** to the usual evaluation order
  - they have their own evaluation rules
  - e.g., take the first argument without evaluating right away, evaluate the second symbol right away
- Use constructs like (delay foo), (force foo) behind the scenes

## 1.7 Tail Recursion

- **Linear iterative processes** in Scheme
- No *deferred operations*
  - **recursive call** is the **last operation** of the procedure
- In Scheme, recursion is *tail optimized*
  - this means that it will run in *constant space*
  - number of steps will **grow linearly**, but memory will **remain constant**
- Even though the *program* is still recursive, the *process* is linear iterative because of tail-recursion optimization
- E.g., to compute a factorial using tail recursion, we do the following:

```
(define (factorial x)
  (define (iter prod i)
    (if (> i x)
        prod
        (iter (* i prod) (+ i 1)))
  )
  (iter 1 1)
)
```

- To compute a factorial using normal recursion, we would do the following instead:

```
(define (factorial x)
  (if (= x 1)
      x
      (* x (factorial - x 1)))
  )
)
```