

Question 1:

In this question, suppose you have variables for the following:

1. Student name
2. score (0-100)
3. Attendance percentage (0 – 100)
4. Behavior (1-5)

Step 1: Validate score

- If score is less than 0 or greater than 100 -> Print "Invalid entries"
- Or, if attendance percentage is less than 0 or greater than 100 -> Print "Invalid entries"
- Or, if behavior score is less than 1 or greater than 5 -> Print "Invalid entries"

Step 2: Pass / Fail Decision

- If score ≥ 50 AND attendance ≥ 75 -> Student passes
- Otherwise -> Student fails

Step 3: Letter grade (Only if passed):

Score Range	Grade
90 – 100	A
80 – 89	B
70 – 79	C
60 – 69	D
50 – 59	E

Step 4: Behavior Evaluation:

- If behavior score = 5 -> "Excellent behavior"
- If behavior score = 4 -> "Good behavior"
- If behavior score = 3 -> "Average behavior"
- If behavior score = 2 -> "Weak behavior"
- If behavior score = 1 -> "Bad behavior"

Step 5: Behavior Evaluation:

1. If student **passes** AND grade is **A or B** AND behavior ≥ 3 :
-> "Commendation awarded"
2. If student **passes** behavior ≤ 2 :
-> "Warning issued"
3. If student fails AND attendance < 50 :
-> "Disciplinary notice"
4. Otherwise:
-> "No special action"

Your code must output as following:

Run 1:

```
Name is Alice
Score = 92
Attendance percentage = 88
Behavior score = 5
-----
Alice has PASSED
Grade: A
```

Excellent behavior
Commendation awarded

Run 2:

Name is Ali
Score = 67
Attendance percentage = 80
Behavior score = 2

Ali has PASSED
Grade: D
Weak behavior
Warning issued

Run 3:

Name is Sara
Score = 74
Attendance percentage = 45
Behavior score = 3

Sara has FAILED
Average behavior
Disciplinary notice

Run 4:

Name is Samy
Score = 40
Attendance percentage = 70

Behavior score = 4

Samy has FAILED

Good behavior

No special action

Run 5:

Name is Jimmy

Score = 114

Attendance percentage = 15

Behavior score = -4

Invalid entries

Question 2:

In this question, implement the following:

- 1) Print all numbers starting from 1 to c1, suppose that $c1 > 1$ using while.
- 2) Print all numbers starting from c2 down to 1, suppose $c2 < 1$ using do-while.
- 3) Print the multiplication table of a variable c3 using for loop
- 4) Print all indices and variables of an array contains three elements: HTML, CSS, JS using foreach
- 5) Print **only** values of the same array of part 4) using foreach.

Run:

c1 = 10

1,2,3,4,5,6,7,8,9,10

c2 = 15

15-14-13-12-11-10-9-8-7-6-5-4-3-2-1

c3 = 5

5x1 = 5

5x2 = 10

5x3 = 15

5x4 = 20

5x5 = 25

5x6 = 30

5x7 = 35

5x8 = 40

5x9 = 45

5x10 = 50

0 -> HTML

1 -> CSS

2 -> JS

HTML

CSS

JS