


# FULL SOLUTION : PART 1: MAPPING (TurtleBot3 + SLAM Toolbox)

*Exercise: Create a Custom ROS2 Package for Mapping and Navigation*



## 1. Create the Package

Open a terminal inside your ROS2 workspace:

```
cd ~/ros2_ws/src
```

Create the package:

```
ros2 pkg create tb3_mapping_navigation --build-type ament_python
```

This generates:

```
tb3_mapping_navigation/
├─ package.xml
├─ setup.py
├─ resource/
│   └─ tb3_mapping_navigation
└─ tb3_mapping_navigation/
    └─ __init__.py
```

## 2 . Create the Launch Folder

```
mkdir ~/ros2_ws/src/tb3_mapping_navigation/launch
```

## 3. Add SLAM Parameters

Create a config folder:

```
mkdir ~/ros2_ws/src/tb3_mapping_navigation/config
```

Create the file:

```
nano ~/ros2_ws/src/tb3_mapping_navigation/config/slam_params.yaml
```

Paste this inside:

```
slam_toolbox:
  ros__parameters:
    use_sim_time: true
    slam_params_file: "mapper_params_online_sync.yaml"
    mode: "mapping"
```

Save and exit.

## 4. Create the Mapping Launch File

```
nano ~/ros2_ws/src/tb3_mapping_navigation/launch/mapping.launch.py
```

Paste the **full solution code**:

```
#!/usr/bin/env python3
"""
TurtleBot3 Mapping Launch File - SLAM with Gazebo + Teleop
```

```

"""

import os
from ament_index_python.packages import get_package_share_directory
from launch import LaunchDescription
from launch.actions import (
    DeclareLaunchArgument,
    IncludeLaunchDescription,
    ExecuteProcess,
    TimerAction,
    LogInfo,
    OpaqueFunction,
)
from launch.launch_description_sources import
PythonLaunchDescriptionSource
from launch.substitutions import LaunchConfiguration
from launch_ros.actions import Node

def launch_setup(context, *args, **kwargs):

    use_sim_time = context.launch_configurations.get('use_sim_time',
'true')
    with_teleop = context.launch_configurations.get('with_teleop',
'true')

    # Paths
    turtlebot3_gazebo_pkg =
get_package_share_directory('turtlebot3_gazebo')
    tb3_mapping_pkg =
get_package_share_directory('tb3_mapping_navigation')

    world_path = os.path.join(
        turtlebot3_gazebo_pkg, 'worlds', 'turtlebot3_world.world'
    )

    # -----
    # 1. Gazebo + TurtleBot3
    # -----
    gazebo_launch = IncludeLaunchDescription(
        PythonLaunchDescriptionSource([

```

```

        os.path.join(turtlebot3_gazebo_pkg, 'launch',
'turtlebot3_world.launch.py')
    ]),
    launch_arguments={
        'use_sim_time': use_sim_time,
        'world': world_path,
    }.items()
)

actions = [gazebo_launch]

# -----
# 2. SLAM Toolbox (Delayed)
# -----
slam_params = os.path.join(tb3_mapping_pkg, 'config',
'slam_params.yaml')

slam_node = Node(
    package='slam_toolbox',
    executable='async_slam_toolbox_node',
    name='slam_toolbox',
    output='screen',
    parameters=[
        slam_params,
        {'use_sim_time': use_sim_time == 'true'}
    ],
)

actions.append(TimerAction(period=8.0, actions=[slam_node]))

# -----
# 3. Teleoperation (Optional)
# -----
if with_teleop.lower() == 'true':
    teleop = ExecuteProcess(
        cmd=[
            'xterm', '-e',
            'ros2', 'run', 'teleop_twist_keyboard',
'teleop_twist_keyboard'
        ],
        output='log',

```

```

    )

    actions.append(TimerAction(period=10.0, actions=[teleop]))
    actions.append(LogInfo(msg="Teleop starts in a separate
xterm window..."))

    return actions

def generate_launch_description():

    return LaunchDescription([
        DeclareLaunchArgument(
            'use_sim_time',
            default_value='true',
            description='Use simulation time'
        ),
        DeclareLaunchArgument(
            'with_teleop',
            default_value='true',
            description='Launch teleop keyboard'
        ),
        LogInfo(msg='Starting TurtleBot3 Mapping Pipeline...'),
        OpaqueFunction(function=launch_setup),
    ])

```

Save and exit.

## 5. Update setup.py

Open:

```
nano ~/ros2_ws/src/tb3_mapping_navigation/setup.py
```

Edit entry points:

```

entry_points={
    'console_scripts': [],
    'launch': [

```

```
        'mapping =
tb3_mapping_navigation.mapping:generate_launch_description',
    ],
},
```

Save.

## 6. Build the Package

```
cd ~/ros2_ws
colcon build --packages-select tb3_mapping_navigation
```

Source workspace:

```
source install/setup.bash
```

## 7. Run the Mapping Pipeline

```
ros2 launch tb3_mapping_navigation mapping.launch.py
```

What will happen:

- ✓ Gazebo opens
- ✓ TurtleBot3 loads
- ✓ LiDAR publishes `/scan`
- ✓ Odometry publishes `/odom`
- ✓ After 8 seconds → SLAM Toolbox starts
- ✓ After 10 seconds → teleop keyboard window opens

## 8. Drive the Robot to Build the Map

In the teleop window:

```
W = forward
```

A = rotate left  
D = rotate right  
S = stop

As you move:

- ✓ /map topic updates
- ✓ Occupancy grid appears in RViz

## 9. Save the Map

Run:

```
ros2 service call /slam_toolbox/save_map slam_toolbox/srv/SaveMap \
  "{name: {data: '/home/housseem/ros2_ws/src/tb3_mapping_navigation/maps/tb3_map'}}"
```

The following files appear:

tb3\_map.yaml  
tb3\_map.pgm

These will be used later in **Part 2 (Navigation)**.

## 10. Expected Mapping Result

**A correct solution will show:**

- ✓ /map is being published
- ✓ Map grows as the robot moves
- ✓ No TF errors appear
- ✓ Student can save the map
- ✓ SLAM Toolbox outputs:

[INFO] Map saved!

## 11. Final File Tree (Correct Structure)

```
tb3_mapping_navigation/  
├── config/  
│   └── slam_params.yaml  
├── launch/  
│   └── mapping.launch.py  
├── package.xml  
├── setup.py  
├── resource/  
│   └── tb3_mapping_navigation  
└── tb3_mapping_navigation/  
    ├── __init__.py
```



