

# puerF

Commandline interface to use puer <https://github.com/leeluolee/puer> with FreeMarker templates <http://freemarker.org/>.

## Usage

Install it either as a global command line tool or as a local development dependency:

```
npm install -g puer-freemarker
or
npm install --save-dev puer-freemarker
```

Move into your working directory and run it:

```
cd your/working/directory
puerf
```

puerF requires that you have Java installed as it is needed to render FreeMarker templates.

## Command reference

Usage: puerf [cmd] [options]

Commands:

init [options]	Set up basic folders and files to work with puerf
convert	Convert FreeMarker templates into static HTML using mock data.

Start a puer Server, easily mock routes and render FreeMarker templates

Options:

-h, --help	output usage information
-V, --version	output the version number
-r, --routes <file>	Configuration file for mocked routes (multiple possible)
-c, --config	If a config file should be used
-t, --templates <path>	Path to folder in which Freemarker templates are stored
-r, --root <folder>	The root folder that files should be served from
-p, --port <number>	Specific port to use
-w, --watch <files>	Filetypes to watch, defaults to js css html xhtml ftl
-x, --exclude <files>	Exclude files from being watched for updates
-l, --localhost	Use "localhost" instead of "127.0.0.1"
--no-browser	Do not automatically open a browser
--debug	Display debug messages

## Mocking requests

This is what puerF is really all about. Making it as easy as possible for you to "fake" a backend. To achieve this puerF builds upon puer's mocking of request <https://github.com/leeluolee/puer#mock-request>. And simplifies the use of FreeMarker templates for those requests.

To mock requests create modules that export a single object following the syntax outlined below. You may split your routes over as many files as and modules as you wish, puerF will combine them for you. `demo` contains a sample file.

By default puerF will assume that you spread your routes over two files `mock/routes.js` and `mock/ftlRoutes.js`. Should you wish to use files from a different location you can do so using the `-r` option.

## Syntax for routes

All routes should be described as a String identifying the route and a `routeObject` containing information about how to mock that route. The `routeObject` may have any of the following properties:

Property	Description
handler	A function that handles this route
template	A FreeMarker template to be rendered for this route
data	An object to be returned at this route or used for the template
jsonFile	The path to a file containing the <code>data</code> for this route

When a route is called puerF resolves the `routeObject` as such:

- If a handler is present, it is executed
- Else if a template is specified it is parsed
- If none of the above are true the data is returned

## Working with query parameters

Real world applications might use query parameters to get specific results from a URL. You can easily mock those requests as well. To mock a route like `/example/some?user=name`, inside your regular routes file, you can simply access `req.query.user` to get the users name.

```
"GET /example/some": {
  handler: function(req, res, next) {
    var name = req.query.user;

    //Do something with the name, like sending it back.
    res.status(200).send(name).end();
  }
}
```

## FreeMarker templates

By default puerF will look for FreeMarker templates in `./templates`. To specify another folder you can use `-t`. Read the guide to author FreeMarker templates <http://freemarker.org/docs/dgui.html>.

## FreeMarker to static HTML

puerF can also convert FreeMarker templates into static HTML using mock data provided in a routes file. This needs the `routesFile` from which to take the templates to make static. `templateRoot` the root folder in which FreeMarker templates are and `targetFolder` in which to export the static HTML files.

Usage: `puerf convert <routesFile> <templateRoot> <targetFolder>`

# Use as a dependency

Instead of using `puer-freemarker` as a commandline tool, you might also use it as a dependency in your development pipeline. For instance in your gulpfile.

To do so simply `var puerf = require('puer-freemarker')`. The full docs may be found here <http://hoverbaum.github.io/puerF>. Below is the public API of puerF.

## puer-freemarker

puerF, a simple tool to run a live reloading server with mocked routes and FreeMarker templates.

- puer-freemarker
  - `.init(options, callback)`
  - `.start(options, callback)`
  - `.close(callback)`

### puer-freemarker.init(options, callback)

Runs the initializer. Will output basic files to the current working directory.

**Kind:** static method of `puer-freemarker`

**See:** initializer

Param	Type	Default	Description
options	object		Options for the initializer.
[options.onlyConfig]	boolean	false	Only create the config file.
callback	function		Function to call once done.

### puer-freemarker.start(options, callback)

Starts the core application.

**Kind:** static method of `puer-freemarker`

Param	Type	Default	Description
options	object		An object containing options.
[options.routes]	array	<code>['mock/ftlRoutes.js', 'mock/routes.js']</code>	An array of paths to all files containing mocked routes.
[options.config]	boolean	false	Use config file.
[options.templates]	string	<code>"templates"</code>	Root folder for FTL template files.

[options.root]	string	"'./'"	Root folder for static files to serve.
[options.port]	number	8080	The port to use for the server.
[options.watch]	string	"'js css html xhtml ftl'"	Filetypes (seperate them by pipes) to watch for changes.
[options.exclude]	regEx	/node_modules/	Files to exclude from watching.
[options.localhost]	boolean	false	Use localhost instead of 127.0.0.1 .
[options.browser]	boolean	true	Automatically open a browser for the user.
[options.debug]	boolean	false	Enable debugging output and log file.
callback	function		Function to call once started.

puer-freemarker.close(callback)

Programatically closes puerF.

**Kind:** static method of `puer-freemarker`

Param	Type	Description
callback	function	Function to call once done.

Testing

puerF utilizes [tape](https://github.com/substack/tape) <https://github.com/substack/tape> for testing. Install development dependencies and run `npm test` to run the tests.