

Mouse auditory experiment

A first plan

October 8, 2026

We want to play short tones to a mouse and record its brain responses. SONIC tested awake sheep; our mouse state and tone settings remain open. (Methods 6.6, p.13)

1. Choose the sounds

- Choose the frequency, duration, loudness, and gap between tones.
- **SONIC:** initially explored 1.4–32 kHz; benchmark tones were 10 ms sine waves with 2 ms fades at each end. (Methods 6.1–6.2, p.11)
- **SONIC:** random frequencies, balanced within each block, with no silence between tones. (Methods 6.1, p.11)
- Save the sequence before playback, as SONIC did. (Methods 6.2, p.11)

2. Set up the speaker

- Check what audio equipment the lab already has.
- **SONIC:** NI USB-6361 output at 192 kHz, TDT SA1 amplifier, and MF1 free-field speaker; about 80 dB SPL at sheep-ear distance. (Methods 6.2, p.11)
- **Our plan:** assess that equipment, keep speaker placement fixed, and measure each tone with a calibrated microphone at the mouse-ear position.

3. Keep everything on one timeline

- Schedule each tone with a timing pulse and record it alongside the neural signals.
- **SONIC:** recorded electrical sound output and trial-start markers; shared clock references aligned these with Connexus brain recordings. (Methods 6.2, p.11)
- **Our additions:** synchronize a microphone recording to check actual sound arrival. Align video frame times too if we add behavior video.

Reference: Perkins et al. (2025), SONIC: A Benchmarking Paradigm for Brain-Computer Interfaces, bioRxiv v1. Page numbers above refer to the printed manuscript. Mouse choices and additions are proposals.