東京大学
THE UNIVERSITY OF TOKYO

UTokyo Field Phenomics Lab

Virtual Broccoli Farmland Implementation by Drone-based Phenotyping and Cross-scale Data Fusion

Haozhou Wang Tang Li, Nishida Erika, Kato Yoichiro, Fukano Yuya, Wei Guo

2023/11/29

: haozhou-wang@outlook.com

東京大学
THE UNIVERSITY OF TOKYO

UTokyo Field Phenomics LAB

Vegetables around us

Problems of vegetable farmers





Multi-time harvest： labor cost

One-time harvest： food loss

Farmer’s income decrease

Determine the optimal harvest date

Field check
(longest + shortest length)
High labor cost
↓
Growth condition in the field
↓
Subjective estimate harvest date

Smart farming / digital twin virtual farmland

High-throughput data collection



3D reconstruction



Organ Segmentation



Traits calculation

Simulation



Individual growth prediction



Price / food loss prediction

Data visualization



[1] Augmented Reality Company | VR & MR Solution | AR Development Agency (yeppar.com)

Challenges： big image data

Need to analysis huge amount of image data
(difficult to process in time)

Cost of data storage for 1ha



Large amount of time-series data
(38 flights in 2022)

One flight

200+

raw images
(2.7GB+)



5742 x 3648 pixels

200 x 20 billion
=
4 trillion pixels
per flight



(1GB+)

19572 x 17664 pixels

0.3 trillion
pixels
per flight

Challenges：quality for organ-level analysis

Aerial reconstruction products hard to achieve organ-level analysis quality



3D canopy model
(PCD)



2D field map
(DOM)

Challenges：occlusion



Canopy occlusion affects traits accuracy



Non-complete structure affects the virtual farmland visualization

Solutions：temporal data fusion

Narrow the processing regions by using prior knowledge of agriculture





Broccoli head position is almost the same as its seedling position





Narrow the processing area around the seedling area

(100 x 100) pixels x 3000 count = 30 billion pixels per flight ~ 1.5 raw image

per crop

5742 x 3648 ~ 20 billon pixels

Solutions：spatial data fusion

Combine raw images (pixel coordinates) with field maps (geo coordinates)



(2341,1492)

Pixel coordinates

Better quality
Lacks spatial context



(35.7393N,139.5414E, 96.34m)

Geo coordinates

Lower quality
Has spatial context



[1]

Powered by EasyIDP

pixel-coordinates

Spatial fusing

geo-coordinates

[1] Wang, H., Duan, Y., Shi, Y., Kato, Y., Ninomiya, S., Guo, W., 2021. EasyIDP: A python package for intermediate data processing in UAV-based plant phenotyping. Remote Sensing 13, 2622. https://doi.org/10.3390/rs13132622

Solutions： paired data fusion

Destructive sampling



Close-range 3D reconstruction

High-quality 3D models



Traits without occlusion

Paired aerial images



Traits with occlusion

Auto-ML

$\{X_{train}, Y_{train}, X_{test}, \mathcal{L}\}$ → meta-learning → AutoML system { Bayesian optimizer; ML framework { data pre-processor → feature preprocessor → classifier }; build ensemble } → Calibration model

[1] https://automl.github.io/auto-sklearn/master

Results： temporal data fusion



Seedling position on flowering stage on field map (geo-coordinate)

Results：head segmentation & traits calculation

Segmented head results





Minimum area rectangle max/min side-length



Equivalent diameter



broccoli
center points

Eccentricity, circularity

Major axis length
Minor axis length

Area, perimeter



Convex area

Results： occlusion calibration

The Auto-ML calibration improved the traits closer to actual size



Results： growth and profit prediction

Individual growth prediction model by temperature sum (first year)

One day shift in harvest from the optimal date could lead to considerable income loss (3.7% to 20.4% reduction)







Wang, H., Li, T., Nishida, E., Kato, Y., Fukano, Y., Guo, W., 2023. Drone-Based Harvest Data Prediction Can Reduce On-Farm Food Loss and Improve Farmer Income. Plant Phenomics 5, 0086. https://doi.org/10.34133/plantphenomics.0086

Results：3D virtual farmland visualization

Aerial survey obtained position and traits





Aerial field low quality 3D models

Conclusion

- Smart farming / virtual farmland has shown its potential to:

  Evaluate and predict individual plant growth

  Reducing the effects of occlusion & provide 3D visualization

  Reducing on-farm food loss & Increase farmer's income

- Future work:

  Collect more valuable data & robust model

  Test and apply to commercial farmland

東京大学
THE UNIVERSITY OF TOKYO

Thank you

2023

: haozhou-wang@outlook.com