



Apigee Edge Training

Anatomy of an API proxy



Digging into our new Proxy



- Endpoints
- Virtual Hosts
- Endpoint Properties
- Flows
- Policies

API Proxy and Target Endpoints

- Define an API as a series of resources that access a given target system.
- Client-side interfaces can be access using either HTTP or HTTPS
- Targets can be accessed using either HTTP or HTTPS, using either one-way SSL or two-way SSL with mutual authentication
- REST and SOAP targets supported
- “First match” selection: define a set of resource criteria matching incoming requests, and the first match found controls request execution
- Resource matching on path nodes, query parameters, HTTP verbs and other types of conditions
- Determine target service for requests using either static or dynamic routing


Virtual Hosts

An environment can contain multiple virtual hosts and a proxy's client side endpoint is configured to listen on one or more virtual hosts. The virtual host's configuration determines how an API request will route into an API proxy.

Environment Configuration

Virtual Hosts

Name	Port	Alias
default	80	michaelarusso-prod.apigee.net
Name secure	Port 443	Alias michaelarusso-prod.apigee.net
SSL Info		
Enabled	<input checked="" type="checkbox"/>	Client Auth Disabled
Key Store	freetrial	Trust Store
Key Alias	freetrial	Ciphers



Apigee classifies requests using the following:

- Virtual Host Port
- Request's Host Alias (value of Host header)
- Proxy Endpoint BasePath

```
<HTTPProxyConnection>  
  <BasePath>/v1/products</BasePath>  
  <VirtualHost>default</VirtualHost>  
  <VirtualHost>secure</VirtualHost>  
</HTTPProxyConnection>
```

Endpoint Properties

In addition to the standard endpoint configurations there are some commonly used properties to control advanced functionality.

<HTTPProxyConnection>

- ***allow.http.method.**** - by default all HTTP methods are allowed. To disable a method you can use this property: `<Property name="allow.http.method.POST">false</Property>`
- ***request.streaming.enabled*** – if the payload will not be read or updated during the proxy processing, you can enable to to avoid payload buffer size limits
- ***response.streaming.enabled*** - if the payload will not be read or updated during the proxy processing, you can enable to to avoid payload buffer size limits

<HTTPTargetConnection>

- ***connect.timeout.millis*** – this is used to set the connection timeout for backend connections (in ms). Defaults to 60000 (1 min) and highly recommended to lower
- ***io.timeout.millis*** – this is used to set the response read timeout (waiting for response from backend). Defaults to 120000 (2 min) and extremely encouraged to reduce to optimize connection handling in the event that a backend service is degraded.
- ***response.streaming.enabled*** - if the payload will not be read or updated during the proxy processing, you can enable to to avoid payload buffer size limits
- ***success.codes*** – this property is used to set the response status codes that are treated as ‘success’. Defaults to 1XX,2XX,3XX. This is a helpful configuration when you want to access 4XX responses are success to continue response flow processing.

Proxy Endpoint Route Rules

- Target is determined by RouteRules
 - One or more RouteRule sections at the bottom of the proxy definition file (proxies/{proxy}.xml) within ProxyEndpoint

```
<RouteRule name="auth">
  <Condition>proxy.pathsuffix MatchesPath "/auth"</Condition>
  <!-- no target called -->
</RouteRule>
<RouteRule name="routeToTestServer">
  <Condition>request.header.X-TestServer == "true"</Condition>
  <TargetEndpoint>testServer</TargetEndpoint>
</RouteRule>
<RouteRule name="default">
  <!-- no condition, so always executes if it reaches this far -->
  <TargetEndpoint>default</TargetEndpoint>
</RouteRule>
```

- RouteRules evaluated top to bottom, taking first match only
- TargetEndpoint is the name of the target file
 - No TargetEndpoint means no target called (no Target Request and Target Response)
- No condition supplied means that RouteRule will automatically match

Advanced Routing


Once the Route Rules have selected a TargetEndpoint and processing has begun inside the Target, you can then apply logic to route the request to specific paths in the backend.

- ***target.url*** variable for read/write. You can override this via policy, but when doing so it stops the automatic copying of the request querystring.


```
1  try{
2
3      var url = context.getVariable("target.url");
4      var pathsuffix = context.getVariable("proxy.pathsuffix");
5      var querystring = context.getVariable("request.querystring");
6      url += pathsuffix + "/myAddedPathParam";
7      if(querystring){
8          url += "?" + querystring;
9      }
10     context.setVariable("target.url", url);
11
12 }catch(e){
13
14     throw e;
15
16 }
```

Policy Flows

“Policies” are steps within the API Flow. The **Proxy Endpoint** contains policies that affect the request and response to the Client. The **Target Endpoint** contains policies that affect the request and response to the backend Target server



API Flow Processing



apiproxy/proxies/default.xml

```
<ProxyEndpoint name="default">
  <PreFlow>
    <Request>1</Request>
    <Response>10</Response>
  </PreFlow>
  <Flows>
    <Flow name="getDogs">
      <Request>2</Request>
      <Response>11</Response>
      <Condition></Condition>
    </Flow>
  </Flows>
  <PostFlow>
    <Request>3</Request>
    <Response>12</Response>
  </PostFlow>
  ...
</ProxyEndpoint>
```

apiproxy/targets/default.xml

```
<TargetEndpoint name="default">
  <PreFlow>
    <Request>4</Request>
    <Response>7</Response>
  </PreFlow>
  <Flows>
    <Flow name="purchaseTarget">
      <Request>5</Request>
      <Response>8</Response>
      <Condition></Condition>
    </Flow>
  </Flows>
  <PostFlow>
    <Request>6</Request>
    <Response>9</Response>
  </PostFlow>
  ...
</TargetEndpoint>
```

Post Response Flow




- PostClientResponseFlow
 - Lives in the proxy definition
 - Can only have Message Logging policies attached
 - Used as a method to alleviate the latency associated with logging to a syslog server.

Adding Resources



Conditional Flows / Resources

A “**Conditional Flow**” is a collection of policies within the API Flow that all share one rule. All policy attachments in the **PreFlow** execute first, then the first matching **Conditional Flow** execute, then everything in the **PostFlow** executes. This happens on the Proxy Request, then the Target Request, and repeats back through the Target Response and the Proxy Response.



```
<Condition>(proxy.pathsuffix MatchesPath &quot;/trucks&quot;,) and (request.verb = &quot;GET&quot;)</Condition>
```

Adding Resources (Conditional Flows)

Revision 1 Summary

Dates Created: Sep 5, 2014 7:48:43 PM, Updated: Sep 10, 2014 12:15:08 PM

Description

Default Proxy Endpoint Base Path /v1/apieatery

Default Target Endpoint URL http://apigee-edu-prod.apigee.net/v1/apieatery

 Edit Revision Summary









Resources

Name	Proxy Endpoint	Method	Path	URL	Policies	Actions
------	----------------	--------	------	-----	----------	---------

+ Resource



Resources

Name	Proxy Endpoint	Method	Path	URL	Policies	Actions
trucks	default	GET	/trucks	http://trainingmats-test.apigee.net/v1/apieatery/trucks [+]	0	 Edit  Delete
chefs	default	GET	/chefs	http://trainingmats-test.apigee.net/v1/apieatery/chefs [+]	0	 Edit  Delete
cuisines	default	GET	/cuisines	http://trainingmats-test.apigee.net/v1/apieatery/cuisines [+]	0	 Edit  Delete
routes	default	GET	/routes	http://trainingmats-test.apigee.net/v1/apieatery/routes [+]	0	 Edit  Delete

+ Resource

Resource Menu

Steves-APIEatery

Project Save Revision 1 New New Policy Attach Policy Tools Deployment Help for Selected Flow

Map: Endpoint default, Flow routes

Property Inspector: routes

Flow

Flow name	routes
Description	
Request	
Response	
Condition	(proxy.pathsuffix MatchesPath "/routes") and (request.verb = "GET")

App

Code: routes

```
1 <Flow name="routes">
2   <Description/>
3   <Request/>
4   <Response/>
5   <Condition>(proxy.pathsuffix MatchesPath &quot;/routes&quot;) and (request.verb = &quot;GET&quot;)
6 </Flow>
```

Navigator

- Policies
 - basic_authentication
 - kvm_get_credentials
- Proxy Endpoints
 - default
 - All PreFlow
 - GET trucks
 - GET chefs
 - GET cuisines
 - GET routes
 - All PostFlow
- Target Endpoints
 - default
 - All PreFlow
 - All PostFlow
- Scripts

Conditional Flows in XML

Steves-APIEatery

OVERVIEW DEVELOP TRACE

Project Save Revision 1 New New Policy Attach Policy Tools Deployment Help for Selected Flow

Navigator

- Map: Endpoint default, Flow routes

Property Inspector: routes


Flow

Flow name	routes
Description	
Request	
Response	
Condition	(proxy.pathsuffix MatchesPath "/routes") and (request.verb = "GET")

App

Code: routes

```
1 <Flow name="routes">
2   <Description/>
3   <Request/>
4   <Response/>
5   <Condition>(proxy.pathsuffix MatchesPath &quot;/routes&quot;) and (request.verb = &quot;GET&quot;)
6 </Flow>
```



Revisit Lab1

- We created pass through proxy in lab1 for ratings API
 - Is it the right way to setup a proxy?
 - What are the limitations of setting it this way?
 - How can we fix this?

Day 1 – Lab 2



- Adjust the proxy created in Lab1 to set it up the right way
 - Create a new resource as follows
 - Name = rating
 - Method = GET
 - Path = /ratings
 - Update the target URL and remove /ratings
- Test your proxy using Postman

Day 1 – Lab 3 – Dynamic Routing

- Create a new resource as follows:
 - Name=chefs, method=GET, Path=/chefs
- Create a new Target Endpoint, name=baasTarget, type=Target
 - URL=<https://api.usergrid.com/bellevue2015/sandbox>
- Change default Target Endpoint
 - URL=<https://apigee-edu-test.apigee.net/v1/apieatery>
- Setup Route Rules to send your request
 - In Proxy EndPoint, Define route rule as follows:

```
<RouteRule name="baasTarget">
```

```
  <Condition>(proxy.pathsuffix MatchesPath &quot;/ratings&quot;,) and (request.verb = &quot;GET&quot;)</Condition>
```

```
  <TargetEndpoint>baasTarget</TargetEndpoint>
```

```
</RouteRule>
```

```
<RouteRule name="default"><TargetEndpoint>default</TargetEndpoint></RouteRule>
```

Day 1 – Lab 3 – Dynamic Routing Cont.

- Using Postman, test the following urls:
 - <http://orgname-envname.apigee.net/v0/apieatery/ratings>
 - <http://orgname-envname.apigee.net/v0/apieatery/chefs>

Day 1 – Lab 4 – Advance Dynamic Routing

- Add a javascript policy
 - Display name = Dynamic Routing, Script Name = Dynamic-Routing
 - Script File = Create new script, Script Name = Dynamic-Routing.js
 - Attach Policy = check, Flow = Flow baasTarget, Target PreFlow
 - Segment = request
 - Type following javascript content:

```
Try {  
    var new_target = "http://httpbin.org/get";  
    context.setVariable("target.url", new_target);  
} catch(e) {  
    throw e;  
}
```

Thank you

An abstract network diagram on a solid orange background. It features several white circular nodes of varying sizes connected by thin white lines. The nodes are arranged in a way that suggests a complex, interconnected system or network. Some nodes are isolated, while others are part of larger clusters or chains.

apigee

January 2014