

Code review: AZANIR/cypressAllure

master @ bb313ea · 2 blocker · 7 major · 10 minor

1. **BLOCKER** config/config.config.ts:22

```
21     },
22     baseUrl: 'http://automationpractice.com/index.php',
23     specPattern: 'cypress/e2e/tests/**/*.test.ts',
```

Problem: automationpractice.com no longer hosts the shop (it returns a hosting placeholder), so every test fails.

Fix: Point baseUrl at a working instance of the app.

2. **BLOCKER** .github/workflows/cyAllureRun.yml:9, 15, 17, 29

```
8     Run_test:
9       runs-on: ubuntu-20.04 # Choosing OS
10      strategy:
11      ...
14      steps:
15        - uses: actions/checkout@v2
16        - name: Use Node.js ${{ matrix.node-version }}
17          uses: actions/setup-node@v2
18          with:
19          ...
28        - name: Upload artifact allure-report
29          uses: actions/upload-artifact@v1
30          if: always()
```

Problem: The ubuntu-20.04 runner and the v1/v2 actions are retired, so CI no longer starts.

Fix: Update the runner and the actions.

```
runs-on: ubuntu-latest
- uses: actions/checkout@v4
  uses: actions/setup-node@v4
  uses: actions/upload-artifact@v4
```

3. **MAJOR** cypress/e2e/tests/login.test.ts:35

```
34     loginPage.login(this.data.invalid_credentials.wrong_email_format.emailId, this.data.invalid_cr...
35     loginPage.validateLoginError('Invalid email addressssss.')
36   })
```

Problem: Typo in the expected message, so the test always fails and CI is always red, which hides real failures.

Fix: Fix the text.

```
loginPage.validateLoginError('Invalid email address.')
```

4. **MAJOR** cypress/e2e/tests/myAccount.test.ts:5-6, 8-10

```
4     beforeEach(() => {
5       cy.visit('https://google.com');
6       //loginPage.launchApplication()
7     })
8     it('Sample Test', () => {
9       console.log("This is a sample test")
10    })
11  })
```

Problem: The test has no assertion (only console.log) and visits google.com, so it always passes.

Fix: Write a real My Account test, or delete the file.

5. **MAJOR** .github/workflows/cyAllureRun.yml:38

```
37         with:
38             ACCESS_TOKEN: ${{'secrets.ACCESS_TOKEN'}}
39             BRANCH: master # The branch the action should deploy to.
```

Problem: The quotes turn the secret into the literal string 'secrets.ACCESS_TOKEN'.

Fix: Remove the quotes.

```
ACCESS_TOKEN: ${{ secrets.ACCESS_TOKEN }}
```

6. **MAJOR** .github/workflows/cyAllureRun.yml:39-41

```
38         ACCESS_TOKEN: ${{'secrets.ACCESS_TOKEN'}}
39         BRANCH: master # The branch the action should deploy to.
40         FOLDER: allure-report # The folder the action should deploy.
41         TARGET_FOLDER: docs
```

Problem: CI commits the generated report into master/docs (81 files, including videos). The repo fills up with report commits.

Fix: Deploy to the gh-pages branch, delete docs/ from master, and add docs/ to .gitignore.

```
BRANCH: gh-pages
```

7. **MAJOR** package.json:10

```
9     "cy:run": "cypress run --config-file config/config.config.ts --env allure=true",
10    "report": "npx allure generate reports/ui/allure-results --clean -o reports/ui/allure-report && al...
11    "allure:generate": "npx allure generate allure-results --clean",
```

Problem: `report` reads reports/ui/allure-results, but results are written to allure-results, so the report is empty.

Fix: Use one path.

```
"report": "npx allure generate allure-results --clean -o allure-report && npx allure open allure-report",
```

8. **MAJOR** package.json:12

```
11    "allure:generate": "npx allure generate allure-results --clean",
12    "clear": "rm -r reports/** || true"
13  },
```

Problem: `rm` doesn't exist on Windows, so `npm run cy:e2e:run` fails right away.

Fix: Use rimraf.

```
"clear": "rimraf reports allure-results allure-report"
```

9. **MAJOR** cypress/fixtures/users.json:3-4

```
2    "valid_credentials": {
3      "emailId": "testautomation@cypress-test.com",
4      "password": "Test@1234"
5    },
```

Problem: Account credentials are committed to the repo.

Fix: Read them from Cypress.env() (CI secrets or a local cypress.env.json in .gitignore).

10. **MINOR** cypress/e2e/tests/login.test.ts:11-16

```
10  })
11  it('login with valid credentials', function () {
12    loginPage.login("testautomation@cypress.test.com", "Test@1234")
13    myAccountPage.validateSuccessfulLogin()
14    myAccountPage.logout()
15    myAccountPage.validateSuccessfulLogout()
16  })
17  it('login with valid credentials read data from fixture', function () {
```

Problem: Duplicates the next test (lines 17-22), but with hardcoded credentials.

Fix: Delete it; keep the fixture-based test.

11. **MINOR** cypress/e2e/pages/myAccountPage.ts:3, 18

```
2
3  import { loginPage } from "../loginPage"
4
...
17  public validateSuccessfulLogout() {
18    loginPage.signinLink.should('be.visible')
19  }
```

Problem: MyAccountPage uses a LoginPage locator.

Fix: Check the logout in the spec through loginPage.

12. **MINOR** cypress/e2e/pages/loginPage.ts:8

```
7  get signinBtn() { return cy.get('#SubmitLogin') }
8  get alertBox() { return cy.get('p:contains("error")')}
9  get alertMessage() { return cy.get('.alert-danger > ol > li') }
```

Problem: The locator depends on the error text.

Fix: Use the CSS class.

```
get alertBox() { return cy.get('.alert-danger') }
```

13. **MINOR** config/config.config.ts:20

```
19  setupNodeEvents(on, config) {
20    return require('cypress/plugins/index.js')(on, config)
21  },
```

Problem: The import path looks like a file from the cypress package, and the old Cypress 9 plugins file is kept alive.

Fix: Call allureWriter(on, config) directly in setupNodeEvents and delete cypress/plugins/.

14. **MINOR** config/config.config.ts:6-8

```
5  defaultCommandTimeout: 5000,
6  execTimeout: 5000,
7  taskTimeout: 5000,
8  pageLoadTimeout: 30000,
9  requestTimeout: 5000,
```

Problem: Timeouts are below the Cypress defaults (60 s) for no reason, which causes flaky runs on a slow site.

Fix: Delete these lines.

15. **MINOR** package.json:8-9

```
7   "cy:e2e:run": "npm run clear && npm run cy:run && npm run report",
8   "cy:open": "cypress open --config-file config/config.config.ts --env allure=true",
9   "cy:run": "cypress run --config-file config/config.config.ts --env allure=true",
10  "report": "npx allure generate reports/ui/allure-results --clean -o reports/ui/allure-report && al...
```

Problem: The config isn't in the default place, so a plain `npx cypress open` runs without baseUrl.

Fix: Move it to the root as cypress.config.ts and drop --config-file.

16. **MINOR** tsconfig.json:13-14

```
12  "include": ["**/*.ts",
13    "../node_modules/@shelex/cypress-allure-plugin/reporter",
14    "../node_modules/cypress"]
15 }
```

Problem: ../node_modules points outside the project, so these paths match nothing.

Fix: Delete these two lines.

17. **MINOR** .github/workflows/cyAllureRun.yml:22

```
21       - run: npm i npm@latest
22       - run: npm i
23       - name: run test
```

Problem: npm i doesn't follow package-lock.json.

Fix: Use npm ci.

```
- run: npm ci
```

18. **MINOR** cypress/support/commands.js:1-3

```
1 // *****
2 // This example commands.js shows you how to
3 // create various custom commands and overwrite
4 // existing commands.
```

Problem: The file is only the template comment; there are no commands.

Fix: Delete the file (and its import in support/e2e.js).

19. **MINOR** README.md:1

```
1 # cypress-e2e-allure# Cypress-e2e-Allure Automation-Framework with allure reports
2
```

Problem: Two headings run together on one line.

Fix: Split them.

```
# Cypress E2E Allure
```