

cypressAllure — fix list

github.com/AZANIR/cypressAllure · master @ bb313ea · 4 blocker · 11 major · 16 minor · highlighted lines = where the problem is, green = what to write instead

1. **BLOCKER** config/config.config.ts:22

```
config/config.config.ts
20   return require('cypress/plugins/index.js')(on, config)
21 },
22 baseUrl: 'http://automationpractice.com/index.php',
23 specPattern: 'cypress/e2e/tests/**/*.test.ts',
24 },
```

Problem: Target site is dead: automationpractice.com now serves an InMotion Hosting placeholder page, so no test can pass.

Fix: Point baseUrl at a working app (self-hosted shop, other demo, or a mock); use the origin only, without index.php.

```
baseUrl: 'https://<working-app-origin>',
```

2. **BLOCKER** cypress/e2e/tests/login.test.ts:35

```
cypress/e2e/tests/login.test.ts
33   it('login with wrong email format credentials read data from fixture', function () {
34     loginPage.login(this.data.invalid_credentials.wrong_email_format.emailId,
35       this.data.invalid_credentials.wrong_email_format.password)
36     loginPage.validateLoginError('Invalid email addresssssss.')
37   })
```

Problem: Typo in the expected text, so the test always fails (CI run: "expected 'Invalid email addresssssss.' but the text was 'Invalid email address.'").

Fix: Fix the expected string.

```
loginPage.validateLoginError('Invalid email address.')
```

3. **BLOCKER** cypress/e2e/tests/myAccount.test.ts:5-9

```
cypress/e2e/tests/myAccount.test.ts
1  import { loginPage } from '../pages/loginPage';
2
3  describe('My Account Functionality', () => {
4    beforeEach(() => {
5      cy.visit('https://google.com');
6      //loginPage.launchApplication()
7    })
8    it('Sample Test', () => {
9      console.log("This is a sample test")
10    })
11 })
```

Problem: The test only calls console.log and visits google.com; it always passes and checks nothing. loginPage is imported, but the only call is commented out.

Fix: Log in through loginPage and assert the My Account heading, or delete the spec.

```
beforeEach(() => loginPage.launchApplication())
it('shows My Account after login', function () {
  loginPage.login(this.users.valid_credentials.emailId, this.users.valid_credentials.password)
  myAccountPage.pageHeading.should('contain.text', 'My account')
})
```

4. **BLOCKER** .github/workflows/cyAllureRun.yml:9-29

```
.github/workflows/cyAllureRun.yml
9   runs-on: ubuntu-20.04 # Choosing OS
10   strategy:
11     matrix:
12       node-version: [14.17.0]
13       # See supported Node.js release schedule at https://nodejs.org/en/about/releases/
14   steps:
15     - uses: actions/checkout@v2
16     - name: Use Node.js ${ matrix.node-version }
17       uses: actions/setup-node@v2
18       with:
19         node-version: ${ matrix.node-version }
20         cache: "npm"
21     - run: npm i npm@latest
22     - run: npm i
23     - name: run test
24       run: npm run cy:run
25     - name: Create Report
26       if: always()
27       run: npm run allure:generate
28     - name: Upload artifact allure-report
29     uses: actions/upload-artifact@v1
```

Problem: CI can't run: the ubuntu-20.04 runner is retired, upload-artifact@v1 is retired, and checkout/setup-node@v2 and Node 14 are end-of-life. `npm i npm@latest` adds npm as a dependency.

Fix: Update the runner and actions; drop the npm self-install.

```
runs-on: ubuntu-latest
node-version: [20.x]
- uses: actions/checkout@v4
  uses: actions/setup-node@v4
  uses: actions/upload-artifact@v4
```

5. **MAJOR** .github/workflows/cyAllureRun.yml:38

```
.github/workflows/cyAllureRun.yml
34     - name: Deploy report
35       uses: JamesIves/github-pages-deploy-action@3.1.0
36       if: always()
37       with:
38         ACCESS_TOKEN: '${ secrets.ACCESS_TOKEN }'
39         BRANCH: master # The branch the action should deploy to.
40         FOLDER: allure-report # The folder the action should deploy.
41         TARGET_FOLDER: docs
```

Problem: The secret is quoted, so the expression yields the literal text 'secrets.ACCESS_TOKEN'. Deploys only work because checkout's persisted GITHUB_TOKEN is used.

Fix: Remove the quotes. Change it together with the next item, otherwise deploys will re-trigger the workflow in a loop.

```
ACCESS_TOKEN: ${ secrets.ACCESS_TOKEN }
```

6. **MAJOR** .github/workflows/cyAllureRun.yml:5

```
.github/workflows/cyAllureRun.yml
3 on:
4   push:
5     branches: [master]
```

Problem: The workflow runs on push to master, and the deploy step (line 39: BRANCH: master, TARGET_FOLDER: docs) commits the report back into master. That produced 12 'Deploying to master' commits.

Fix: Deploy to gh-pages, not master.

```
BRANCH: gh-pages
FOLDER: allure-report
```

7. MAJOR docs/

Problem: The generated Allure report is committed: 81 files, including 7 .mp4 and 5 .png.

Fix: Delete it from the repo and ignore it.

```
git rm -r docs/
echo docs/ >> .gitignore
```

8. MAJOR package.json:10-12

```
package.json
7   "cy:e2e:run": "npm run clear && npm run cy:run && npm run report",
8   "cy:open": "cypress open --config-file config/config.config.ts --env allure=true",
9   "cy:run": "cypress run --config-file config/config.config.ts --env allure=true",
10  "report": "npx allure generate reports/ui/allure-results --clean -o reports/ui/allure-report && allure open reports/ui/allure-report",
11  "allure:generate": "npx allure generate allure-results --clean",
12  "clear": "rm -r reports/** || true"
```

Problem: Results path mismatch: the config writes ../allure-results (which ends up at the root allure-results that line 11 reads), but `report` reads reports/ui/allure-results, so the local report is empty. `clear` uses rm, which fails on Windows. `allure open` lacks npx.

Fix: Use one path everywhere; use rimraf for clean-up.

```
"report": "npx allure generate allure-results --clean -o allure-report && npx allure open allure-report",
"clear": "rimraf allure-results allure-report reports"
```

9. MAJOR config/config.config.ts:14

```
config/config.config.ts
13  env: {
14    allureResultsPath: '../allure-results',
15  },
```

Problem: The '../' path is confusing and doesn't match the package.json scripts.

Fix: Use a plain project-relative path.

```
allureResultsPath: 'allure-results',
```

10. MAJOR cypress/fixtures/users.json:3-4

```
cypress/fixtures/users.json
1  {
2    "valid_credentials": {
3      "emailId": "testautomation@cypressstest.com",
4      "password": "Test@1234"
5    },
```

Problem: Real credentials are committed in plaintext.

Fix: Read them from Cypress.env() (CI secrets or a git-ignored cypress.env.json).

```
Cypress.env('USER_EMAIL'), Cypress.env('USER_PASSWORD')
```

11. MAJOR cypress/e2e/tests/login.test.ts:7-12

```
cypress/e2e/tests/login.test.ts
5   beforeEach(() => {
6     loginPage.launchApplication()
7     cy.fixture('users.json').then(function (data) {
8       this.data = data;
9     })
10  })
11  it('login with valid credentials', function () {
12    loginPage.login("testautomation@cypressstest.com", "Test@1234")
13    myAccountPage.validateSuccessfulLogin()
14    myAccountPage.logout()
15    myAccountPage.validateSuccessfulLogout()
16  })
```

Problem: Line 12 hardcodes the credentials that are already in the fixture. `this.data` is untyped, so `strict: true` doesn't protect it. All negative data is static.

Fix: Use a typed fixture alias; generate negative data with `@faker-js/faker`.

```
beforeEach(() => cy.fixture<Users>('users.json').as('users'))
loginPage.login(faker.internet.email(), faker.internet.password())
```

12. MAJOR .github/workflows/cyAllureRun.yml:22

```
.github/workflows/cyAllureRun.yml
21   - run: npm i npm@latest
22   - run: npm i
```

Problem: `npm i` ignores the lockfile.

Fix: Use `npm ci`.

```
- run: npm ci
```

13. MAJOR cypress/e2e/pages/loginPage.ts:4-9

```
cypress/e2e/pages/loginPage.ts
3  class LoginPage {
4    get signinLink() { return cy.get('.login') }
5    get emailAddressTxt() { return cy.get('#email') }
6    get passwordTxt() { return cy.get('#passwd') }
7    get signinBtn() { return cy.get('#SubmitLogin') }
8    get alertBox() { return cy.get('p:contains("error")') }
9    get alertMessage() { return cy.get('.alert-danger > ol > li') }
```

Problem: Selectors are hidden inside getters, so they can't be reused or reviewed in one place.

Fix: Move them to module-level constants.

```
const SIGNIN_LINK = '.login'
const EMAIL_INPUT = '#email'
const PASSWORD_INPUT = '#passwd'
const SUBMIT_LOGIN_BTN = '#SubmitLogin'
```

14. **MAJOR** cypress/e2e/pages/myAccountPage.ts:5

```
cypress/e2e/pages/myAccountPage.ts
1  /// <reference types="cypress" />
2
3  import { LoginPage } from "../loginPage"
4
5  class MyAccountPage {
6    get signoutLink() { return cy.get('.logout') }
7    get pageHeading() { return cy.get('.page-heading') }
8  }
```

Problem: There is no base page class; every page calls cy.get directly.

Fix: Add a BasePage with shared helpers and extend it.

```
export class BasePage {
  protected click(selector: string) { cy.get(selector).click() }
  protected fill(selector: string, value: string) { cy.get(selector).clear().type(value) }
}
```

15. **MAJOR** cypress/e2e/pages/myAccountPage.ts:3-18

```
cypress/e2e/pages/myAccountPage.ts
3  import { LoginPage } from "../loginPage"
4
5  class MyAccountPage {
6    get signoutLink() { return cy.get('.logout') }
7    get pageHeading() { return cy.get('.page-heading') }
8
9    public validateSuccessfulLogin() {
10      this.pageHeading.should('have.text', 'My account')
11    }
12
13    public logout() {
14      this.signoutLink.click()
15    }
16
17    public validateSuccessfulLogout() {
18      LoginPage.signinLink.should('be.visible')
19    }
19 }
```

Problem: MyAccountPage imports LoginPage and uses its locator.

Fix: Assert the logout state in the spec through LoginPage.

```
myAccountPage.logout()
LoginPage.signinLink.should('be.visible')
```

16. **MINOR** config/config.config.ts:17-20

```
config/config.config.ts
16  e2e: {
17    // We've imported your old cypress plugins here.
18    // You may want to clean this up later by importing these.
19    setupNodeEvents(on, config) {
20      return require('cypress/plugins/index.js')(on, config)
21    },
22  }
```

Problem: The bare specifier 'cypress/plugins/index.js' resolves only through tsconfig baseUrl, and the legacy plugins file is kept alive.

Fix: Inline the writer and delete cypress/plugins/.

```
import allureWriter from '@shelex/cypress-allure-plugin/writer'
setupNodeEvents(on, config) { allureWriter(on, config); return config }
```

17. MINOR config/config.config.ts:6-10

```
config/config.config.ts
4   video: true,
5   defaultCommandTimeout: 5000,
6   execTimeout: 5000,
7   taskTimeout: 5000,
8   pageLoadTimeout: 30000,
9   requestTimeout: 5000,
10  responseTimeout: 30000,
11  screenshotsFolder: 'reports/screenshots',
12  videosFolder: 'reports/videos',
```

Problem: exec/task/pageLoad timeouts are below the defaults (60000) with no reason given; request/response timeouts just repeat the defaults. There are no retries.

Fix: Delete the default-value lines and add retries.

```
retries: { runMode: 2, openMode: 0 },
```

18. MINOR package.json:8-9

```
package.json
8   "cy:open": "cypress open --config-file config/config.config.ts --env allure=true",
9   "cy:run": "cypress run --config-file config/config.config.ts --env allure=true",
```

Problem: The config file is outside the default location, so a plain `cypress open` runs without baseUrl or specPattern.

Fix: Move it to the root as cypress.config.ts and drop --config-file.

19. MINOR tsconfig.json:13-14

```
tsconfig.json
11  "exclude": ["node_modules"],
12  "include": ["**/*.ts",
13    "../node_modules/@shelex/cypress-allure-plugin/reporter",
14    "../node_modules/cypress"]
15 }
```

Problem: ../node_modules points outside the repo, so the Allure typings are never loaded.

Fix: Load them through types.

```
"types": ["node", "cypress", "@shelex/cypress-allure-plugin"]
```

20. MINOR cypress/e2e/pages/loginPage.ts:8

```
cypress/e2e/pages/loginPage.ts
8   get alertBox() { return cy.get('p:contains("error")') }
9   get alertMessage() { return cy.get('.alert-danger > ol > li') }
```

Problem: The locator is tied to visible text.

Fix: Use the CSS class.

```
get alertBox() { return cy.get('.alert-danger') }
```

21. MINOR cypress/e2e/pages/loginPage.ts:23-24

```
cypress/e2e/pages/loginPage.ts
22   public validateLoginError(errorMessage: string) {
23     this.alertBox.should('be.visible')
24     this.alertMessage.should('have.text', errorMessage)
25   }
26 }
```

Problem: Assertions live inside the page object.

Fix: The page object returns elements; specs assert.

22. **MINOR** cypress/e2e/pages/myAccountPage.ts:10

```
cypress/e2e/pages/myAccountPage.ts
9   public validateSuccessfulLogin() {
10   this.pageHeading.should('have.text', 'My account')
11   }
```

Problem: An exact have.text match is sensitive to whitespace.

Fix: Use contain.text.

```
this.pageHeading.should('contain.text', 'My account')
```

23. **MINOR** cypress/e2e/pages/loginPage.ts:1

```
cypress/e2e/pages/loginPage.ts
1  /// <reference types="cypress" />
```

Problem: Redundant triple-slash directive; tsconfig already has types: cypress. The same applies to myAccountPage.ts:1.

Fix: Delete it.

24. **MINOR** cypress/e2e/tests/login.test.ts:11-17

```
cypress/e2e/tests/login.test.ts
11  it('login with valid credentials', function () {
12    loginPage.login("testautomation@cypresstest.com", "Test@1234")
13    myAccountPage.validateSuccessfulLogin()
14    myAccountPage.logout()
15    myAccountPage.validateSuccessfulLogout()
16  })
17  it('login with valid credentials read data from fixture', function () {
18    loginPage.login(this.data.valid_credentials.emailId, this.data.valid_credentials.password)
19    myAccountPage.validateSuccessfulLogin()
20    myAccountPage.logout()
21    myAccountPage.validateSuccessfulLogout()
22  })
```

Problem: Tests 1 and 2 are the same happy path. Each login test also checks logout, so a failure doesn't say which one broke.

Fix: Keep one login test; add a separate logout test.

25. **MINOR** cypress/support/commands.js:1-6

```
cypress/support/commands.js
1  // *****
2  // This example commands.js shows you how to
3  // create various custom commands and overwrite
4  // existing commands.
5  //
6  // For more comprehensive examples of custom
```

Problem: Template comments only, no commands. The same applies to support/e2e.js. Support files are JS in a TS project.

Fix: Clean up and convert to .ts.

26. **MINOR** .gitignore:2-6

```
.gitignore
1 node_modules
2 videos
3 reports
4 screenshots
5 cypress/downloads
6 reports/**
7 allure-report/**
8 allure-results/**
```

Problem: Duplicate entries; docs/ and cypress/screenshots|videos are missing.

Fix: Clean up and add the missing entries.

```
node_modules
reports
allure-results
allure-report
docs/
cypress/screenshots
cypress/videos
cypress/downloads
```

27. **MINOR** package.json:4-5

```
package.json
4 "description": "\"Automation Testing framework using cypress and typescript with allure-report\"",
5 "main": "index.js",
```

Problem: The description has escaped quotes, main points to a missing file, and the package isn't marked private.

Fix: Fix it.

```
"description": "Cypress + TypeScript + Allure e2e framework",
"private": true,
```

28. **MINOR** package.json:33-37

```
package.json
32 "devDependencies": {
33   "@shelex/cypress-allure-plugin": "^2.28.0",
34   "@types/node": "^18.0.5",
35   "allure-commandline": "^2.18.1",
36   "cypress": "^10.3.0",
37   "typescript": "^4.7.4"
38 }
```

Problem: Cypress 10 and TS 4.7 are several majors behind (current Cypress is 16).

Fix: Update; consider the official allure-cypress adapter.

29. MINOR .github/workflows/cyAllureRun.yml:1-12

```
.github/workflows/cyAllureRun.yml
1 name: Cypress Tests using Cypress Docker Image with allure-report
2
3 on:
4   push:
5     branches: [master]
6
7 jobs:
8   Run_test:
9     runs-on: ubuntu-20.04 # Choosing OS
10    strategy:
11      matrix:
12        node-version: [14.17.0]
13        # See supported Node.js release schedule at https://nodejs.org/en/about/releases/
```

Problem: The name mentions Docker, but there's none. The single-version matrix is pointless. No workflow_dispatch, no Cypress binary cache, and the deploy action is 3.1.0 (current is v4).

Fix: Clean it up.

30. MINOR README.md:1-25

```
README.md
1 # cypress-e2e-allure# Cypress-e2e-Allure Automation-Framework with allure reports
2
3 ## **This Framework contains sample code for # Cypress-e2e-Allure Automation-Framework**
4
5 - Page Object Model
6
7 - Reading test data from json file
8
9 - Simple login scenario with valid credentials and with invalid credentials
10
11 - Allure report integration
12
13 ---
14
15 **Directory Structure**
16
17 
18
19 ---
20
21 ## **Steps to run**
22
23 - Clone the repository using "git clone "
24
25 - Change "Username" and "Password"
26
27 - npm install
28
29 - npm run cy:run
```

Problem: Two headings are merged into one line. Images are hotlinked from imgur. "Change Username and Password" doesn't say where, and the scripts aren't described.

Fix: Fix the heading, commit the images, describe setup and scripts.

31. MINOR project-wide

Problem: No ESLint/Prettier: inconsistent semicolons (login.test.ts:8 vs others). No cy.allure() annotations, so the report is flat. Thin coverage: no empty fields, forgot password or session checks.

Fix: Add a linter and formatter, Allure labels, and a follow-up coverage ticket.