

NAME: HRISHIVENDAN P

REG NO: 241801094

FINDING TIME COMPLEXITY OF ALGORITHMS

PROGRAM 1:

Question 1 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
```

```
{
```

```
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
```

```
    {
```

```
        i++;
```

```
        s += i;
```

```
    }
```

```
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include<stdio.h>
void function(int n)
{
    int count=0;
    int i=1;
    count++;
    int s=1;
    count++;
    while (s<=n)
    {
        count++;
        i++;
        count++;
        s+=i;
        count++;
    }
    count++;
    printf("%d",count);
}
```

	Input	Expected	Got	
✓	9	12	12	✓
✓	4	9	9	✓

Passed all tests! ✓

PROGRAM 2:

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
        printf("*");
    }
    else
    {
        for(int i=1; i<=n; i++)
        {
            for(int j=1; j<=n; j++)
            {
                printf("*");
                printf("*");
                break;
            }
        }
    }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  void func(int n)
3  {
4      int count=0;
5      if(n==1)
6      {
7          count++;
8          //printf("*");
9      }
10     else
11     {
12         count++;
13         for(int i=1; i<=n; i++)
14         {
15             count++;
16             for(int j=1; j<=n; j++)
17             {
18                 count++;
19                 count++;
20                 count++;
21                 //printf("*");
22                 //printf("*");
23                 break;
24             }
25             count++;
26         }
27         count++;
28     }
29     printf("%d",count);
30 }
31 int main()
32 {
33     int n;
34     scanf("%d",&n);
35     func(n);
36 }
```

	Input	Expected	Got	
✓	2	12	12	✓
✓	1000	5002	5002	✓
✓	143	717	717	✓

Passed all tests! ✓

Correct

PROGRAM 3:

Question 1 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {  
    {  
        for (i = 1; i <= num; ++i)  
        {  
            if (num % i == 0)  
            {  
                printf("%d ", i);  
            }  
        }  
    }  
}
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
1  #include<stdio.h>
2  void Factor(int num)
3  {
4      int count=0;
5      for (int i = 1; i <= num;++i)
6      {
7          count++;
8          if (num % i== 0)
9          {
10             count++;
11             //printf("%d ", i);
12          }
13          count++;
14      }
15      count++;
16      printf("%d",count);
17  }
18  int main()
19  {
20      int n;
21      scanf("%d",&n);
22      Factor(n);
23  }
```

	Input	Expected	Got	
✓	12	31	31	✓
✓	25	54	54	✓
✓	4	12	12	✓

PROGRAM 4:

Question 1 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
    int rev = 0, remainder;
    while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n /= 10;
    }
    print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

```

1  #include<stdio.h>
2  void reverse(int n)
3  {
4      int count=0;
5      int rev = 0, remainder;
6      count++;
7      count++;
8      while (n != 0)
9      {
10         count++;
11         remainder = n % 10;
12         count++;
13         rev = rev * 10 + remainder;
14         count++;
15         n/= 10;
16         count++;
17     }
18     count++;
19     //print(rev);
20     printf("%d",count);
21 }
22 int main()
23 {
24     int n;
25     scanf("%d",&n);
26     reverse(n);
27 }

```

	Input	Expected	Got	
✓	12	11	11	✓
✓	1234	19	19	✓

Passed all tests! ✓