

Rajalakshmi Engineering College

Name: Hrishivendan P

Email: 241801094@rajalakshmi.edu.in

Roll no: 241801094

Phone: 9345916829

Branch: REC

Department: I AI & DS FB

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 2

Attempt : 1

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Moniksha, a chess coach organizing a tournament, needs a program to manage participant IDs efficiently. The program maintains a doubly linked list of IDs and offers two functions: Append to add IDs as students register, and Print Maximum ID to identify the highest ID for administrative tasks.

This tool streamlines tournament organization, allowing Moniksha to focus on coaching her students effectively.

Input Format

The first line consists of an integer n , representing the number of participant IDs to be added.

The second line consists of n space-separated integers representing the participant IDs.

Output Format

The output displays a single integer, representing the maximum participant ID.

If the list is empty, the output prints "Empty list!".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

163 137 155

Output: 163

Answer

```
#include <stdio.h>
#include <stdlib.h>
```

```
// Node structure
typedef struct Node {
    int data;
    struct Node* prev;
    struct Node* next;
} Node;
```

```
// Create a new node
Node* createNode(int data) {
    Node* newNode = (Node*)malloc(sizeof(Node));
    newNode->data = data;
    newNode->prev = newNode->next = NULL;
    return newNode;
}
```

```
// Append to end
void append(Node** head, Node** tail, int data) {
    Node* newNode = createNode(data);
    if (*head == NULL) {
        *head = *tail = newNode;
    } else {
        (*tail)->next = newNode;
    }
}
```

```
        newNode->prev = *tail;
        *tail = newNode;
    }
}
```

```
// Find maximum ID
int findMax(Node* head) {
    if (head == NULL) return -1; // Indicates empty list
```

```
    int max = head->data;
    Node* current = head->next;
```

```
    while (current != NULL) {
        if (current->data > max) {
            max = current->data;
        }
        current = current->next;
    }
```

```
    return max;
}
```

```
int main() {
    int n;
    scanf("%d", &n);
```

```
    if (n == 0) {
        printf("Empty list!\n");
        return 0;
    }
```

```
    Node* head = NULL;
    Node* tail = NULL;
```

```
    for (int i = 0; i < n; i++) {
        int id;
        scanf("%d", &id);
        append(&head, &tail, id);
    }
```

```
    int maxID = findMax(head);
    printf("%d\n", maxID);
```

```
} return 0;
```

Status : Correct

Marks : 10/10