

# Rajalakshmi Engineering College

Name: Hrishivendan P

Email: 241801094@rajalakshmi.edu.in

Roll no: 241801094

Phone: 9345916829

Branch: REC

Department: I AI & DS FB

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 4

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

#### ***Input Format***

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

### **Output Format**

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

10 20 30 40 50

Output: 10 20 30 40 50

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
// Define Node structure
```

```
typedef struct Node {
```

```
    int data;
```

```
    struct Node* prev;
```

```
    struct Node* next;
```

```
} Node;
```

```
// Create a new node
```

```
Node* createNode(int data) {
```

```
    Node* newNode = (Node*) malloc(sizeof(Node));
```

```
    newNode->data = data;
```

```
    newNode->prev = newNode->next = NULL;
```

```
    return newNode;
```

```
}
```

```
// Append node at the end
```

```
void append(Node** head, Node** tail, int data) {
```

```
    Node* newNode = createNode(data);
```

```
    if (*head == NULL) {
```

```
        *head = *tail = newNode;
```

```
    } else {
```

```
        (*tail)->next = newNode;
        newNode->prev = *tail;
        *tail = newNode;
    }
}
```

```
// Display the list
void displayList(Node* head) {
    Node* current = head;
    while (current != NULL) {
        printf("%d ", current->data);
        current = current->next;
    }
}
```

```
int main() {
    int N;
    scanf("%d", &N);

    Node* head = NULL;
    Node* tail = NULL;

    for (int i = 0; i < N; i++) {
        int id;
        scanf("%d", &id);
        append(&head, &tail, id);
    }

    displayList(head);
    return 0;
}
```

**Status :** Correct

**Marks :** 10/10