SENTINEL-REMEDIATE · TRIAGE CONSOLE

A Guide to the Frontend

How the sentinel-console works, end to end: screens, data flow, live streaming, mock and live modes, the design rules, and how to change it

`frontend/` · React + TypeScript

About 1,996 lines of TypeScript · 17 feature components · 4 screens

Screenshots taken from the console running in live mode against the real gateway.

10 October 2026 · generated from repository commit `85f4d41`

How to read this guide

The **sentinel-console** is the part of the project people actually see. It shows an incident's evidence, lets you start a remediation run, and streams the agent → verifier → executor loop live. Its centrepiece is the **layered verdict**: every verification layer's decision is shown, not just the final one. It also presents the evaluation results.

The guide builds up in three passes:

- **Chapters 1–5: what the console is and how it is put together.** The stack, the folders, where each piece of state lives, and how the same code runs against fake data (mock mode) or the real backend (live mode).
- **Chapters 6–8: what happens on screen and why.** Every screen, then the live run step by step, then the VerdictCard in detail.
- **Chapters 9–14: working with the code.** The API layer, the generated types, the design rules, recipes for common changes, troubleshooting, and questions to expect in a viva.

File names are given as `src/…`, relative to `frontend/`. Each concept links to the file where it lives, so you can read the code alongside.

Contents

1 What the Console Is 1

1.1 Purpose 1

1.2 The four screens 1

1.3 Starting it 1

2 Technology Stack 2

3 Project Structure 3

4 Architecture 4

4.1 Layers 4

4.2 Where state lives 4

5 Boot Sequence, Mock Mode and Live Mode 5

5.1 What happens when the page loads 5

5.2 Mock mode 5

5.3 Live mode 5

6 The Screens, One by One 7

6.1 Queue 7

6.2 Triage 8

6.3 Results 10

6.4 Observability 11

7 The Live Run, Step by Step 12

7.1 Why EventSource and not polling 12

7.2 The stream's states 12

7.3 Reading a timeline step 13

8 The VerdictCard 14

9 The API Layer 16

10 Types Shared with the Backend 17

11 Design Rules 18

11.1 Color means decision, everywhere 18

11.2 Charts have their own palette 18

11.3 Typography, density and motion 18

12 Recipes: Changing the Console 20

13 Commands and Troubleshooting 21

14 Questions to Expect in a Viva 22

A File Reference 23

List of figures

Figure 1. Layers of the console 4

Figure 2. Ownership of state 4

Figure 3. One code path, two answerers 5

Figure 4. The Queue screen in live mode: 41 incidents served by the gateway 7

Figure 5. Triage for pod-crashloop, before a run: telemetry (logs), topology (payments-api red because an alert targets it) and run controls 8

Figure 6. The Metrics tab: restarts rising, readiness falling, errors climbing 8

Figure 7. Run controls 9

Figure 8. Results in live mode, rebuilt by the gateway from the evaluation's DuckDB rows 10

Figure 9. Observability without Grafana running: the screen explains what is missing instead of showing a broken frame 11

Figure 10. One run from click to summary 12

Figure 11. A resolved run (bad-rollout-latency, Learned, real apply) 13

Figure 12. The thesis on one screen (itbench-sre-scenario-12, Learned) 14

Figure 13. One source of truth for data shapes: the backend's Pydantic models 17

List of tables

Table 1. Screens and routes (src/App.tsx) 1

Table 2. The three ways to run the console 1

Table 3. Libraries and the job each one does 2

Table 4. The four kinds of state and their homes 4

Table 5. Environment variables (prefix VITE_ so Vite exposes them to the browser) 6

Table 6. useRunStream status values and what the timeline shows (src/api/runs.ts, LoopTimeline.tsx) 12

Table 7. Outcome pills 13

Table 8. How the VerdictCard renders a Verdict (src/features/triage/VerdictCard.tsx) 15

Table 9. Hooks, the endpoints they call and their cache keys 16

Table 10. Decision tokens (dark console theme) 18

Table 11. Frontend commands (run in frontend/ unless marked) 21

Table 12. Common problems 21

Table 13. Likely questions and short answers 22

Table 14. Every source file in frontend/src and what it is responsible for 23

1 What the Console Is

1.1 Purpose

The backend makes decisions: the agent proposes a remediation, the verifier rules on it, and the executor acts only on an `allow`. The console makes those decisions *visible*, and it was designed around the live demonstration. In about three minutes, a viewer should see:

1. an incident's evidence (logs, metrics, traces, alerts, topology), much as an on-call engineer would;
2. the agent's proposal and the verifier's verdict, **layer by layer**;
3. a destructive action that the deterministic envelope *passes* and the learned layer *blocks*. This is the project's thesis on one screen;
4. the aggregate evidence: a Pareto curve, the prevention partition, and baselines.

1.2 The four screens

Table 1. Screens and routes (`src/App.tsx`).

Screen	Route	What it is for
Queue	`/`	Every incident, with source, fault family, alert count and last outcome. Click a row to open it.
Triage	`/incidents/:id`	The main screen: evidence, topology, run controls, and the live loop trace with the layered VerdictCard.
Results	`/results`	Evaluation results: risk–autonomy Pareto chart, prevention partition, baseline metrics, ablations.
Observability	`/observability`	Embeds the Grafana dashboard of live-loop metrics, when the Docker stack is running.

1.3 Starting it

Table 2. The three ways to run the console.

Command	What you get
`cd frontend` `npm run dev`	**Mock mode** at http://localhost:5173. No backend needed: a mock server inside the browser answers every API call (§5.2). The header shows *mock mode (MSW)*.
`make demo-local` (gateway + `npm run dev:live`)	**Live mode** at http://localhost:5173, talking to the real gateway on :8080. The header shows *live gateway*. All screenshots in this guide were taken this way.
`make demo`	The full Docker stack. The console is served by nginx on :4173, alongside the gateway, Prometheus and Grafana.

2 Technology Stack

Each library was chosen for one job, and the rest of the code relies on that division of labour. Most of the "rules" in later chapters follow from this table.

Table 3. Libraries and the job each one does.

Library	Job	Why it matters here
React 18 + TypeScript (strict)	UI components, type safety	Every API payload is typed from generated types (§10), so a backend schema change breaks the build instead of the demo.
Vite	Dev server and bundler	Fast reloads. In live mode its dev server **proxies** `/api` to the gateway (`vite.config.ts`).
React Router 6	URL → screen	Four routes. The incident ID lives in the URL, so a triage page can be bookmarked and reloaded.
TanStack Query 5	**Server state** (fetch, cache, retry)	Incidents, runs and experiment tables. Cached by query key, re-fetched when told to (§4.2).
Zustand	**UI state** shared across screens	τ, the verifier choice and the dry-run flag. The τ slider in Run Controls and the τ marker on the Pareto chart are the same value.
`EventSource` (browser built-in)	The **live run stream**	Server-Sent Events: the backend pushes each loop step as it happens (§7). The console never polls.
MSW (Mock Service Worker)	Mock mode	Intercepts `fetch` and `EventSource` inside the browser and answers with fixture data (§5.2).
Tailwind CSS	Styling via design tokens	Colors are named tokens (`console-*` , `decision-*` , `accent`), never raw hex in components (§11).
Recharts	Pareto and partition charts	Results screen.
React Flow	Topology graph	Services as nodes, dependencies as edges; alerting services drawn in red.
json-schema-to-typescript	Type generation	Turns the backend's Pydantic models into `src/api/types.ts` (§10).

3 Project Structure

The code is organised **by role**. Routes are thin screens. Features hold the real components, grouped by screen. `api/` is the only place that talks to the backend. `lib/` holds pure helpers, and `mock/` holds the fake backend.

```
frontend/
├── index.html, vite.config.ts, tailwind.config.ts, tsconfig*.json, .eslintrc.cjs
├── .env.live              live mode: VITE_USE_MOCKS=false, API target, Grafana URL
├── Dockerfile, nginx.conf container build (nginx serves the app and proxies /api)
├── scripts/gen-types.mjs  JSON Schema → src/api/types.ts
├── public/                mockServiceWorker.js (MSW), shield.svg (logo)
└── src/
    ├── main.tsx           boot: start MSW if mock mode → QueryClient → <App/>
    ├── App.tsx            header, navigation, mode indicator, routes
    ├── routes/            one file per screen (thin: fetch data, lay out features)
    ├── features/
    │   ├── queue/         IncidentTable
    │   ├── triage/        TelemetryPanel, TopologyGraph, DiagnosisCard, RunControls,
    │   │                  LoopTimeline, ActionCard, VerdictCard
    │   ├── results/       ParetoChart, PreventionPartition, MetricsGrid, AblationTable
    │   └── shared/        Card, Tag, StatusDot, CodeBlock, KeyValue
    ├── api/               client.ts (fetch wrapper), incidents.ts, runs.ts,
    │                      experiments.ts (hooks), types.ts (GENERATED)
    ├── store/ui.ts        Zustand store: tau, verifierChoice, dryRun, selectedIncidentId
    ├── lib/               decisionColors.ts (one source of truth), format.ts (number for-
mats)
    ├── mock/              handlers.ts, fixtures.ts, experiments.json, browser.ts,
server.ts
    └── styles/index.css   Tailwind layers, scrollbars, focus ring, reduced-motion rule
```

The dependency rule

Data flows one way: **routes → features → api hooks → api client → network**. Components never call `fetch` directly, and nothing outside `api/` knows URLs. That is why mock mode can replace the whole backend without touching a single component.

4 Architecture

4.1 Layers




Figure 1. Layers of the console. A request always travels down through the API client. The only switch between mock and live is *who answers* at the bottom: the MSW worker, or the proxy to the gateway.

4.2 Where state lives

A frontend gets messy when the same data is kept in two places. The console avoids that with four kinds of state, each with exactly one home (Tab. 4, Fig. 2).

Table 4. The four kinds of state and their homes.

Kind	Home	Examples and rules
Server state	TanStack Query	Incident list (`["incidents"]`), one incident (`["incident", id]`), runs (`["runs"]`), experiment tables. Cached, retried once; `staleTime` 10 s; no re-fetch on window focus (`main.tsx`).
Live run	`useRunStream` (local state + `EventSource`)	The steps of the run in progress, its status and its final record. Not a Query: it is pushed, not fetched. When it finishes it *invalidates* `["runs"]` , so cached lists refresh.
Shared UI state	Zustand `useUiStore`	`tau` , `verifierChoice` , `dryRun` , `selectedIncidentId` . Shared by Run Controls and the Pareto τ marker.
Local UI state	`useState` in a component	Selected telemetry tab, whether a timeline step is expanded, the current `runId` in TriageRoute.




Figure 2. Ownership of state. Each value has one home; components subscribe to it rather than copying it.

5 Boot Sequence, Mock Mode and Live Mode

5.1 What happens when the page loads

1. `index.html` loads `src/main.tsx`.
2. `main.tsx` runs `enableMocking()`. If `VITE_USE_MOCKS` is anything other than `"false"`, it starts the MSW worker from `mock/browser.ts` and **waits** for it before rendering. This avoids a race in which the first fetch escapes to a backend that isn't there.
3. It creates one `QueryClient` (10 s stale time, one retry, no re-fetch on focus) and renders `<App/>` inside `QueryClientProvider`.
4. `App.tsx` draws the header (logo, navigation, mode indicator) and a `<Routes>` switch that mounts one screen.

5.2 Mock mode

MSW installs a **service worker** (`public/mockServiceWorker.js`) that intercepts the page's network requests and answers `/api/*` from `mock/handlers.ts`. To the rest of the app the responses look exactly like real ones, because handlers return the same JSON shapes and use the same generated types. Unmatched requests (fonts, images) pass through untouched.

- **Incidents** come from `mock/fixtures.ts`: six incidents mirroring the hand-built backend fixtures, with full telemetry for the two used in the demo.
- **Runs are simulated.** `POST /api/runs` picks a canned `RunRecord`. The stream handler then replays its steps as genuine SSE events, about 0.9 s apart, so the timeline really streams. This is a demo device, not a real orchestrator.
- **Results are measured.** `mock/experiments.json` is a snapshot of the real `make eval` output, written by `make mock-results`. Mock mode therefore shows real numbers, and the Results header says which experiment they came from.

5.3 Live mode

With `VITE_USE_MOCKS=false` (set by `.env.live`, used by `npm run dev:live`), MSW never starts and requests go to `/api` on the same origin:

- In development, Vite's proxy forwards them to `VITE_API_TARGET` (default `http://localhost:8080`).
- In Docker, nginx forwards them to the gateway with buffering off, so the SSE stream is not held back.

The same-origin `/api` path means the browser never needs CORS. The header's mode indicator reads the same variable, so you can always tell which mode you are looking at.




Figure 3. One code path, two answerers. The decision is made once, at boot.

Table 5. Environment variables (prefix `VITE_` so Vite exposes them to the browser).

Variable	Set in	Effect
`VITE_USE_MOCKS`	`.env.live`, Docker build arg	`"false"` means live mode; anything else (including unset) means mock mode.
`VITE_API_TARGET`	`.env.live`	Where the dev proxy forwards `/api` (default :8080).
`VITE_GRAFANA_URL`	`.env.live`, Docker build arg	Grafana dashboard URL for the Observability screen. If unset, the screen shows an explanation instead of a broken frame.

6 The Screens, One by One

6.1 Queue




Figure 4. The Queue screen in live mode: 41 incidents served by the gateway.

`QueueRoute` calls `useIncidents()` (`GET /api/incidents`) and hands the list to `IncidentTable`. Each row shows:

- the incident ID, in monospace because it is machine output;
- the source tag (`offline` or `itbench`);
- the fault-family tag;
- the alert count;
- a status dot.

The status comes from the latest console run of that incident: *queued* if never run, then *resolved*, *blocked* or *escalated*. Its color is a decision color (§11.1). Clicking a row calls `navigate("/incidents/<id>")`.

6.2 Triage




Figure 5. Triage for `pod-crashloop`, before a run: telemetry (logs), topology (`payments-api` red because an alert targets it) and run controls. The loop trace sits underneath.

`TriageRoute` reads `:incidentId` from the URL, loads the incident with `useIncident(id)`, and holds one piece of local state: the `runId` of the run it is showing. It passes that ID to `useRunStream(runId)`. The layout is a three-column grid: evidence and the loop trace across two columns, run controls in a narrow right column.

6.2.1 TelemetryPanel

Four tabs, held in local state:

- **Logs**: monospace, with lines containing FATAL or ERROR in the block color.
- **Metrics**: one small bar per data point, scaled to the series maximum. Bars, not a chart library, because this is a sparkline-style glance, not an analysis tool.
- **Traces** and **Alerts**: pretty-printed JSON in `CodeBlock`.

The generated types mark telemetry fields as optional (`?`). The backend defaults them to empty lists or maps but JSON Schema does not say so, so the panel normalises them once with `?? []` and `?? {}`.




Figure 6. The Metrics tab: restarts rising, readiness falling, errors climbing.

6.2.2 TopologyGraph

The topology graph is built with React Flow:

- Each service in `telemetry.topology.services` becomes a node, laid out left to right in a zig-zag.
- Each `[source, target]` pair becomes an edge.
- A service is drawn red if some alert's `target` starts with its name, so `payments-api` matches the pod `payments-api-7d9f-xk2z`.

- Edges touching a red node are animated.
- Nodes can't be dragged or connected; the graph is for reading, not editing.
- The layout is computed in `useMemo`, so it is only redone when the telemetry changes.

6.2.3 RunControls

Run Controls holds the experiment's three knobs, all stored in Zustand:

- **Verifier**: *Ungated* (`none`), *Envelope only*, *Learned* (default; works offline), *LLM-judge* and *Combined*. The last two need an API key on the gateway; without one the judge fails closed and blocks everything.
- **Risk threshold τ**: 0–1 in steps of 0.05.
- **Dry-run**: when ticked, the run ends at the first vetted plan and nothing is applied.

Start run calls `useStartRun()`, a TanStack *mutation*. On success it hands the new `run_id` up to TriageRoute. The button is disabled while a run is connecting or streaming.




Figure 7. Run controls. Hovering a verifier shows what it does.

6.2.4 DiagnosisCard

The Diagnosis card appears once a run has produced a step. It shows the latest proposal's `rationale` and `predicted_effect`, which is the agent's own account of what is wrong and what its action will do. Because the agent is an untrusted planner, the card only states its claim; the VerdictCard is where that claim is judged.

6.3 Results



Figure 8. Results in live mode, rebuilt by the gateway from the evaluation's DuckDB rows.

Four hooks fetch the four tables in parallel. The header line says where the numbers came from (*live: rebuilt from the gateway's DuckDB run store*, or the mock snapshot's experiment). If the store has no evaluation yet, the screen asks you to run `make eval` instead of showing empty charts.

- **ParetoChart**: bad-action-prevented (y) against false-block (x) across τ, one line per verifier variant.
  - Colors are keyed by **variant** (envelope blue, learned orange, judge aqua), never by position, so a missing series cannot repaint the others.
  - The **τ slider** moves a marker to the nearest swept point on each line. It is the same τ as in Run Controls.
- **PreventionPartition**: for each baseline, a stacked bar splitting destructive proposals into *missed (reached the executor)*, *caught by envelope* and *caught by judge/learned only*. "Missed" is magenta and sits first, against the baseline, where its length is easiest to compare (§11.2).
- **MetricsGrid**: resolution, bad-prevented, false-block, MTTM and cost per baseline. It is a table, not a chart, because readers compare exact values.
- **AblationTable**: rows grouped by ablation. Rates are shown as percentages; step counts as plain numbers.

6.4 Observability



Figure 9. Observability without Grafana running: the screen explains what is missing instead of showing a broken frame.

This screen embeds Grafana in an `<iframe>` when `VITE_GRAFANA_URL` is set. With `make demo`, it shows the provisioned "sentinel — live loop" dashboard: verdicts by decision, destructive actions blocked versus executed, runs by outcome, step latency and LLM spend. The rule is *embed Grafana, don't rebuild it*.

7 The Live Run, Step by Step

This is the most important flow in the console. Fig. 10 traces one click of **Start run** from the button to the run summary.




Figure 10. One run from click to summary. Steps ⑥–⑧ repeat once per orchestrator step. The browser receives each step as the backend produces it, so the timeline grows in real time.

7.1 Why EventSource and not polling

A run produces steps one at a time. Polling would either lag behind (a slow interval) or hammer the server (a fast one), and would replay steps it had already seen. Server-Sent Events invert this: the backend pushes each `StepRecord` the moment the orchestrator emits it. The browser's `EventSource` handles reconnection, and the gateway replays the full event log to a reconnecting client.

The live run is deliberately **not** a TanStack Query. It is a stream with its own lifecycle, and it touches the Query cache only once, to invalidate `["runs"]` when it finishes.

7.2 The stream's states

Table 6. `useRunStream` status values and what the timeline shows (`src/api/runs.ts` , `LoopTimeline.tsx`).

Status	When	Timeline shows
`idle`	No `runId` yet	"Start a run to see the loop trace."
`connecting`	EventSource created, not yet open	Pulsing dot: "connecting…"
`streaming`	Open; zero or more steps received	The steps so far, plus a pulsing "diagnosing next step…"
`done`	`final` event received	All steps plus the **RunSummary**
`error`	Stream failed before `final`	"Stream error — the run may still have progressed server-side."

The hook also cleans up after itself. Changing `runId` , or leaving the page, closes the previous `EventSource` in the effect's cleanup function, so old runs never write into a new timeline.

7.3 Reading a timeline step




Figure 11. A resolved run (`bad-rollout-latency`, Learned, real apply). Envelope and learned layer both allow; the rollback is applied; the summary shows *Resolved* and no unsafe execution.

Each step row shows the step index, action type and target, and an **outcome pill**. The pill is derived from the step itself by `outcomePillForStep` (Tab. 7). Clicking the row expands it to show the ActionCard and the VerdictCard. The first step, and any step that was not allowed, start expanded, because those are the steps worth reading.

Table 7. Outcome pills.

Condition	Pill	Color
verdict = block	`blocked`	block (red)
verdict = revise	`revised → retry`	revise (amber)
allowed and resolved	`applied · resolved`	allow (emerald)
allowed, not resolved	`applied · not resolved`	allow (emerald)

The **RunSummary** at the bottom carries the run's safety headline, *Unsafe action reached exec: yes/no*, along with MTTM, tokens and cost. Offline the agent and the learned verifier make no LLM calls, so tokens and cost read 0 and $0.0000.

8 The VerdictCard

The VerdictCard is the project's contribution made visible. A collapsed "BLOCK" would hide the point. The card shows the whole decision pipeline, so a viewer can see *which layer* passed an action and *which layer* caught it.




Figure 12. The thesis on one screen (`itbench-sre-scenario-12` , Learned). The envelope **allows** `cordon_node` (allow-listed, valid params, risk 35%). The LLM judge is greyed out, being inactive for this run. The learned layer **blocks** it at risk 100% against $\tau = 0.5$. Combined: Block, *never reached executor*.

Table 8. How the VerdictCard renders a `Verdict` (`src/features/triage/VerdictCard.tsx`).

Part	Rule
Header badge	The final decision (`ALLOW`, `BLOCK`, `REVISE`) in its decision color. The card's ring uses the same color.
One row per layer	Always all three, Envelope · LLM-judge · Learned, from `verdict.layers`. **Never** only the final decision.
Inactive layer	Decision `skipped` → the row at 40% opacity with "not active for this run". It is shown, never hidden, so the viewer sees which layers were in play.
Active layer	✓ Allow / ✗ Block / ↻ Revise in its decision color, the layer's risk, and (for secondary layers) the τ it was compared with.
Reasons	One per line, prefixed ↳, exactly as the backend wrote them. The learned layer's reasons are its strongest per-feature contributions, so some read as raw features (e.g. `n_params = 1`, `param_enabled = −1`, which means "no enabled flag").
Footer	*COMBINED* · *decision* plus its consequence: cleared for execution / never reached executor / returned to agent for revision.

> **How to explain Fig. 12 in one sentence**
>
> "The deterministic gate can only check structure. `cordon_node` is a legal action with valid parameters, so the envelope passes it. The learned layer sees that nothing in the telemetry points at that node, scores it as destructive, and blocks it before it reaches the executor. Run the same incident ungated and the cordon executes."

9 The API Layer

`src/api/client.ts` is a thin wrapper. `apiGet` and `apiPost` prefix `/api`, send and parse JSON, and turn a non-2xx response into an `ApiError` carrying the HTTP status. `sseUrl` builds stream URLs. Every hook is built on these three functions.

Table 9. Hooks, the endpoints they call and their cache keys.

Hook (file)	Endpoint	Kind / key
`useIncidents` (incidents.ts)	`GET /api/incidents`	Query `["incidents"]`
`useIncident(id)`	`GET /api/incidents/{id}`	Query `["incident", id]`, runs only when `id` is set
`useStartRun` (runs.ts)	`POST /api/runs`	Mutation → `{run_id}`
`useRunStream(runId)`	`GET /api/runs/{id}/stream` (SSE)	EventSource; invalidates `["runs"]` on final
`useRuns` / `useRun(id)`	`GET /api/runs`, `/api/runs/{id}`	Query `["runs"]`, `["run", id]`
`usePareto` (experiments.ts)	`GET /api/experiments/pareto`	Query `["pareto", variant]`
`useMetrics`	`GET /api/experiments/metrics`	Query `["metrics"]`
`usePreventionPartition`	`GET /api/experiments/prevention_partition`	Query `["prevention-partition"]`
`useAblations`	`GET /api/experiments/ablations`	Query `["ablations"]`

The backend also refuses some requests, and the console surfaces the reason:

- **403**: a real (non-dry-run) start when the gateway's config does not allow execution;
- **409**: the learned variant requested but no trained model exists (`make train`);
- **404**: an unknown incident or run.

10 Types Shared with the Backend




Figure 13. One source of truth for data shapes: the backend's Pydantic models.

`types.ts` defines `IncidentContext`, `Telemetry`, `ProposedAction`, `Verdict`, `LayerVerdict`, `StepRecord` and `RunRecord` exactly as the backend does. **Never edit it by hand.** When the UI needs a new field:

1. add it to the Pydantic model;
2. run `make types`;
3. let the TypeScript compiler show every place that must handle it.

Fields with defaults in Pydantic become optional (`?`) in TypeScript, which is why components write `verdict.layers ?? []`. A few response shapes are not Pydantic models, because they are tables computed by the evaluation report: `IncidentSummary`, `ParetoPoint`, `MetricsRow`, `PreventionRow` and `AblationRow`. Those are typed by hand in `mock/fixtures.ts` and must be kept in line with `gateway/api.py`.

11 Design Rules

11.1 Color means decision, everywhere

Four hues are reserved for the four outcomes. They appear on pills, verdict bands, timeline dots, status dots and Grafana panels. The tokens are defined in `tailwind.config.ts` and mapped to class names in `lib/decisionColors.ts`. Components import those class names and **never** hard-code an allow or block color.

Table 10. Decision tokens (dark console theme).

Decision	Token	Hex	Used for
allow	`decision-allow`	`#34D399`	allowed or resolved; "no" on unsafe execution
block	`decision-block`	`#F87171`	blocked, unresolved, FATAL/ERROR log lines, alerting topology nodes
revise	`decision-revise`	`#FBBF24`	revise; queued status
escalate	`decision-escalate`	`#A78BFA`	escalated to a human
accent	`accent`	`#22D3EE`	interactive elements only (buttons, active tab, slider): never a decision

11.2 Charts have their own palette

Chart series are identities (which verifier), not decisions, so they use a **separate** categorical palette. Each palette was checked with the dataviz skill's color validator against the console's actual dark card surface: lightness band, chroma, separation under color-vision deficiency, normal-vision separation and contrast.

- **ParetoChart**: envelope `#3987e5`, learned `#d95926`, judge `#199e70`, keyed by variant.
- **PreventionPartition**, stacked in this order: missed `#d55181` (magenta), caught by envelope `#3987e5`, caught by secondary `#d95926`.
  - An earlier version drew "missed" in green, which read as "good".
  - Red, amber, emerald and violet are reserved for decisions, so they were not options.
  - Magenta passes the validator only when it is not next to orange. Hence its position first, against the baseline.

11.3 Typography, density and motion

- **Monospace for anything a machine emitted**: IDs, action types, parameters, log lines, risk scores, durations. Everything else uses the sans-serif UI font.
- **Dense and dark**, like an on-call tool: compact tables, small uppercase card titles, and space reserved for the two things people read closely (the VerdictCard and the RunSummary).
- **Minimal motion**:
  - new timeline steps fade in (0.2 s);
  - the in-progress dot pulses;
  - chart animation is off, so a screenshot never catches a half-drawn bar;
  - everything is disabled under `prefers-reduced-motion`.

- **Accessibility**: a visible focus ring (accent), text labels beside every colored dot or pill, and hover titles on verifier buttons.
- **No browser storage.** UI state lives in memory (Zustand); nothing goes to `localStorage`.

12 Recipes: Changing the Console

12.1 Show a new backend field

1. Add the field to the Pydantic model in `src/sentinel/schemas/`.
2. Run `make types`. `types.ts` now has it.
3. Render it in the component, using `lib/format.ts` for numbers and monospace if it is machine output.
4. If mock mode should show it, add it to `mock/fixtures.ts`.
5. Run `npm run typecheck`, `npm run lint` and `make e2e`.

12.2 Add an endpoint and a hook

1. Add the route in `src/sentinel/gateway/api.py`, reusing the schemas.
2. Add a hook in `src/api/` with `useQuery` (reads) or `useMutation` (writes), and a distinct query key.
3. Add a matching MSW handler in `mock/handlers.ts`, so mock mode keeps working with the backend down. This is required.

12.3 Add a screen

1. Create `src/routes/XRoute.tsx`: fetch with hooks, compose features.
2. Register it in `App.tsx`: a `<Route>`, plus a `NAV_ITEMS` entry if it belongs in the header.
3. Put real components under `src/features/x/`, built from `features/shared/` (Card, Tag, StatusDot, CodeBlock).

12.4 Change a color

- **Decision colors**: change the token in `tailwind.config.ts`. Every pill, band and dot follows.
- **Chart colors**: re-run the palette validator against the console surface before changing any hex, and keep colors keyed by entity.

12.5 Refresh the numbers shown in mock mode

Run `make eval`, then `make mock-results`. The second command rewrites `mock/experiments.json` from the new results.

13 Commands and Troubleshooting

Table 11. Frontend commands (run in `frontend/` unless marked).

Command	Does
`npm install`	Install dependencies (first time only)
`npm run dev`	Mock mode at :5173
`npm run dev:live`	Live mode at :5173 (needs the gateway on :8080)
`npm run typecheck` · `npm run lint`	TypeScript check · ESLint with zero warnings allowed
`npm run build`	Production build into `dist/`
`make types` (repo root)	Regenerate `src/api/types.ts`
`make demo-local` · `make demo` (root)	Gateway + live console · full Docker stack
`make e2e` (root)	Headless-browser rehearsal of the demo; fails on any console error

Table 12. Common problems.

Symptom	Cause and fix
Header says "mock mode" when you expected live	Started with `npm run dev`. Use `npm run dev:live`, or check `VITE_USE_MOCKS`.
Live mode: incidents fail to load	The gateway is not running on :8080 (`make gateway`), or `VITE_API_TARGET` points elsewhere.
Every action is blocked with "judge unavailable"	LLM-judge or Combined chosen without an Anthropic key. The judge fails closed. Use Learned offline.
Start run returns 409	No trained learned-verifier model. Run `make train`.
Start run returns 403 with dry-run off	The gateway config doesn't allow real execution. Use `SENTINEL_CONFIG=config/offline_eval.yaml`, as `make demo-local` does.
Observability is empty	Grafana runs only in the Docker stack (`make demo`).
Type errors after pulling backend changes	A schema changed. Run `make types`.
Results says "No evaluation results"	The store has no evaluation yet. Run `make eval`.

14 Questions to Expect in a Viva

Table 13. Likely questions and short answers.

Question	Answer
Why show every layer instead of just the final decision?	The contribution *is* the layering. Showing the envelope passing an action and the learned layer blocking it is the evidence that each layer earns its place.
How does the live trace work?	Server-Sent Events. The gateway runs the orchestrator in a background thread and pushes each `StepRecord` as it is produced; the browser's `EventSource` appends it to the timeline. No polling.
Can the demo run without the backend?	Yes. In mock mode MSW intercepts `/api` in the browser and replays canned runs over real SSE. The results shown are a measured snapshot of the evaluation.
How do you keep frontend and backend in sync?	The TypeScript types are generated from the Pydantic models (`make types`). A schema change fails the TypeScript build instead of failing silently at runtime.
Why TanStack Query *and* Zustand?	They hold different things. Query caches server data with refetch and retry; Zustand holds a few UI values shared across screens, such as τ in both Run Controls and the Pareto marker.
Why is "missed" magenta in the partition chart?	Green read as "good"; red, amber, emerald and violet are reserved for decisions. Magenta passed the color-vision validator only when placed away from orange, so it sits first, against the baseline.
Can the console execute something unsafe?	No. It only *requests* runs. The gateway refuses real execution unless its config allows it, the executor requires an `allow` verdict, and human approve/reject decisions are recorded for audit but never execute anything.
How do you know the demo works?	`make e2e` drives a headless browser through the demo against the real gateway: happy path, blocked cordon, ungated execution, results. It fails on any browser console error.

A File Reference

Table 14. Every source file in `frontend/src` and what it is responsible for.

File	Responsibility
`main.tsx`	Boot: start MSW in mock mode, create the QueryClient, render App
`App.tsx`	Header, navigation, mode indicator, route table
`routes/QueueRoute.tsx`	Incident list screen
`routes/TriageRoute.tsx`	Incident screen; owns `runId`; wires `useRunStream`
`routes/ResultsRoute.tsx`	Results screen; data source line; empty state
`routes/ObservabilityRoute.tsx`	Grafana iframe, or an explanation if it is not configured
`features/queue/IncidentTable.tsx`	Clickable incident table with tags and status dots
`features/triage/TelemetryPanel.tsx`	Logs, metrics, traces and alerts tabs
`features/triage/TopologyGraph.tsx`	React Flow service graph; alerting services in red
`features/triage/DiagnosisCard.tsx`	Latest proposal's rationale and predicted effect
`features/triage/RunControls.tsx`	Verifier, τ, dry-run; Start run mutation
`features/triage/LoopTimeline.tsx`	Streaming step list, outcome pills, RunSummary
`features/triage/ActionCard.tsx`	One proposed action: type, target, params
`features/triage/VerdictCard.tsx`	Layered verdict (Chapter 8)
`features/results/ParetoChart.tsx`	Pareto lines keyed by variant, τ marker
`features/results/PreventionPartition.tsx`	Stacked partition bars (validated palette)
`features/results/MetricsGrid.tsx`	Baseline metrics table
`features/results/AblationTable.tsx`	Grouped ablation rows
`features/shared/*`	Card, Tag, StatusDot, CodeBlock, KeyValue building blocks
`api/client.ts`	`apiGet`, `apiPost`, `sseUrl`, `ApiError`
`api/incidents.ts · runs.ts · experiments.ts`	Hooks (Tab. 9); `useRunStream` lives in runs.ts
`api/types.ts`	GENERATED shared types: never edit
`store/ui.ts`	Zustand UI store and the `VerifierChoice` type
`lib/decisionColors.ts`	Decision → classes and labels; step-state labels
`lib/format.ts`	Formatting of durations, tokens, USD, risk and percentages
`mock/handlers.ts`	MSW handlers for every endpoint, including simulated SSE
`mock/fixtures.ts · experiments.json`	Mock incidents and canned runs · measured results snapshot
`mock/browser.ts · server.ts`	MSW worker (browser) · MSW server (for future Node tests)
`styles/index.css`	Tailwind layers, scrollbars, focus ring, reduced motion