

## Jenkins Class – 4

In the devops cycle we have Plan, Code, Build, Test, deploy, monitoring.


We already know till test the code. So now we have to deploy the code in server.

Tomcat is one of the deployment servers. We need to create new instance for deploy the code. Once build the code in maven, we will get the war file. We should deploy it to the application server.

Before create tomcat application server we have to create the code and host it in public/private repository then build the code by maven.


So, we need to install maven in current instance with java1.8.0. Now go to the Jenkins then configure it as follow below steps.

1. Add the github repo link in GitHub project.




The screenshot shows the 'Add New Project' dialog in Jenkins. The 'GitHub project' option is selected with a checkmark. The 'Project url' field is populated with 'https://github.com/yogitech2000/one.git'. There is an 'Advanced' dropdown menu at the bottom.

2. Add the SCM (Source Code Management) url. If the instace doesn't install git we will get the below error. After install the git in aws instance where the Jenkins has been installed the git error will disappear.




The screenshot shows the 'Git' configuration page in Jenkins. The 'Repository URL' field contains 'https://github.com/yogitech2000/one.git'. Below the field, there is a red error message: 'Failed to connect to repository : Error performing git command: git ls-remote -h https://github.com/yogitech2000/one.git HEAD'. The 'Credentials' dropdown is set to '- none -'. There is an 'Add' button and an 'Advanced' dropdown menu.

3. Select the branch.




The screenshot shows the 'Branches to build' section in Jenkins. The 'Branch Specifier (blank for \'any\')' field is populated with '\*/master'.

4. Select the build tool in build steps. We are using maven to build the code. So we have to choose the **Invoke top-level Maven targets**.



Then enter the maven command in goals field. We have a command to build the code in single command which is **mvn clean package**. but we can ignore **mvn** command because we already selected the maven tool in build steps.



Before build the job make sure that **git and maven with java 1.8.0 has been installed**. If you did not install maven we will get the below error in console log and job also will not build.

```
Build step 'Invoke top-level Maven targets' marked build as failure  
Finished: FAILURE
```

After build the job we can see the **target** folder in **workspace** of the Jenkins job. Now we have war file. So we should deploy it on the tomcat application server.

Now we need to launch new instance then follow the below steps.

Tomcat will work all either java 1.8.0 or java 11. But java is must to be run tomcat.

Tomcat is the one of the product of apache. So we can get the tomcat file form the apache website follow by the link <https://dldcn.apache.org/tomcat/> . select the tomcat version from there and click on the bin folder finally we will have the **.tar.gz** file, then copy the link address of the tomcat file. Then execute the below command in instance.

wget <https://dldcn.apache.org/tomcat/tomcat-9/v9.0.82/bin/apache-tomcat-9.0.82.tar.gz>

Now the file has been downloaded and need to extract the tar file by follow the below command

**tar -zxvf <file\_name>.tar.gz** (to unzip the tar file)

now you will have a folder and tar file.


```
[root@ip-172-31-28-125 ~]# ll
total 11448
drwxr-xr-x 9 root root      220 Oct 15 14:10 apache-tomcat-9.0.82
-rw-r--r-- 1 root root 11721126 Oct 11 13:34 apache-tomcat-9.0.82.tar.gz
```

After unzipped the tar file need to start the tomcat by run the startup.sh file. Go to the path


**cd apache-tomcat-9.0.82/bin/** then run the startup.sh file by the command **./startup.sh**

the tomcat is started. **<Public IP of the instance>:8080**. Ex , **54.167.91.182:8080**.

The Tomcat will look like the below pic.



If we launch the manage app. We will get the below error.



To resolve it follow the instructions over there.

By default the Manager is only accessible from a browser running on the same machine as Tomcat. If you wish to modify this restriction, you'll need to edit the Manager's `context.xml` file.

To find the context.xml file follow the below commands.

1. We to update the DB before find the file. – **updated**
2. To find the context.xml file – **locate context.xml**


```
[root@ip-172-31-28-125 bin]# locate context.xml
/root/apache-tomcat-9.0.82/conf/context.xml
/root/apache-tomcat-9.0.82/webapps/docs/META-INF/context.xml
/root/apache-tomcat-9.0.82/webapps/examples/META-INF/context.xml
/root/apache-tomcat-9.0.82/webapps/host-manager/META-INF/context.xml
/root/apache-tomcat-9.0.82/webapps/manager/META-INF/context.xml
```

As per the instruction we need to edit the manager's context.xml file. Open it in vim.

Now remove the following two lines by using vim editor commands.

```
<Context antiResourceLocking="false" privileged="true" >
  <CookieProcessor className="org.apache.tomcat.util.http.Rfc6265CookieProcessor"
    sameSiteCookies="strict" />
  <Valve className="org.apache.catalina.valves.RemoteAddrValve"
    allow="127\.\d+\.\d+\.\d+|::1|0:0:0:0:0:0:0:1" />
  <Manager sessionAttributeValueClassNameFilter="java\.lang\.(?:Boolean|Integer|Long
ed)?HashMap"/>
</Context>
```

After delete the lines we'll get the login popup notification.



Now click on cancel. Again, we will get instruction page to fix it. Because we didn't set any credential yet. So we need to set the credentials by follow the instruction showing on the page.

You are not authorized to view this page. If you have not changed any configuration files, please examine the file `conf/tomcat-users.xml` in your installation. That file must contain the credentials to let you use this webapp.

For example, to add the `manager-gui` role to a user named `tomcat` with a password of `s3cret`, add the following to the config file listed above.

```
<role rolename="manager-gui"/>
<user username="tomcat" password="s3cret" roles="manager-gui"/>
```

Note that for Tomcat 7 onwards, the roles required to use the manager application were changed from the single `manager` role to the following four roles. You will need to assign the role(s) required for the functionality you wish to access.

- `manager-gui` - allows access to the HTML GUI and the status pages
- `manager-script` - allows access to the text interface and the status pages
- `manager-jmx` - allows access to the JMX proxy and the status pages
- `manager-status` - allows access to the status pages only

The HTML interface is protected against CSRF but the text and JMX interfaces are not. To maintain the CSRF protection:

- Users with the `manager-gui` role should not be granted either the `manager-script` or `manager-jmx` roles.
- If the text or jmx interfaces are accessed through a browser (e.g. for testing since these interfaces are intended for tools not humans) then the browser must be closed afterwards to terminate the session.


For more information - please see the [Manager App How-To](#).

add the below 3 lines in last line of the file.

```
<role rolename="manager-gui"/>
<role rolename="manager-script"/>
<user username="tomcat" password="1234" roles="manager-gui, manager-script"/>
```

Now save it by using :wq.

After edit we need to restart the tomcat by executing shutdown.sh and startup.sh files.




The screenshot shows the Tomcat Web Application Manager interface. At the top, there's a message box with "OK". Below it, a navigation bar includes "List Applications", "HTML Manager Help", "Manager Help", and "Server Status". The main section is titled "Applications" and contains a table with columns: Path, Version, Display Name, Running, Sessions, and Commands. The table lists several applications: "/", "/docs", "/examples", "/host-manager", and "/manager". Each application row has a "Start" button, a "Stop" button, a "Reload" button, and an "Undeploy" button. Additionally, there are "Expire sessions" and "with idle ≥ 30 minutes" links for each application.

Path	Version	Display Name	Running	Sessions	Commands
/	None specified	Welcome to Tomcat	true	0	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes
/docs	None specified	Tomcat Documentation	true	0	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes
/examples	None specified	Servlet and JSP Examples	true	0	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes
/host-manager	None specified	Tomcat Host Manager Application	true	0	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes
/manager	None specified	Tomcat Manager Application	true	1	Start Stop Reload Undeploy Expire sessions with idle ≥ 30 minutes


After launched the tomcat application server, we can deploy our source code to the application server.

Now we need to install the **Deploy to container** plugin.




The screenshot shows the "Deploy to container" plugin installation page. It features a blue checkmark icon in a circle. The text "Deploy to container 1.16" is displayed in blue. Below it, the text "Artifact Uploaders" is shown in a light blue box. The main description reads: "This plugin allows you to deploy a war to a container after a successful build. Glassfish 3.x remote deployment".

Then open Jenkins and edit the configure of the job. If you install the Deploy to container then only it'll reflect in the **Deploy war/ear to a container** option. Select it.




We have the war file in **target** folder, right? So, we need to enter the folder name and war file name. we can use **\*.war** which is all the files contains .war extension. So, we can simply use the **\*.war** format.




We give the details of the folder and file name as well. But we didn't mention the which tool we have to use for deploy in it. So we need to declare it in the containers field.

We took the tomcat 9x version so we need to select the tomcat 9x.



After select the Tomcat 9x. you will get the new fields to fill. Here we need to add the tomcat credentials to login this Jenkins.



Here we need to fill the credentials of the Tomcat which username and password has set in the **conf/tomcat-users.xml** file.

**Jenkins Credentials Provider: Jenkins**

**Add Credentials**

Domain  
Global credentials (unrestricted) ▼

Kind  
Username with password ▼

Scope ?  
Global (Jenkins, nodes, items, all child items, etc) ▼

Username ?

☐ Treat username as secret ?

After put the credentials in this field we can see the credentials as a choice.

**Containers**

≡ **Tomcat 9.x Remote**

Credentials

- none - ▼

- none -

tomcat/\*\*\*\*\*\*

Then enter the tomcat URL till 8080/.

**Containers**

≡ **Tomcat 9.x Remote**

Credentials

tomcat/\*\*\*\*\*\*

Add ▼

Tomcat URL ?

After build the job our code has been deployed to the tomcat application server.

Tomcat Web Application Manager

Message:  OK

Manager

List ApplicationsHTML Manager HelpManager HelpServer Status

Applications

Path	Version	Display Name	Running	Sessions	Commands
/	None specified	Welcome to Tomcat	true	0	<div>StartStopReloadUndeploy</div> <div>Expire sessions with idle ≥ 30 minutes</div>
firstApp	None specified	Archetype Created Web Application	true	0	<div>StartStopReloadUndeploy</div> <div>Expire sessions with idle ≥ 30 minutes</div>
/docs	None specified	Tomcat Documentation	true	0	<div>StartStopReloadUndeploy</div> <div>Expire sessions with idle ≥ 30 minutes</div>
/examples	None specified	Servlet and JSP Examples	true	0	<div>StartStopReloadUndeploy</div> <div>Expire sessions with idle ≥ 30 minutes</div>
/host-manager	None specified	Tomcat Host Manager Application	true	0	<div>StartStopReloadUndeploy</div> <div>Expire sessions with idle ≥ 30 minutes</div>
/manager	None specified	Tomcat Manager Application	true	1	<div>StartStopReloadUndeploy</div> <div>Expire sessions with idle ≥ 30 minutes</div>

http://tomcat.apache.org



Whenever we build the job it will store in Jenkins as well. We can see the logs in the path  
**`/var/lib/jenkins/jobs/<job_name>/builds/<build_number>`**