

HTML5 Structural Elements

Chapter-3

HTML5 Structural Elements

- div element
- header element
- nav element
- main element
- footer element

Div element

- The div element configures a structural area or “ on a web page as a block display with empty space above and below
- A div element begins with a `<div>` tag and ends with a `</div>` tag.

header element

- the HTML 5 header element is to contain the headings of either a web page document or an area within the document such as a section or article
- begins with the `<header>` tag and ends with the `</header>` tag

HTML5 nav element

- Contain a section of navigation links
- Begins with the `<nav>` tag and ends with the `</nav>` tag

HTML5 main element

- contain the main content of a web page document
- There should be only one main element per web page
- begins with the `<main>` tag and ends with the `</main>` tag

HTML5 footer element

- contain the footer content of a web page or section of a web page
- begins with the `<footer>` tag and ends with the `</footer>` tag

Sample Code

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Trillium Media Design</title>
</head>
<body>
  <header>
    <h1> Trillium Media Design</h1>
  </header>
  <nav>
    <b>Home &nbsp;  Services &nbsp;  Contact</b>
  </nav>
```

```
<main>
  <h2>New Media and Web Design</h2>
  <p>Trillium Media Design will bring your
company's Web presence to the next level. We
offer a comprehensive range of services.
</p>
  <h2>Meeting Your Business Needs</h2>
  <p>Our expert designers are creative and eager to work
with you.
</p>
</main>
<footer>
  <small><i>Copyright &copy; 2016 Your Name Here
</i></small>
</footer>
</body>
</html>
```

Anchor Element

- Used to create hyperlinks to web pages or files.
- begins with an `<a>` tag and ends with a `</a>` tag.
- The text between the opening and closing tags is the clickable link.
- the href attribute configures the hyperlink reference, which identifies the name and location of the file to access.

```
<a href="http://webdevfoundations.net">Web Development & Design  
Foundations</a>
```

absolute hyperlink

- An absolute hyperlink indicates the absolute location of a resource on the Web.
- Use absolute hyperlinks when you need to link to resources on other websites.
- The href value for an absolute hyperlink to the home page of a website includes the http:// protocol and the domain name.

```
<a href="http://webdevfoundations.net">Web Development & Design  
Foundations</a>
```

Sample Code

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <title>Anchor Example</title>
    <meta charset="utf-8">
  </head>
  <body>
    <a href= "http://www.webdevfoundations.net">
      Web Development & Design Foundations </a>
  </body>
</html>
```

relative hyperlink

- When you need to link to web pages within your site, use a relative hyperlink.
- The href value for a relative hyperlink does not begin with the http:// and does not include a domain name.

```
<a href="contact.html">Contact Us</a>
```

Contact.html File သည်ယခု html နှင့် folder တစ်ခုထဲတွင်ရှိ နေရမည်။

e-mail hyperlinks

- The anchor tag can also be used to create e mail hyperlinks
- An e mail hyperlink will automatically launch the default mail program configured for the browser
- Pre fills the recipient's email address
- Uses mailto:

```
<a href="mailto:help@terrymorris.net">help@terrymorris.net</a>
```

Next Lecture

Configuring Color and Text with CSS